

# SF61B



## Rugged 2D Pocket Scanner

Designed to provide the highly mobile worker with performance scanning in an extremely compact and rugged package, the SF61B integrates with existing data capture workflows and easily pairs with Apple® iOS, Android™, and Windows Mobile® smartphones and tablets.



*The robust scanning performance of SF61B is complemented with equally impressive communication and battery performance.*

With its unique form factor and magnetic quick attach/release system, workers can accomplish their data collection tasks with more efficiency, safety, and agility than ever before. Traditional gun-shaped scanners weren't made for the worker on the go. To address this, we designed the SF61B so that it can be quickly accessed or securely stowed away as needed. A magnetic quick disconnect system and variety of smart accessories make it easy to rapidly access the device when needed – and just as quick to securely stow away when unencumbered use of both hands is needed

Despite its compact size, the SF61B packs the same high performance 2D imagers as our full-size handheld scanners. With unmatched motion tolerance (up to 500 in/sec) and omni-directional reading capability, the SF61B keeps up with your workers on the go by delivering incredible scan speed at any angle.

An integrated Bluetooth® Class 1 radio enables wireless communication at ranges up to 100 m (325 ft), and the field-replaceable lithium-ion battery lasts well beyond a full shift, even in the most scan-intensive applications. The SF61B offers performance characteristics commonly found in full-size scanners, at just a fraction of their size and weight.

## FEATURES AND BENEFITS



### SPEED

Compact form factor and available quick attach/release system enable rapid, on-demand scanning.



### SCANNING

Includes the industry's fastest 2D imaging technology for snappy, omni-directional scanning.



### RADIO

Bluetooth wireless easily pairs with Apple iOS, Android, and Windows Mobile devices.



### RUGGED

Tested to withstand 26 drops to concrete from 2 m (6.5 ft) and rated IP65 for protection from liquid and dust ingress.



### BATTERY

Field-replaceable battery lasts well beyond a full shift, even in scan-intensive applications.



# SF61B Technical Specifications



## PHYSICAL CHARACTERISTICS

**Dimensions with Magnet End-Cap (L x W x H):**  
15.6 cm x 4.6 cm x 3.9 cm (6.1 in x 1.8 in x 1.5 in)  
**Dimensions with Ring End-Cap (L x W x H):**  
16.0 cm x 4.6 cm x 3.9 cm (6.3 in x 1.8 in x 1.5 in)  
**Weight:** 184 g (6.5 oz)

## ELECTRICAL SPECIFICATIONS

**Battery:** Lithium-ion rechargeable (2,600 mAh)  
**Battery Life<sup>1</sup>:** 25,000 scans (2D), with 1 scan every 4 seconds<sup>2</sup>  
**Recharging Time:** 3 hours

<sup>1</sup> Battery life varies depending on ambient temperature, ambient light, and battery life.  
<sup>2</sup> Typical number of scans possible without a battery recharge, in a typical office environment (250 lux) at ambient temperature.

## BLUETOOTH RADIO

**Type:** Bluetooth Class 1 v2.1+EDR  
**Frequency:** 2.4 GHz with Adaptive Frequency Hopping  
**Range:** 100 m (325 ft) in open space, 30 m (100 ft) in typical work environment  
**Profiles:** HID, SPP

## CONNECTIVITY

**Operating System Compatibility:** Apple iOS; Android; Microsoft Windows®

## SCAN TECHNOLOGY

Honeywell 2D Imager with Laser Aimer (EA30)

## READING PERFORMANCE

**Maximum Code Resolution:** 6.6 mils  
**Print Contrast:** 20%  
**Motion Tolerance, HP:** Up to 500 in/s

## USER FEEDBACK

- Indication LED
- Configurable Buzzer
- Configurable Vibrator (Haptic Feedback)

## BARCODE SYBLOGIES (SF61BHP)

Codabar, Code 11, Code 39, Code 93/93i, Code 128 / GS1-128, EAN/UPC, GS1 DataBar Limited, GS1 Composite (linear only), GS1 DataBar Expanded, GS1 DataBar Limited, GS1 DataBar Omni-directional, GS1 DataBar Stacked, Interleaved 2 of 5, Matrix 2 of 5, MSI, Plessey, Standard 2 of 5, Telepen, DataMatrix, QR Code, Micro QR, PDF417, Micro PDF417, Aztec, Maxicode, Han Xin, Codablock A, Codablock F, GS1 Composite, TLC 39, and Postal Codes (Australian Post, BPO, Canada Post, Dutch Post, Infomail, Intelligent Mail, Japan Post, Planet, Postnet, Sweden Post)

## ENVIRONMENT

**Operating Temperature:** -20°C to +50°C (-4°F to +122°F)  
**Storage Temperature:** -40°C to +70°C (-40°F to +158°F)  
**Charging Temperature:** 0°C to 45°C (32°F to 113°F)  
**Relative Humidity:** 5% to 95% non-condensing  
**Drop:** 26 drops from 2 m (6.5 ft) to concrete  
**Environmental Rating:** IP65  
**Ambient Light:** 0 to 100,000 lux

## STANDARD WARRANTY

Three-year standard warranty, with extended protection available through Honeywell Edge Services

## ACCESSORIES

View the SF61B Accessories Guide for complete details on charging options and accessories.

TYPICAL READING DISTANCES <sup>3</sup> SF61BHP			
SYBLOGY	DENSITY	MIN. DISTANCE	MAX. DISTANCE
Code 39	0.1 mm (4 mils)	5 cm (1.97 in)	22 cm (8.66 in)
	0.125 mm (5 mils)	4 cm (1.57 in)	27 cm (10.63 in)
	0.5 mm (20 mils)	6 cm (2.36 in)	71 cm (27.95 in)
	1 mm (40 mils)	14 cm (5.51 in)	125 cm (49.21 in)
EAN/UPC	0.33 mm (13 mils)	5 cm (1.97 in)	47 cm (18.50 in)
PDF417	0.25 mm (10 mils)	4 cm (1.57 in)	27 cm (10.63 in)
	0.38 mm (15 mils)	4 cm (1.57 in)	36 cm (14.17 in)
DataMatrix	0.25 mm (10 mils)	6 cm (2.36 in)	22 cm (8.66 in)

<sup>3</sup> The reading distances for each scanner are typical distances measured from the front end of the scanner bezel in an office environment (200 lux) with extended reading range activated (if applicable).

For a complete listing of all compliance approvals and certifications, please visit [www.honeywellaidc.com/compliance](http://www.honeywellaidc.com/compliance).  
For a complete listing of all supported barcode symbologies, please visit [www.honeywellaidc.com/symbologies](http://www.honeywellaidc.com/symbologies).  
Android is a trademark or registered trademark of Google LLC.  
Apple is a trademark or registered trademark of Apple Inc.  
Bluetooth is a trademark or registered trademark of Bluetooth SG, Inc.  
Windows and Windows Mobile are trademarks or registered trademarks of Microsoft Corporation.  
All other trademarks are the property of their respective owners.



Zapraszamy do kontaktu!  
Więcej informacji: [www.kreski.pl](http://www.kreski.pl)

**For more information**  
[www.honeywellaidc.com](http://www.honeywellaidc.com)

**Honeywell Safety and Productivity Solutions**  
9680 Old Bailes Road  
Fort Mill, SC 29707  
800-582-4263  
[www.honeywell.com](http://www.honeywell.com)

