



MS652 / MS652+

Wearable 2D Ring Scanner



unitech electronics today introduced the new 2D ring scanner to its industry-leading wearable portfolio: MS652 series, features wearable design that gives users freedom of movement to perform barcode scanning tasks comfortably while keeping both hands free. The MS652 series is designed to streamline the workflow for a wide range of applications such as retail, logistics, field service and hospitality.

Ergonomic design for mobile operators

The MS652 series wearable 2D ring scanner enables its operator to move products, packages, materials and proceed with their barcode reading tasks more efficiently, safely and comfortably. Whether you prefer left or right-handed operation, users can instantly switch between right and left hand operation with the special one push rotate design. It improves productivity in your operations with the wearable technology.

Ultimate 2D wireless ring scanner

Featuring a superior scan engine, MS652 series is available to scan most 1D, 2D and PDF417 barcodes printed on paper labels or displayed on the screen of a mobile phone. The Bluetooth® 4.2 and NFC technology delivers the most efficient way to pair with smart phone and tablets (including iOS or android system) with just a touch. Moreover, the wireless technology keeps the scanner connected up to 10 m (30 ft) from the computer, increasing productivity by allowing workers to move to the task. The MS652 series can be utilized with an auto mode that ensures no data is lost while it is out of range of the wireless signal, also upload the data to the back-end system automatically when it gets back in range, allowing users to complete their tasks without interruption.

Small but Durable

The MS652 series is small but extremely rugged which supports IP42 protection against water and dust as long as 1.5 meters drop-resistant housing. In addition, the MS652 series is built in changeable and rechargeable battery pack that allows users to improve your work productivity at work. With an ergonomic and compact design, the MS652 series 2D ring scanner delivers users powerful way to improve efficiency to the next level.

Features

- Lightweight and unique wearable ring design
- One push rotate design allows right and left hand operation switch easily.
- Available to read 1D, 2D and PDF417 barcodes
- Bluetooth® 4.2 wireless design with 10M operation range
- Rugged and durable design with IP42 and 1.5m drops
- Bluetooth® to NFC pairing : Easily pair to smart phones and tablets (Including iOS/ Android devices)
- Changeable and rechargeable battery pack.
- Full Shift Battery Life: Up to 13 Hours
- Mounted on two fingers to enhance the operation stability.
- Larger flash memory storage with 7.5 MB built-in USB drive (store up to store up to 590,000 of EAN13 codes)
- Easier scanner configuration, data access and firmware upgrade via built-in USB drive

Kreski

unitech
because we care



MS652 / MS652+

Specifications

Functionality

Symbologies

1D: All major symbologies and PDF417

2D: QR Code, Data Matrix, Aztec Code, PDF417, Macro PDF417, Micro PDF417, MaxiCode, Coda block A, Codablock F, GS1Composite, Han Xin Code, Australian Post, British Post, Canadian Pos, InfoMail, Intelligent Mail Bar Code, Japanese Post, KIX (Netherlands) Post, GS1 Composite, Korea Post, Planet Code, Postal, Postnet

Operation Mode

Trigger mode, Presentation mode, Auto mode, Batch mode

Data Formatting

Prefix, Suffix, Code ID, Reformatting Date

Electrical

Operation Voltage

DC 5V +/- 10%

Current Consumption

Operation mode: 160mA, Standby mode: 23mA
Power off mode 1uA

RTC backup time

Support main battery replacement to keep RTC data within 5 mins.

Battery Type

Rechargeable Lithium-ion

Battery Capacity

800mAh / 3.7V

Charging Time

Fully charged in 4 hours

Operating Time

14 hours at 1 scan / 5 secs with good reading beep sound.

Charging Method

USB Cable or Battery Charging cradle

Environmental

ESD Protection

Functional after 8K Contact and 12K Air

Mechanical Shock

1.5M onto concrete (scanner only)

Operating Temperature

-10°C to 50°C

Storage Temperature

-20°C to 60°C

Relative Humidity

95% non-condensing

IP Rating

IP42

Accessories

Battery

Hand strap

Micro USB cable

Single slot cradle

4-Slot battery charger (optional)

5-Slot charging cradle

What comes in the box

MS652 Scanner with trigger module

Battery

USB charger cable

Wrist strap

Finger rubber pad

Two double sided tapes



Single slot cradle



4-Slot battery charger (optional)



5-Slot charging cradle

System

Connection

Connect to host with Windows, Android, or iOS

Memory

7.5Mbytes, store up to 590,000 of EAN13 codes

Keys

1 Scan Button

Optical & Performance

Scan Engine

Zebra SE2707

Sensor

CMOS sensor with 640 x 400 pixel

Light Source

1 Hyper Red 660nm LED

Ambient Light

Max 107, 639 lux (direct sunlight)

Skew Angle

60 degrees

Pitch Angle Sensor

60 degrees

Printing Contrast Scale

minimum 20%

Depth of Field

(DOF PCS=80%)

SYMBOLGY / X-DIM TYPICAL RANGE*

Near

Far

5 mil Code 39 2.0 in / 5.1 cm 6.4 in / 16.2 cm

5 mil Code 128 2.5 in / 6.3 cm 5.0 in / 12.7 cm

6.6 mil PDF417 2.5 in / 6.3 cm 6.3 in / 16.0 cm

10 mil PDF417 1.8 in / 4.5 cm* 9.0 in / 22.8 cm

13 mil 100% UPC 2.0 in / 5.0 cm* 12.5 in / 31.7 cm

20 mil Code 39 2.0 in / 5.0 cm* 19.5 in / 49.5 cm

20 mil Data Matrix 1.5 in / 3.8 cm 13.5 in / 34.3 cm

20 mil QR Code 1.5 in / 3.8 cm 11.0 in / 27.9 cm

Communication

Radio

MS652 : Bluetooth® 4.2

MS652+ : Bluetooth® 4.2

Bluetooth® V2.1

Range

30ft/10M (line of sight)

Host Interface supported

USB

Protocol

HID / SPP (MS652+)

Mechanical

Scanner Dimension

50 x 71 x 21 mm

Scanner Weight

95g

Trigger Switch Life

1 million times

Regulatory Approvals

CE, FCC, BSMI, VCCI, TELEC, NCC



Headquarters

Taipei, Taiwan

<http://www.ute.com> e-mail: info@hq.ute.com

unitech America

Los Angeles

<http://us.ute.com> e-mail: info@us.ute.com

<http://can.ute.com> info@can.ute.com

Mexico

<http://latin.ute.com> e-mail: info@latin.ute.com

unitech Asia Pacific & Middle East

Taipei

<http://apac.ute.com> info@apac.ute.com / info@india.ute.com

<http://mideast.ute.com> info@mideast.ute.com

unitech Europe

Tilburg / Netherlands

<http://eu.ute.com> e-mail: info@eu.ute.com

unitech Japan

Tokyo

<http://jp.ute.com> e-mail: info@jp.ute.com

unitech Greater China

Beijing, Shanghai, Guang Zhou, Xiamen

<http://cn.ute.com> info@cn.ute.com

Taipei <http://tw.ute.com> info@tw.ute.com



www.ute.com

01/19 Rev.B