

Affordable, worry free wireless 1D scanning capabilities

Looking for an affordable solution for 1D wireless scanning? The MS351 is designed to remove restrictions!

Reliable allrounder

Our affordable MS351 fits into many environments, whether it is retail, warehousing or manufacturing. There is no need to worry about missing a barcode reading as this Unitech scanner provides additional vibration feedback. A great feature beside the standard LED and beeper indicator - pretty ideal when working in a noisy environment.

The MS351 enables you to remove wired restrictions in your working environment. Moreover, its interface is also suitable for different applications, making this a widely applicable product to use.

Robust and powerful

The MS351 is not only widely applicable thanks to its software versatility, it is also suitable for rough environments thanks to its impressive drop resistance. It has an IP52 rating, safeguarding it from moisture and dust.



Successful scanning can be achieved by its long reading distance. This scanner is capable to read barcodes under high ambient light environments. The MS351 makes barcode reading in busy working environments easy and allows users to be assured that they have captured each and every barcode.

Connectivity and durability

The sturdy materials, reading performance combined with a 2600 mAh LI-ION battery and a durable trigger makes the MS351 an incredible value-for-money option for many environments. Reading long 1D barcodes used for utility bills, packaging or even document processing, you can rely on the MS351.

Its Bluetooth connectivity and wide host range (30 meters), provide high transmission speed and freedom of movement.

Features

- 1D Laser engine
- Large 2600 mAh Li-ION battery
- LED, beeper and vibration indicator
- Connectivity with Dual Band BLE 4.2
- Durable construction with protection bumpers
- Comprehensive 4-year, worry-free warranty





Operational & Performance

Technology Light Source Decoding rate Scan angle Minimum resolution Printing contrast Programming Method Program Upgrade

1D Laser engine Visible Laser Diode 650nm 200 scans/sec Skew 60°, Pitch 65°, Roll 42°

3 mil 20% min. reflection difference

Manual (reading special barcode) Using Flash Utility software, while a cradle unit is required.

Standby Time Operating Time

Battery

Power Source

Operating voltage

Current scanner

Current cradle

Charge Time

Enclosure Scanner dimension Cradle dimension Scanner weight Cradle weight

90.2 x 70 x 180 mm 118 x 89.5 x 74 mm 207 g (Scanner only)

Working: 60 mA

6 hours

7 days

Charging: max. 500 mA

 5 ± 0.25 VDC (Scanner/Cradle)

2600 mAh Lithium-ion battery

Working: 150 mA / Standby: 4mA

36 hours (1 scan per 5 seconds)

140 g

Reading distance (DOF)

20 mm - 70 mm 3 mil Code39 (3 chars) 5 mil Code39 (3 chars) 0 mm - 120 mm 10 mil Code39 (3 chars) 0 mm - 280 mm 13 mil UPC (6 chars) 0 mm - 350 mm 25 mm - 480 mm 20 mil Code39 (3 chars) 30 mil Code39 (2 chars) 15 mm - 650 mm

Symbologies

1D

UPC-A, UPC-E, UPC-E1, EAN-13, EAN-8, ISBN (Bookland EAN), ISSN, Code 39, Code 39 full ASCII, Code 32, Trioptic Code 39, Interleaved 2 of 5, Industrial 2 of 5, Matrix 2 of 5, Codabar (NW7), Code128, - Communication UCC/EAN 128, ISBT 128, Code 93, Code 11 (USD-8), MSI/Plessey, UK/Plessey, China Post, China Finance, GS1 DataBar (formerly RSS) variants

Indicator

Scanner Cradle

LED, Beeper, Vibrator

LED

Environmental

0°C to 50°C Operating temperature -40°C to 60°C Storage temperature Humidity 5%-95% non-condensing Drop resistance 1.5 m IP rate IP51

Cable Cradle

Straight 2.0 m (PS/2) / Straight 1.5 m (USB) / Straight 2.0 m (RS-232)

Radio Frequency 2.4-2.5 GHz,

Bluetooth 4.2, Class 2 Range 30 meters (open air) Range

Safety

Laser safety: EN 60825 1 Class 1 EMC: EN55032, EN 55024 Electrical Safety: EN60950 1

Warranty

Scanner/cradle 4-year limited warranty 3 months Battery

Unitech Europe

Tilburg, The Netherlands

- Tel.: +31 (0)13 460 9292
- Email: info@eu.ute.com
- Website: eu.ute.com



Kreski

Zapraszamy do kontaktu! Więcej informacji: www.kreski.pl

unitech because we care

Unitech America

Unitech Asia Pacific

Unitech China

Unitech Europe

Unitech Japan

Unitech Tai-

^{*} Warranty: Unitech reserves the right to call back the defect units at her discrete sole decision if Unitech may find it necessarily. Upon the calling, the returning shipping cost will be borne by Unitech except tax and duty if any. Unitech has full decision to stop the warranty coverage before expiration if the defect is found due to abused, sabotage, and/or caused by the acts of God Specifications subject to change without notice.