

Status: 09/2019



Products need labeling
Label printers
for desktop applications



MACH1/2
Kreski

Key features



With the MACH1/2, cab completes its printer range in the lower price segment:

- Reliable 4" desktop printers in proven technology
- Ideal for small to medium-volume printing
- For thermal transfer and direct thermal printing
- MACH1 with control buttons and LED display, MACH2 with colored LCD display and navigator pad
- Printable resolutions 200 dpi or 300 dpi for both printer types
- Processing of label widths up to 118 mm
- The solid double-walled construction allows printing in all areas.



Operation

The MACH1/2 can be opened up widely to insert the ribbon and the label roll **1**. Adjustment of different materials is done via a calibration button without loss of time.

The multi-language color display **2** and the cab navigator pad **3** of the MACH2 are logically structured and intuitively operable for the user.

A total of four interfaces (including Ethernet) **4** offer flexibility and fast device connection.

Fields of application

Business area	Applications
Office / authorities	Information and warning labels, inventory labels
Production	Product labels, protocol, certification and test labels
Healthcare	Labels for patient admission, blood banks
Trading	Product labels, pricing
Warehouse	Labels for storage location, shelf labeling
Transport / logistics	Address and shipping labels, incoming goods
Events	Labels for events in sports and schools, tickets

Software and printer drivers

Besides a cab Windows driver, each device is provided with the cablabel S3 software which allows creating label formats of all kinds. Via the integrated real-time clock the labels can be signed with the current date and time.

Materials and accessories

The MACH1/2 rely on standard ribbons with an 1" core and a length of 300 m. The maximum outer diameter for the label roll to be inserted in centered position is 127 mm.

Accessories such as the cutter, the present sensor and the external unwinder allow universal use of the low-maintenance compact printers.

Delivery program

Pos.		Part no.	Printers
1.1		5430001	Label printer MACH1/200
		5430002	Label printer MACH1/300
1.2		5430003	Label printer MACH2/200
		5430004	Label printer MACH2/300

Pos.	Part no.	Accessories
2.1	5430051	Cutter (cutting height between labels at least 30 mm)
2.2	5430052	Present sensor (label height at least 25 mm)
2.3	5430053	External unwinder (for roll diameters up to 250 mm)

Technical data¹⁾

				1.1		1.2	
Label printer				MACH1		MACH2	
Print head							
Printing method				Thermal transfer, direct thermal			
Printable resolution				203		300	
Print speed				127		177	
Print width				108		105.7	
Material ²⁾							
Paper, cardboard, plastics continuous material on a roll or fanfold				■		■	
Width		Labels		25 - 112			
		Liner		25 - 118			
		continuous material					
Label height				4			
				1,727		762	
Thickness				0.06 - 0.2			
Weight				60 - 160			
Roll		Outer diameter		127			
		Core diameter		25.4 - 38.1			
Winding				outside or inside			
Ribbon							
Ink side				outside or inside			
Roll diameter				68			
Core diameter				25.4			
Variable lenght				300			
Width				25 - 114			
Printer size and weights							
Width x Height x Depth				210 x 186 x 280			
Weight				2.7		3	
Label sensor with position indication							
Gap sensor				fixed at center			
Reflective sensor from below				adjustable			
Electronics							
Storage		Flash		16			
		SDRAM		8			
				(4 MB for the application)			
Batterie for current date / time, real-time clock				■		■	
Interfaces							
RS232C				■		■	
USB for PC connection				■		■	
Ethernet				■		■	
USB host				-		■	
Operating data							
Power supply				100 - 240 VAC ~ 50/60 Hz, PFC			
Power consumption				60			
Temperature / humidity		Operation		5 - 40°C / 30 - 85 % not condensing			
		Storage		-20 - 50°C / 10 - 90 % not condensing			
		Transport		-25 - 60°C / 20 - 80 % not condensing			
Approvals				CE, FCC, CCC, CB, UL, KCC			

¹⁾ All information on the design and technical specifications correspond to the date of the printing. Subject to change. The data provided in the catalog do not represent any warranty or guarantee. For current data see website www.cab.de/en/mach1-2

²⁾ Limitations may apply to small labels, thin materials or strong adhesives. These applications need to be tested and approved.

■ Standard □ Option

Operation panel			
Buttons	Feed	■	■
	On / off	■	■
	Material sensor calibration	■	■
LEDs	Ready	■	-
	Status	■	-
Colored TFT display with navigator pad		-	■
On display (MACH2)			
	Printer settings Label settings Devices Diagnostics Exit Digital clock		
Control			
	End of ribbon End of material Print head open		
Testing			
System diagnostics	when device is switched on, including print head detection		
Short status report, status printout	Printer settings Label settings Devices Diagnostics Exit Test printout Label calibration		
Fonts			
Font types	11 bitmap fonts including OCR-A, OCR-B		
Character sets	Codepage 437, 737, 850 bis 852, 855, 857, 860 bis 863, 865, 866, 869 Windows 1250 bis 1255, 1257		
Bitmap fonts	Zoom factor up to eight, orientation 0°, 90°, 180°, 270°		
Graphic formats			
	PCX, BMP		
Barcodes			
1D codes	Code 39	Postnet	
	Code 93	ITF 14	
	EAN/UPC Appendix 2	China Postal Code	
	EAN/UPC Appendix 5	HIBC	
	Interleaved 2/5	MSI	
	Codabar	Plessey	
	Code 128 A, B, C	Telepen	
	EAN 128	FIM	
	UCC 128	GS1 DataBar	
2D codes	DataMatrix	PDF417	
	QR code	Micro PDF417	
	Micro QR code	Aztec	
	MaxiCode		
Software			
Printer language	EZPL		■
Label software	cablabel S3 Lite cablabel S3 Viewer cablabel S3 Pro cablabel S3 Print		■ ■ □ □
Windows drivers certified 32/64 Bit for	Windows Vista Windows 7 Windows 8 Windows 8.1 Windows 10	Server 2008 Server 2008 R2 Server 2012 Server 2012 R2 Server 2016 Server 2019	■

Germany

cab Produkttechnik GmbH & Co KG

Karlsruhe

Phone +49 721 6626 0

www.cab.de

USA

cab Technology, Inc.

Chelmsford, MA

Phone +1 978 250 8321

www.cab.de/us

Taiwan

cab Technology Co., Ltd.

Taipei

Phone +886 (02) 8227 3966

www.cab.de/tw

China

cab (Shanghai) Trading Co., Ltd.

Guangzhou

Phone +86 (020) 2831 7358

www.cab.de/cn

France

cab Technologies S.à.r.l.

Niedermörsen

Phone +33 388 722501

www.cab.de/fr

Mexico

cab Technology, Inc.

Juárez

Phone +52 656 682 4301

www.cab.de/es

China

cab (Shanghai) Trading Co., Ltd.

Shanghai

Phone +86 (021) 6236 3161

www.cab.de/cn

South Africa

cab Technology (Pty) Ltd.

Randburg

Phone +27 11 886 3580

www.cab.de/za

cab // 820 distribution partners in more than **80** countries

