

NEW

AS-9400DC



Made for
 **GS1
DotCode**



**Support New
European Tobacco
Barcode**



Best choice for Entry-level 2D imager

Application



Retail



Manufacturing



Transportation & Logistics



Library & Office



Healthcare

Feature-rich to make daily work simple and easy



**New European Pharmacy
(GS1 Data Matrix) reading available**



**New European Tobacco
(GS1 DotCode) reading available**



Multiple language keyboard support



**Resolution:
1D >= 4mil; 2D >= 9mil**



**Drop resistance:
1.5 meters onto the concrete**



**Auto-sensing (presentation)
mode available**

Models		AS-9400DC
1-D Symbologies	Code11, Code39, Code93, Code32 (Pharmaceutical), Code128 (GS1-128), ISBT-128, Codabar (NW7), Interleaved 2of 5, Industrial 2 of 5, Discrete 2 of 5 (DTF), IATA 2 of 5, Matrix 2of 5, EAN/JAN-13, plus supplement, EAN/JAN-8, plus supplement, UPCA, plus supplement, UPCE, plus supplement, UPCE1, ISBN (Bookland), MSI Plessey Code, GS1 Databar RSS14, GS1 Databar Limited, GS1 Databar Omnidirectional, GS1 Databar Expanded	
2-D Symbologies	GS1 Databar Expanded Stacked, GS1 Databar RSS14 Stacked, PDF417, Micro PDF417, Composite Codes (CC-A, CC-B, CC-C/CC-B, CC-C), Aztec, MaxiCode, DataMatrix/ECC 200, QR Code, Micro QR Code, New European Pharmacy (GS1 Data Matrix), New European Tobacco (GS1 DotCode)	
Depth of field	Code 128 10mil 18bytes: 60~200mm Code 128 18bytes: 60~200mm QR 10mil 160bytes: 40~120mm DM 15mil 100bytes: 50~140mm QR 18bytes: 50~250mm	
Characteristics		
Dimensions	90mm x 60mm x 160mm	
Weight	210g	
Power	5V±5%	
Trigger switch	>1,000,000 cycles	
Light source	630nm visible red LED	
Image sensor	1280 x 800 array image sensor	
Interface	USB-HID, USB-Virtual COM	
Indication	LED, Beeper	
Keyboard support	American, Belgium, Barzil, Denmark, France, Austria, Germany, Hungary, Italy, Norway, Poland, Portugal, Romania, Russia, Slovakia, Spain, Sweden, Turkey_Q, England, Japan, Czech, Croatia, Bulgaria, Swiss	
Performance		
Resolution	1D: ≥4mil 2D: ≥9mil	
Scan Rate	60 fps	
Scan Angle	Yaw±55°, Rotation±180°, Pitch±55°	
Environment		
Light strength	Up to 100000 lux	
Temperature	Operating	0°C to 50°C
	Storage	-20°C to 80°C
Humidity	5% to 95% relative humidity (non-condensing)	
Drop	1.5 meters onto concrete	
Regulatory		
Regulatory Approvals	CE, FCC, BSMI, RoHS, etc.	

*Argox reserves the right to enhance and modify the specification without prior notice. Please check Argox sales representative for most updated specifications.

Optional Items



Stand:
Auto-sensing (presentation)
applications



Zapraszamy do kontaktu!
Więcej informacji: www.kreski.pl



ARGOX Certified Repair Centers

Consult your local Argox business partners for location and contacts.



Argox Information Co., Ltd.

7F., No.126, Ln.235, Baoqiao Rd., Xindian Dist., New Taipei City 231, Taiwan (R.O.C.)
Tel: +886-2-8912-1121 Fax: +886-2-8912-1124 <https://www.argo.com> <https://www.youtube.com/user/argoxmkt> email: service@argox.com
Copyright © 2020. Argox Information Co., Ltd. All Rights Reserved.