

## 8000T Ultra-Removable

<b>Media Type</b>	Label	✓	<b>Adhesive Type</b>	Permanent	
	Receipt			Removable	✓
	Tag			No Adhesive	
	Wristband		<b>Environment</b>	Indoor	✓
<b>Material Type</b>	Paper	✓		Outdoor	
	Synthetic		<b>Properties</b>	Cold Temperature	✓
<b>Printing Technology</b>	Direct Thermal (no Ribbon Required)			Deep Freeze	✓
	Thermal Transfer (Ribbon Required)	✓		High Temperature	
<b>Finish</b>	Matte	✓		Ultra High Temperature	
	Gloss			High Tack	
				Chemical Resistance	-

Note: The removability of 8000T Ultra-Removable can be affected when exposed to UV light. Please test thoroughly on all surfaces before purchase. If prolonged exposure to UV light is anticipated then please test Z-Select 2000T Removable as an alternative.

### Additional Features

- Produces excellent quality images, especially rotated barcodes, graphics and small characters with Zebra 2100, 2300, 3200 and 3400 ribbons
- Adhesive has good initial tack and superior removability without adhesive residue on a wide variety of substrates
- Excellent low temperature performance
- Adhesive complies with European food regulation EC 1935/2004, EU 10/2011 and BfR Recommendation XXI for direct contact with dry and moist, non-fatty foodstuffs
- Adhesive complies with FDA 175.105 for direct contact with dry foodstuffs, or alternatively separated by a functional barrier
- BPA free
- Latex free adhesive

### Suggested Applications

- Labelling of packaging materials including corrugated, plastic, glass and metal
- Document tracking where clean removability is required
- Removable shelf-edge labels
- Product and price promotion labelling where long term removability is required
- Product identification
- Ultra-removable labels for boxes, pallets, shelves or tote bins



## Technical Specifications

	Description	Caliper
Facestock	Smooth white topcoated paper	74 microns
Adhesive	Ultra-removable rubber adhesive	22 microns
Liner	61gsm glassine liner	54 microns
	Total	150 microns ±10%

**Recommended Zebra Printers:** P4T™, desktop, mid-range and high-performance printers

**Recommended Zebra Ribbons:** 2300, 2100, 3400, 3200

**Minimum Application Temperature:** -20°C  
When the label is applied, the environment and surface should be above this temperature

**Service Temperature Range:** -40°C to 80°C  
Following correct application and appropriate dwell time (usually 24hrs) the media will withstand this temperature range

**Recommended Storage Conditions:** 1 year duration when stored at 20°C to 25°C at 40% to 50% RH  
Storage of product before use

**Expected Life Span in Application:** Indoor use, up to 1 year  
Following correct application and appropriate dwell time (usually 24hrs) we expect, but do not warrant, a life span as indicated

## Product Performance and Suitability

The information contained in this document is to be used for guidance only and is not intended for use in setting specifications. All purchasers of Zebra products shall be solely responsible for independently determining if the product conforms to all requirements of their unique application.

For testing of this material, please order sample roll SAMPLE5146.

