

## PolyE 4000T Matte High-Tack

<b>Media Type</b>	Label	✓	<b>Film Type</b>	Polyethylene	✓
	Receipt			Polyolefin	
	Tag			Polypropylene	
	Wristband			Polyester	
				Polyimide	
<b>Material Type</b>	Paper		<b>Properties</b>	Cold Temperature	✓
	Synthetic	✓		Deep Freeze	
<b>Printing Technology</b>	Direct Thermal (no Ribbon Required)			High Temperature	
	Thermal Transfer (Ribbon Required)	✓		Ultra High Temperature	
<b>Adhesive Type</b>	Permanent	✓		High Tack	✓
	Removable			Chemical Resistance	-
	No Adhesive				
<b>Finish</b>	Matte	✓	<b>Environment</b>	Indoor	✓
	Gloss			Outdoor	✓

Note: PolyE 4000T Matte High-Tack is not recommended for long term exposure to UV light.

### Additional Features

- Topcoated polyethylene label with a high degree of opacity and good rigidity
- Suitable for indoor and outdoor use, with good short term resistance to UV light
- Very strong adhesive which will adhere to a wide range of difficult surfaces
- Good tear and water resistance properties
- ISEGA approval for direct contact with dry and non-fatty foods
- BPA free
- Latex free adhesive

### Suggested Applications

- Labelling of HDPE drums
- Labelling of oily surfaces
- Labelling products made of stone, concrete or other rough surfaces
- Outdoor labelling for plants, garden and DIY products



## Technical Specifications

	Description	Caliper
Facestock	Matte white topcoated polyethylene film	116 microns
Adhesive	Permanent acrylic adhesive	19 microns
Liner	61gsm glassine liner	54 microns
	Total	189 microns $\pm 10\%$

**Recommended Zebra Printers:** Mid-range and high-performance thermal printers

**Recommended Zebra Ribbons:** 3200, 4800, 5095

**Minimum Application Temperature:** 0°C  
When the label is applied, the environment and surface should be above this temperature

**Service Temperature Range:** -20°C to 70°C  
Following correct application and appropriate dwell time (usually 24hrs) the media will withstand this temperature range

**Recommended Storage Conditions:** 6 month duration when stored at 20°C, at 50% RH  
Storage of product before use

**Expected Life Span in Application:** Indoor use, 1 year+  
Outdoor use, up to 1 year  
Following correct application and appropriate dwell time (usually 24hrs) we expect, but do not warrant, a life span as indicated

## Product Performance and Suitability

The information contained in this document is to be used for guidance only and is not intended for use in setting specifications. All purchasers of Zebra products shall be solely responsible for independently determining if the product conforms to all requirements of their unique application.

For testing of this material please order sample roll SAMPLE65337.



Zapraszamy do kontaktu!  
Więcej informacji: [www.kreski.pl](http://www.kreski.pl)