

SIM card -
easy to install**ZONE 1/21
CL I, II, III DIV 1****android
enterprise
recommended**

- › Ideal for IoT maintenance applications
- › Zero-touch capable
- › Android™ 10

IS930.1

The robust and powerful tablet of the Industry 4.0 generation is Android Enterprise Recommended and, thanks to its zero-touch functionality, can be used quickly and is ideally suited for maintenance applications in the IoT environment. The 8-inch display, two freely programmable buttons, a long-life battery, a practical hand strap and a separate leather bag with a shoulder/belt or carry strap system are further highlights.

› All trademarks and copyrights are the properties of their respective owners. › © 2021 by i.safe MOBILE GmbH | All rights reserved. | Misprints, errors and modifications excepted. | 1030MD01REV11_EN_10.2021



i.safe MOBILE



< IS930.1 >



ATEX approval: EX-Zone 1/21
Ⓢ II 2G Ex ib IIC T4 Gb
Ⓢ II 2D Ex ib IIIC T135°C Db IP6X



IECEx approval: EX-Zone 1/21
Ex ib IIC T4 Gb
Ex ib IIIC T135°C Db IP6X



NEC500 approval:
Class I, II, III Division 1
Groups A B C D E F G T4



EAC approval:
1Ex ib IIC T4 Gb X
Ex ib IIIC T135°C Db X IP6X

Further approvals: INMETRO (Brazil) | KCs (South Korea) | PCEC (China) | JNIOOSH (Japan) | SANS (South Africa)

TECHNICAL FEATURES

| | |
|----------------------------|--|
| Operating system | Android™ 10 |
| Processor | SDM660 Octa-Core (Kryo Gold-Quad cores 2,2 GHz; Kryo Silver-Quad cores 1,8 GHz) |
| Memory | 4 GB RAM 64 GB internal memory microSD memory up to 128 GB |
| Frequencies | 2G GSM: 850/900/1800/1900 MHz 3G WCDMA: UMTS B1/2/4/5/8 4G LTE-FDD: B1/2/3/4/5/7/8/12 with MFBI B13/14/17/20/25/ 26/28A/28B/29/30/66 4G LTE-TDD: B38/B39/B40/B41 4G LTE-SCDMA: B34/B39 |
| Dimensions | size: 237 x 156 x 22 mm weight: 890 g |
| Display | 8" Gorilla Glass® 3. generation 1200 x 1920 pixels |
| Battery | 8400 mAh |
| Camera | 13 MP AF rear camera 5 MP FF front camera |
| Connections | WiFi 2,4 GHz + 5 GHz: IEEE 802.11 a/b/g/n/ac/e/k/r/h with max. 8 connections hotspot Bluetooth® 5 GPS, A-GPS, Glonass, Beidou, Galileo Near Field Communication |
| Types of protection | IP68 dust-/waterproof MIL-STD-810H usable from -20 °C to +60 °C |

FURTHER FEATURES



SOS key for loneworker protection
LWP ready (third party application required,
based on country specific regulations)



2 freely programmable keys



Usable with gloves



Accelerometer, gyroscope, magnetic,
temperature and humidity, proximity sensors



Magnetic charger port

SET CONTENT

Tablet with integrated battery, Hand Strap, i.safe PROTECTOR 2.0 Type C USB Cable, i.safe PROTECTOR 3.0 USB Magnetic Charger Cable, Power Adapter universal, Display Protection Foil, Quick Start Manual and Safety Instructions

Please visit our website and you will find more detailed information, as well as an overview of compatible accessories.