



# **RF300**

## **GAIN FULL WORKFLOW** TRANSPARENCY WITH **UHF TECHNOLOGY -**MADE FOR PM30









Industrial Production **Process Control** 



Logistics / Warehouse Management



Medical / Pharmacy

## **Specifications**

PHYSICAL CHARACTERISTICS	
Dimensions	
Standard	76.2 mm W x 130.9 L x 147.6 mm H
Weight	392g with standard battery (only RF300)
Power	
Battery	3,250 mAh 3.6V Li-ion, removable
Buttons	Trigger, Power, Trigger Mode, Connection Mode
Standard Communications	USB interface
Power Supply	5V/2A adaptor
Notification	Charging LED, Status LED, Connect-Mode, Trigger-Mode LED, Vibration
PERFORMA	NCE CHARACTERISTICS


Supported Protocol Standards			
EPC Global UHF Class 1 Gen 2 V2 / ISO 18000-63			

RFID Engine Impinj® Indy® R2000

### Nominal Read Range 6m+ (19.69ft+)

Fastest Read Rate up to 900 tags per second

Frequency / RF Output	EU: 865MHz ~ 868MHz = <30dBm (± 0.3dBm)
	US: 902MHz ~ 928MHz
	******
	= <30dBm (± 0.3dBm)
Memory	
RAM	160 KB
ROM	1MB
USER ENVIR	ONMENT
Operating Temperature	-10°C to 50°C
Storage Temperature	-40°C to 70°C
Drop	1.5m to concrete
Rain / Dust Proof (Sealing)	IP54
WIRELESS	
Bluetooth	Bluetooth Ver. 4.2 BR/EDR/BLE
NFC	Tap-to-Pair



#### **Corporate Headquarters**

Point Mobile Co., Ltd. pm\_sales1@pointmobile.com +82 2 3397 7870

#### **NA Headquarters**

Point Mobile Americas LLC info@pointmobileamericas.com +1 425 780 4452

#### **Europe Headquarters**

Point Mobile Europe GmbH info.pmeg@pointmobile.com +49 6196 777 3666

#### **China Headquarters**

Point Mobile China info@pointmobile.com.cn +86 755 8869 1169

### For more information, visit www.pointmobile.com