# RT112 10.1 Inch Android Rugged Tablet

5G & Wi-Fi 6E | Longevity QCM5430 Processor | IP67 & 1.5M Drop

## Powered by Android 13 OS with GMS & AER Certified

The RT112 is a 10.1-inch Android 13 rugged tablet equipped with an advanced 64-bit Hexa Cores CPU capable of reaching speeds up to 2.1 GHz. It effortlessly handles demanding tasks while ensuring smooth multitasking. With the distinction of Google Certification, encompassing Google Mobile Service (GMS) and Android Enterprise Recommended (AER) endorsement, the dual certification assures a secure and efficient business environment.

## Premier Barcode Reading Performance

Featuring powerful 1D/2D scanning capabilities and utilizing premier 2D barcode scanning technology, the RT112 rugged tablet offers an optional engine that enables barcode reading at distances of up to 10m with 5G and Wi-Fi 6E connectivity. This provides the perfect solution for the warehousing, retail and logistics environments, allowing users to enjoy high-performance barcode reading, whether it's from a short or long distance, and optimize their work efficiency.

# Seamless and Connectivity via Wireless Communication

Featuring Bluetooth® 5.2, wireless Wi-Fi 6E with fast roaming and 5G connectivity for real-time data collection, user can scan the item and instantly connect to the backend system to find out the quantity in stock or make an online order for customers. The RT112 delivers a seamlessly work experience and improves productivity for various applications, making it faster downloads and uploads at user's fingertips on the most reliable networks for your business.

#### 5G IOT Platform

Equipped with the Qualcomm<sup>®</sup> 5430 5G IoT Platform, the RT112 offers seamless integration into the future of technology. Its robust 5G capabilities ensure lightning-fast data transfer and a responsive online experience, all while being optimized for the demands of the Internet of Things. With a focus on longevity, the RT112 boasts an extended life cycle, making it an ideal investment for those seeking a device that will remain relevant and efficient for years to come.

eski

#### **Durable Design**

The RT112 enhances the industrial durable protection with features including IP67 dustproof, waterproof, and 1.5 meters resistance to fall protection. That means it covers fully protected from dust and can survive in 1 meter of water for up to 30 mins. The MIL-STD-810H standard assures an overall environmental vibration and humidity. The light tablet with a slim 12mm edge is designed for workers to comfortably capture data and check inventory in high portability from day to night. For an easy touch and view, the 10.1" display supports glove and wet touch mode with 400 nits.

#### Features

- Android 13 with GMS & AER Certified
- 10.1" (1920 x 1200) LCD display with Gorilla® Glass (400 nits)
- Lightweight but durable: 690g with 12mm
- Rugged Design: IP67 rated, 1.5M drop and MIL-STD-810H certified
- Wireless Communication: 5G & Wi-Fi 6E
- 5G IOT Platform (Qualcomm<sup>®</sup> 5430): Support Long Life Cycle







<u>Kr</u>eski

Zapraszamy do kontaktu! Więcej informacji: <u>www.kreski.pl</u>

# RT112 Specifications

							opeentoutions	
	System Features			Symbologies				
	OS GMS certified CPU	Android 13 (upgradable to Android 15) with AER certified GMS certified Qualcomm <sup>®</sup> Snapdragon <sup>™</sup> 5430 Processor, 64bits, Hexa Cores up to 2.1 GHz (Option: Octa Cores)		1D	and 93 2 of 5,	Bi, EAN/JAI Matrix 2 c	1, Code 128, Code 2 of 5, Code 39, Code 93 N-13, EAN/JAN 8, IATA Code 2 of 5, Interleaved of 5, MSI, GS1 Databar, UPC-A, UPC E, vith Extended Coupon Code, Coupon GS1 Code	
	Memory	6GB RAM + 128GB Flash (Option: 8GB RAM + 128GB Flash)		2D			I-UCC Emulation, GS1 Data Bar dablock F, PDF417, MicroPDF417, Aztec Code,	
	Al Others	6th Gen Qualcomm Al Engine Qualcomm® Trusted Execution Environment (TEE)				/latrix, Max latrix, Dot	κiCode, QR Code, Chinese Sensible (Han Xin), Code	
	Display			Postal			British Post, Canadian Post, China Post, Korea Post, Netherlands Post, Planet Code,	
	10.1" (1920 x 1200) LCD Display 400 nits				Postne	ət		
	Gorilla® Glass, Multi-Touch User Interface with Capacitive, stylus,			Communication				
	glove (thickness ≤ 4 mm), wet-finger Compatibility			Camera		3M (with a th API)	auto-focus and LED flash, Support Google Arcore	
	Buttons / Keypad Indicator 6 Physical Buttons LEDs, Vibrator Power, Volume+/-, Scan Key x 2,					5M (with fi	xed focus)	
				Bluetooth®		luetooth® 5.2		
	Programable Key			WLAN			z & 5GHz & 6GHz	
	RFID				Support Dual-Band Simultaneous (DBS) IEEE 802.11a/b/g/n/ac/ax/d/e/h/i/k/r/v (2x2 MU-MIMO)			
				WWAN (Optional)		rt 2G/3G/4		
	Support HF/NFC				5G FR1 Sub 6GHz:		lz:	
		pe A, Type B), ISO15693, Mifare, Felica(ISO/IEC18092)			N1/N2	N1/N2/N3/N5/N28/N41/N48/N66/N71/N77/N78/N79 (4x4 MIMO)		
							Bands 1, 2, 3, 4, 5, 7, 8, 12, 13, 17, 20, 28, 66, 71	
	1/O Interference					LTE (TDD) – Bands 38, 39, 40, 41, 48		
					3G UMTS/HSPA+ – Bands 1, 2, 5, 8 2G GSM/GPRS/EDGE (850/900/1800/1900 MHz)			
	USB USB3.1 Type-C x 1, DP Alt Mode POGO PIN POGO pin						SMS and Voice capabilities	
	SIM Slot Nano SIM x1 and Micro SD Card x 1					& B48 for (		
		(or Nano SIM x 2)		GPS	GPS, E	GPS, BeiDou, Glonass, Galileo, QZSS, NavIC and SBAS		
	Audio	Dual-speakers			(for W	WAN mod	el only)	
		MIC*2		Sensors	Gyroscope, Accelerometer (G-sensor), E-compass, Light &			
		(noise cancelling & Background noise depression)			Proxim	nity Sensor		
				Enclosure				
	Power Source	e		Dimensions		260x165x	12mm	
	Main Battery	8800mAh (removable)		Weight		690g		
				Environment				
	Software			Operating temperatu	ıre	-20°C ~ 55	°C	
		oftware Solutions and utilities such as Airwatch, SOTI,		Storage temperature	)	-40°C ~ 70	°C	
	Ivanti Wavelink, a	and MoboLink		Drop test to Concrete		1.5m		
				Environmental Sealin	ng	IP67		
	Regulatory A	pprovals		Relative Humidity Vibration and Shock t	tost		% (Non-Condensing) 810H. Method 516.8. Procedure IV	
	CE, UKCA, FCC, IC, NCC, BSMI, VCCI, TELEC, CCC, SRRC, BQB, RoHS,				1631	WIIL-STD-	bron, Method 510.0, Flocedule IV	
	REACH			What comes in t	the bo	× 🛏	Accessories	
				RT112			Rotatable Hand Strap	
•>	Headquarters	unitech		Battery Pack USB-C Adaptor			Shoulder Strap Screen Protector Office Cradle Vehicle Cradle	
	Taipei, Taiwan						Capacitive Stylus Pen (5.5mm) w/ Coil Strap	
	http://www.ute.	com e-mail: info@hq.ute.com		unitech Europe				
	unitech America			Tilburg / Netherland				
		n e-mail: info@us.ute.com		http://eu.ute.com	e-mail: i	nto@eu.ut	e.com	
	http://can.ute.co	m info@can.ute.com		unitech Japan Tokyo				

http://can.ute.com info@can.ute.com Mexico http://latin.ute.com e-mail: info@latin.ute.com

unitech Asia Pacific & Middle East Taipei http://apac.ute.com info@apac.ute.com / info@india.ute.com http://mideast.ute.com info@mideast.ute.com unitech Greater China Beijing, Shanghai, Guang Zhou, Xiamen http://cn.ute.com info@cn.ute.com Taipei http://tw.ute.com info@tw.ute.com

http://jp.ute.com e-mail: info@jp.ute.com



Specifications subject to change without notice. Copyright 2025 unitech Electronics Co., Ltd. All rights reserved. unitech is a registered trademark of unitech Electronics Co., Ltd. All product and company names are trademarks, service marks, or registered trademarks of their respective owners.

Tokyo

