



SPECIFICATION

Customer: _____

Customer's Model No.: _____

Model No.: **LYRA L-9080i**

**Hybrid Desktop Presentation and Handheld
Area Imager Barcode Scanner**

Date: _____

Sample Serial No.: _____

Spec. Version & Revision Date: V02 2021.04.27

Received/Approved by



[Http://www.champtek.com](http://www.champtek.com)
E-mail : sales@champtek.com

ChampTek Incorporated
1F, No. 4, Alley 2, Shih-Wei Lane, Chung Cheng Rd.,
Xindian District, New Taipei City 231, Taiwan
TEL : 886-2-22192385
FAX : 886-2-22192387



Revision History

Version	Date	Context
V00	2019.07.17	Release
V01	2021.04.15	Add RS232 Cable
V02	2021.04.27	Modify Depth of field

TABLE OF CONTENTS

A.	General Description	4
B.	Physical Characteristics	5
C.	Connecting	6
D.	Powering	6
E.	Electrical Characteristics	7
F.	Performance	7
G.	Environmental	8
H.	Reading Range	8
I.	Usage mode and Indicator table	9
J.	Readable Symbolologies	10
K.	Reliability	10



Zapraszamy do kontaktu!
Więcej informacji: www.kreski.pl

A. General Description

The LYRA family is a multi-form, compact size, omni-directional presentation area-imaging scanner engineered to decode all standard 1D and 2D barcodes. Its revolutionary imaging technology is housed in an elegant, stylish, yet durable design. The compact size and small foot-print design, makes it the ideal solution for space-constrained environments.

With the **LYRA L-9080i**, you get the versatility to scan any 1D or 2D bar code — from the printed labels in retail that identify product or mobile bar codes on the screen of a mobile phone, and pricing at the register to mobile coupons, mobile gift and loyalty cards, boarding passes and even theater tickets. The LYRA provides all the features you need to keep your workers productive; intuitive and fast reading performance; true point-and-shoot scanning simplicity — no need to align bar code and scanner; and hands-free and handheld flexibility.

The LYRA reader includes powerful configuration tool, programming bar code and data formatting functionality which allow easy integration into existing or new host systems, management to manage maintenance.



Zapraszamy do kontaktu!
Więcej informacji: www.kreski.pl

B. Physical Characteristics

Weight



Body weight	Approx.315g
RS232 Cable weight	Approx. 85g
USB Cable weight	Approx. 55g
Material	ABS Plastic
Connector	RJ 48C 10 Pin
Dimension (WxDxH)	97.89 x 74.90 x 137.94 mm
Color Available	Black

Note : scanner head can be forward (Max 90°) and backward (Max 90°) tilting adjusted in a total 180° range to accommodate to your application need.

Body Dimension

Unit: mm 97.89(W) x 74.90(D) x 137.94(H)

UNIT : mm



C. Connecting

Interface Selection

LYRA allows you to connect your host system using two different interface cables, RS232 or USB.

Interface Cable	Connector type
USB Black (Product Number: 0114-LY00001)	USB connector
RS232 Black (Product Number: 3114-LY00041)	DB9 connector

D. Powering

LYRA power is designed by USB+5V, do not need power supply once the interface is USB, but will request power supply for RS232 interface.

E. Electrical Characteristics


Interface	RS232	USB
Supply Voltage	DC Adaptor +5V $\pm$ 5%	USB Power
Stand-by (Typ.)	95 mA	90 mA
Operation (Typ.)	320 mA	310 mA

F. Performance

Light source	Visible White LED
View of field	Horizontal – 55°, Vertical – 35°
Depth of field	210mm@20mil/0.5mm, PCS90%
Resolution	1280 (H) x 800 (V) pixels 3.0 mil (Code 39), 8 mil (QR Code)
Scan speed	60 scans per second
Pitch	$\pm$ 60°(from front to back)
Skew	$\pm$ 60°(from plane parallel to symbol(side- to-side))
Roll	360°
Interface	RS-232 or USB
Indicators	Beep and LED



Zapraszamy do kontaktu!
Więcej informacji: www.kreski.pl



G. Environmental

Operating Temp.	0°C to 50°C (32°F to 122°F)
Storage Temp.	-20°C to 70°C (-4°F to 158°F)
Relative Humidity	5% to 95% (Non-condensing)
Sealing	Designed to IP42 water and dust protection

H. Reading Range

Barcode	Depth of field
3mil Code39	0 ~ 60 mm
4mil Code39	0 ~ 90 mm
5mil Code39	0 ~ 120 mm
10mil Code39	0 ~ 150 mm
20mil Code39	0 ~ 210 mm
20mil QR Code	0 ~ 150 mm
20mil PDF417	0 ~ 150 mm
20mil Data Matrix	0 ~ 150 mm

Note : The test is under ambient light 700~800 Lux.

Near distance is Field of View (FOV) limited by the scanner's lens.

I. Usage mode and Indicator table

Usage	Action	LED	Beeper
Desktop usage (Auto-Sense mode)	In stand-by	Orange light	
	Successful reading	Blue Blink 1 time	Be
Handheld usage (Trigger mode)	In stand-by	Blue light	
	Successful reading	Orange Blink 1 time	Be

Note : The LYRA is default booting at desktop “Auto-sense reading mode”, if you press the touch button on side of LYRA, it will be switched to the “Trigger reading mode”, you can then hold it to simulate as a handheld scanner. The LYRA will automatically switch back to the desktop “Auto-sense reading mode” while there is no scan in 3 seconds.



Kreski

Zapraszamy do kontaktu!
Więcej informacji: www.kreski.pl

J. Readable Symbolologies

1D Symbolologies	Readable	Default Enable
UPC-A	V	V
UPC-E	V	V
EAN-8/JAN-8	V	V
EAN-13/JAN-13	V	V
Code 39	V	V
Code 128	V	V
Codabar/NW7	V	V
Interleaved 25	V	V
Industrial 25	V	
Matrix 25	V	
Code 93	V	
China Post	V	
Code 11	V	
MSI/Plessey	V	
Telepen	V	
GS1 Databar Omni-directional	V	
GS1 Databar Limited	V	
GS1 Databar Expanded	V	

2D Symbolologies	Readable	Default Enable
Aztec	V	
Data Matrix	V	V
PDF 417	V	V
Micro PDF 417	V	
QR Code	V	V
Micro QR Code	V	
DotCode	V	

K. Reliability

Life Time	
MTBF(Calculated)	50,000 hours
Temp. Test	
High Temp.	70°C, 48 hours
Low Temp.	-20°C, 48 hours
Cable Bending Test	25,000 times minimum (30 times/min @ 500g/90°)
Drop Resistance	47.24 inches(120cm) drop on concrete surface
Electro-Static Discharge	Both contact and air at up to 20KV