

# Power Xpert 9395P UPS

250 - 1200 kVA



Power Xpert 9395P UPS with optional power module status lights

## Advanced power protection for:

- Large data centres, infrastructure projects, industrial complexes and other buildings
- Process control equipment
- Healthcare
- Finance and banking infrastructure
- Transportation systems
- Security operations
- Telecommunications installations



Zapraszamy do kontaktu!  
Więcej informacji: [www.kreski.pl](http://www.kreski.pl)



Powering Business Worldwide

## Double conversion UPS

### 10% more power

- 96.3% double conversion efficiency, delivers 10% more power than the previous 9395 UPS.
- Complete isolation of output power from all input power anomalies, to deliver 100% conditioned, perfect sine-wave output – even during severe power disturbance.
- High efficiency even when UPS load levels are low, optimised by Variable Module Management System (VMMS).
- Energy Saver System (ESS) improves efficiency levels to 99% by suspending power modules when double conversion is not required. Switches to double conversion mode in less than 2 milliseconds in event of pre-set input limits being exceeded. Filtering against fast low-energy transients provided by ESS.
- Producing 18% less heat helps reduce the need for cooling. Designed for continuous operation at ambient temperatures up to 40 °C without de-rating. Can also deliver safe power in higher temperatures without shutting down.

## Ultimate resiliency

- HotSync® patented load-sharing technology enables parallel operating of static converters without communication or load-share signals. Eliminating the communication link eliminates risk of single point of failure.
- One static switch per UPS enables the full bypass capacity to be achieved from day one. Power modules can be added as loads increase.
- Wide power factor range meets rapidly changing load power factor without de-rating.
- Intelligent battery charging through Advanced Battery Management prevents unnecessary charging and significantly retards battery wear rate.

## Scalability and flexibility

- Number of power modules per UPS can be specified.
- Layout can be chosen to suit installation: back-to-back, L-shaped etc. Front-accessible design minimises installation costs and saves valuable data centre space.
- Preferred bypass topology can be specified. Additional modules can be added as power load increases.
- Centralised multi-module paralleled 9395P systems are supported by the Eaton System Bypass Module (SBM). Available in ratings from 2000 A to 5000 A as standard, the SBM includes a continuous-duty centralised static switch, backfeed protection device and centralised bypass systems.
- Service disconnect in each power module allows easy maintenance while the UPS is supporting the load in double conversion mode.
- More than 90% of materials used can be recycled, decreasing end-of-life impact.

# Technical specification



UPS output power rating								
kVA	250	300	500	600	750	900	1000	1200
kW	250	275	500	550	750	825	1000	1100
General								
Efficiency in double conversion mode (full load)			95.6%					
Efficiency in double conversion mode (half load)			96.3%					
VMMS (double conversion)			Significantly increased efficiency at low loads					
Efficiency in Energy Saver System (ESS)			Up to 99.3%					
Distributed parallelling with Hot Sync technology			Up to 7					
Internal N+1 redundancy capable			In 600 kVA: 300 kVA In 900 kVA: 600 kVA In 1200 kVA: 900 kVA					
Field upgradable			Yes					
Inverter/rectifier topology			Transformer-free IGBT with PWM					
Audible noise			78 dB (300 kVA); <81 dB (600 kVA); <83 dB (900 kVA); <85 dB (1200 kVA)					
Altitude (max)			1000 m without derating (max 2000 m)					
Input								
Input wiring			3 ph + N + PE					
Nominal voltage rating (configurable)			220/380, 230/400, 240/415 V 50/60 Hz					
Input voltage range			+15% / -15% for 400 V or 415 V +15% / -10% for 380 V +10% / -10% for bypass					
Input frequency range			45-65 Hz					
Input power factor			0.99					
Input ITHD			<3% on nominal load in double conversion mode					
Soft start capability			Yes					
Internal backfeed protection			Yes, standard					
Output								
Output wiring			3 ph + N + PE					
Nominal voltage rating (configurable)			220/380, 230/400, 240/415 V 50/60 Hz					
Output UTHD			<2% (100% linear load), <5% (non linear load)					
Output power factor			0.9 (300, 600, 900 and 1200 kVA models) 1.0 (250, 500, 750 and 1000 kVA models)					
Permitted load power factor			0.7 lagging - 0.8 leading					
Overload on inverter			10 min 100-110%; 30 sec 110-125%; 10 sec 125-150%; 300 ms >150%					
Overload when bypass available			Continuous <115%, 20 ms 1000% Note! Bypass fuses may limit the overload capability					

Battery				
Type	VRLA, AGM, Gel, Wet Cell			
Charging method	Current limited constant voltage charging, or Eaton Advanced Battery Management (ABM)			
Temperature compensation	Optional			
Battery nominal voltage (lead-acid)	480 V (40 x 12 V, 240 cells)			
Charging current / Model	300	600	900	1200
Max* A	120	240	360	480
*Limited by maximum UPS input current rating				
Dimensions and weights				
300 kVA	1350 x 880 x 1880 mm (wxdxh)			830 kg
600 kVA	1890 x 880 x 1880 mm			1440 kg
900 kVA	3710 x 880 x 1880 mm			2680 kg
1200 kVA	4450 x 880 x 1880 mm			3120 kg
Accessories				
External battery cabinets with long-life batteries, X-Slot connectivity (Web/SNMP, ModBus/Jbus, Relay, Hot Sync, ViewUPS-X remote display), integrated manual bypass for 300 kVA model				
Communications				
X-Slot	4 communication bays			
Relay inputs/outputs	5/1 programmable			
Compliance with standards				
Safety (CB certified)	IEC 62040-1			
EMC	IEC 62040-2			
Performance	IEC 62040-3			



Zapraszamy do kontaktu!  
Więcej informacji: [www.kreski.pl](http://www.kreski.pl)