Ulovo

DT50P Lite

Lightweight UHF RFID Handheld Reader

Lightweight Design, Perfect Comfort

Weighing just 498g, the device's ergonomic design ensures effortless handling allowing for extended usage without compromising on comfort.

Unmatched RFID Performance, Exceptional Efficiency

Powered by the Impinj E710 chip and supporting Impinj Gen2X, it delivers an RFID reading rate of 1300+ tags per second and a range of over 15 meters, significantly enhancing work efficiency.

Powerful Performance, Effortless Multitasking

Equipped with a Qualcomm Octa-core 2.45 GHz processor and Android 13.0, it ensures fast response times and seamless multitasking for high-performance applications.

Fast and Stable Data Transmission

Supports Wi-Fi 6 Ready, 2.4 GHz and 5 GHz dual-band Wi-Fi, and 4G network, providing fast and stable data transmission indoors and outdoors.

Endurance You Can Count On

Equipped with a 6500mAh removable battery, providing reliable power for your all-day workload and ensuring uninterrupted productivity.







Zapraszamy do kontaktu! Więcej informacji: <u>www.kreski.pl</u>

DT50P Lite Lightweight UHF RFID Handheld Reader Specifications

ি Touch Screen **O.S**. Memory \Box Display Processor Octa-core 2.45 GHz Android 13 RAM: 4GB ROM: 64GB 5.7 inch display Ultra sensitive capacitive touch panel Micro SD, up to 256GB (720×1440) Supports multi-touch Works with gloves, wet fingers **Dimensions** ⊂)» Audio 🕂 Scanning **Batterv** Camera \odot 3.85V / 6500mAh Size: 132 x 162.6 x 78mm Microphone (noise cancellation); Professional scan engine Front 5MP Weight: 498g Speaker (1.3W) Supports international standard Top 13MP with flash Receiver 1D/2D barcodes Support barcode displayed on screen and colored barcode (··) RFID(UHF) Card slot Communication Positioning **Buttons** (口) Micro SD * 1 4G. 3G. 2G PWR button Reading Range: 15m+ GPS, A-GPS, BeiDou, Vol+/- button Nano-SIM * 2 Read Rate: 1300+ tags/sec BT5.0 + BR/EDR + BLE GLONASS 、Galileo (*Environment-Based; Scan button * 2 2.4G/5G. IEEE 802.11 Data from UROVO Lab) Custom button * 1 a/b/g/n/ac/d/e/h/i/k/r/v/w/ax ready **A**[≡] Environment Protection (+)IP67 dustproof and waterproof Operating temperature: $-20 \sim +60^{\circ}C$ 1.5-meter drop resistance Storage temperature: $-40 \sim +70^{\circ}C$ Kreski Humidity: 5%RH ~ 95%RH (non-condensing) ESD: +/-15kv Air; +/-8kv contact Zapraszamy do kontaktu! Więcej informacji: www.kreski.pl

UROVO PTE. LIMITED

Website: en.urovo.com Email: urovo@urovo.com Address: 1 Raffles Place, #21-01 One Raffles Place Tower 1, Singapore 048616

Urovo Europe

Website: europe.urovo.com Email: sales-europe@urovo-emea.com Address: de Maas 9, 5684PL, Best, the Netherlands

Urovo North America Website: us.urovo.com Email: urovo@urovo.com

*This page is subject to change without prior notice

Urovo

Email: urovo@urovo.com Address: 1990 Main Street, Suite 750, Sarasota, Florida 34236