





Lite 8 PoE

USW-Lite-8-PoE



Overview

Dimensions	99.6 x 163.7 x 31.7 mm (4 x 6.4 x 1.3")
Port Layout	
1 GbE RJ45	8 (4 PoE+) (1G/100M/10M)
Max. PoE Output	Up to PoE+
Total PoE Availability	52W
Form Factor	Compact desktop, wall

Performance

Switching Capacity	16 Gbps
Total Non-Blocking Throughput	8 Gbps
Forwarding Rate	12 Mpps
Supported VLANs	1,000



MAC Address Table Size	8,000
Packet Buffer Size	0.5 MB
Access Lists	
IPv4	128
MAC	128

^ Layer 2 Features

LACP Port Aggregation	✓
STP & RSTP	✓
Advanced IGMP Configuration (Querier, Fast Leave, Router Port)	✓
IGMP Snooping	✓
802.1X Control	✓
MAC-Based ACLs & Device Isolation	✓
DHCP Snooping & Guarding	✓
Egress Rate Limit	✓
Flow Control	✓
Storm Control	✓
Multicast & Broadcast Rate Limiting	✓
MAC Address Blocking	✓
IP-Based ACLs & Network Isolation	✓
MAC-Based Port Restriction	✓
Port Isolation	✓
Port Mirroring	✓
Jumbo Frames	✓
LLDP-MED	✓
Voice VLAN	✓
Loop Protection	✓

^ Hardware

PoE Ports

PoE+	4
Max. PoE Wattage per Port by PSE	
PoE+	30W
Max. Power Consumption	8W (Excluding PoE Output) 60W (Including PoE Output)
Power Method	AC/DC Adapter (included)
Power Input Method	DC input
Power Supply	AC/DC, external, 60W
Supported Voltage Range	50—57V DC
Management	Ethernet
Heat Dissipation (Excluding PoE Output)	27.296 BTU/hr
Weight	295 g (10.4 oz)
Enclosure Material	Polycarbonate
Mount Material	Polycarbonate
Ambient Operating Temperature	-15 to 40° C (5 to 104° F)
Ambient Operating Humidity	10 to 90% noncondensing
NDAA Compliant	✓
Certifications	CE, FCC, IC, Anatel
^ Software	
Application Requirements	
UniFi Network	Version 7.2.94 and later



Zapraszamy do kontaktu!
Więcej informacji: www.kreski.pl