






UniFi Express 7

UX7



Overview

Dimensions	117 x 117 x 42.5 mm (4.61 x 4.61 x 1.67")
UniFi Application Suite	
Network	✓
Managed UniFi Devices	30+
Simultaneous Users Connected	300+
Max. WAN Port Count	1
Default WAN Ports	(1) 10 GbE RJ45
Port Layout	
2.5 GbE RJ45	1 (2.5G/1G/100M/10M)
10 GbE RJ45	1 (10G/5G/2.5G/1G/100M)



IDS/IPS Throughput	2.3 Gbps
Form Factor	Compact desktop
Coverage Area	160 m ² (1,750 ft ²)

^ Security

Stateful Firewall	✓
Application-Aware Layer 7 Firewall	✓
DPI & Traffic Identification	✓
Zone-Based Firewall Advanced Filtering (Regions, Domains, Apps)	✓
Content Filtering	✓
Intrusion Prevention (IPS/IDS)	✓
Ad Blocking	✓
IDS/IPS Signatures	20,000+ with CyberSecure
VLAN/Subnet-based Traffic Segmentation	✓

^ VPN & SD-WAN

License-Free SD-WAN	✓
Site-to-Site VPN	
Site Magic	✓
IPsec	✓
OpenVPN	✓
VPN Server	
Identity Endpoint One-Click VPN	✓
Teleport Zero-Configuration VPN	✓
WireGuard	✓
OpenVPN	✓
L2TP	✓
VPN Client	
OpenVPN	✓



WireGuard	✓
^ Networking	
Dynamic Routing	
OSPF	✓
Advanced QoS	✓
Multicast DNS (mDNS)	✓
Advanced NAT (SNAT / DNAT / Masquerade / NAT Pooling / 1-to-1 NAT)	✓
Integrated RADIUS Server	✓
RADIUS over TLS (RadSec)	✓
Additional Internet Failover with UniFi LTE Backup	✓
Internet Quality and Outage Reporting	✓
Policy-based WAN and VPN Routing	✓
Customizable DHCP Server	✓
IPv6 ISP Support	✓
IGMP Proxy	✓
^ Integrated WiFi	
WiFi Standard	802.11a/b/g/n/ac/ax/be (WiFi 6/6E, WiFi 7)
Throughput	
6 GHz	5.7 Gbps
5 GHz	4.3 Gbps
2.4 GHz	688 Mbps
MIMO	
6 GHz	2 x 2 (DL/UL MU-MIMO)
5 GHz	2 x 2 (DL/UL MU-MIMO)
2.4 GHz	2 x 2 (DL/UL MU-MIMO)
Antenna Gain	
6 GHz	6 dBi



5 GHz	7 dBi
2.4 GHz	4 dBi
Max. TX Power	
6 GHz	24 dBm
5 GHz	26 dBm
2.4 GHz	23 dBm
Wireless Security	WPA-PSK, WPA-Enterprise (WPA/WPA2/WPA3/PPSK)
Max. BSSIDs	4 per Radio (Gateway Mode) 4 per Radio (AP Mode)
Supported Data Rates	
802.11a	6, 9, 12, 18, 24, 36, 48, 54 Mbps
802.11b	1, 2, 5.5, 11 Mbps
802.11g	6, 9, 12, 18, 24, 36, 48, 54 Mbps
802.11n	6.5 Mbps to 300 Mbps (MCS0 - MCS15, HT 20/40)
802.11ac (WiFi 5)	6.5 Mbps to 1.7 Gbps (MCS0 - MCS9 NSS1/2, VHT 20/40/80/160)
802.11ax (WiFi 6/6E)	7.3 Mbps to 2.4 Gbps (MCS0 - MCS11 NSS1/2, HE 20/40/80/160)
802.11be (WiFi 7)	7.3 Mbps to 5.7 Gbps (MCS0 - MCS13 NSS1/2, EHT 20/40/80/160/240/320)

^ Hardware

Max. Power Consumption	22W
Power Method	USB type C (5V DC/5A)
Power Supply	USB type C (5V DC/5A) (Adapter included)
Supported Voltage Range	100—240V AC
Processor	Quad-core ARM® Cortex®-A53 at 1.5 GHz
System Memory	3 GB
Weight	422 g (14.9 oz)
Enclosure Material	Polycarbonate
LCM Display	0.96" status display

Management	Ethernet Bluetooth
LEDs	
Ethernet	✓
Button	(1) Factory-reset
ESD/EMP Protection	Air: $\pm 8\text{kV}$, contact: $\pm 4\text{kV}$
Ambient Operating Temperature	-10 to 40° C (14 to 104° F)
Ambient Operating Humidity	5 to 95% noncondensing
NDAA Compliant	✓
Certifications	CE, FCC, IC
^ Software	
VLAN	802.1Q
Guest Traffic Isolation	✓
Application Requirements	
UniFi Network	Version 9.0.108 and later



Zapraszamy do kontaktu!
Więcej informacji: www.kreski.pl