



Switch to  
a New Generation

## WEBSMART SWITCHES ES430 SERIES



• ES430-10P-POE

• ES430-18P-POE

• ES430-26P-POE



Zapraszamy do kontaktu!  
Więcej informacji: [www.kreski.pl](http://www.kreski.pl)



DCN Europe  
30-633 Kraków, ul. Walerego Sławka 8a,  
Poland



WWW  
dcneurope.eu



E-mail  
sales@dcneurope.eu

## PRODUCT OVERVIEW

The ES430 series switches are a new family of intelligent network switches with a convenient management interface via a web browser. Thanks to simple configuration and the ability to power devices using PoE technology, it provides an efficient, easy-to-manage and affordable gigabit solution for small and medium-sized networks.

ES430-10P-POE	<ul style="list-style-type: none"><li>8x10/100/1000Base T+2x100/1000Base X (SFP)</li><li>AC 230 V power supply</li><li>PoE+, up 120 W</li><li>Switching capacity: 20 Gb/s</li><li>Forwarding rate: 14,88 Mp/s</li></ul>
ES430-18P-POE	<ul style="list-style-type: none"><li>16x10/100/1000Base T+2x100/1000Base X (SFP)</li><li>AC 230 V power supply</li><li>PoE+: up to 250 W</li><li>Switching capacity: 36 Gb/s</li><li>Forwarding rate: 26,78 Mp/s</li></ul>
ES430-26P-POE	<ul style="list-style-type: none"><li>24x10/100/1000Base T+2x100/1000Base X (SFP)</li><li>AC 230 V power supply</li><li>PoE+, up to 370W</li><li>Switching capacity: 52 Gb/s</li><li>Forwarding rate: 38,68 Mp/s</li></ul>

- Green Energy**  
ES430 series Ethernet switch complies the IEEE 802.3az (Energy Efficient Ethernet) standard, which greatly reduces equipment power consumption and is green and energy-saving. Fully considering the low-noise requirements of the user environment, some ES430 models adopt a fanless silent design to reduce noise pollution.
- Redundant backup, stable and reliable**  
Supports link aggregation networking with 2 uplink ports to enhance the robustness and high reliability of user network structures.
- Flexible working modes for rapid configuration**  
Standard: default mode with port negotiation enabled.  
Monitor: port isolation enabled on downlink ports and port aggregation enabled on uplink ports (2 SFP ports)  
Aggregation: port aggregation enabled on uplink ports (2 SFP ports)  
Isolation: port isolation enabled on downlink ports
- IGMP snooping**  
Bandwidth consumption will be reduced in a multi-access LAN environments so as to avoid flooding the entire VLAN.
- Loopback detection**  
It allows to avoid the loopback issues on single port or dual ports.
- Enhanced power over Ethernet (PoE+) and monitoring**  
ES430 series provide a maximum output power of 30W per port. The real time total PoE powers and rest powers can be monitored via web page.
- Fast PoE powering.**  
The switches can supply power to PDs less than 10 seconds when they are powering on.
- Uninterrupted powering**  
When the switch is rebooting, PDs will be kept on working mode without break

ES430 series	10P-POE	18P-POE	26P-POE
<b>Switch classification</b>			
Web Smart Gigabit Switch	✓	✓	✓
<b>Ports</b>			
10/100/1000Base-T (RJ45) with PoE	8	16	24
100/1000Base-X (SFP)	2	2	2
<b>Technical specification</b>			
MAC addresses	8 K	8 K	8 K
Switching capacity	20 Gbps	36 Gbps	52 Gbps
Forwarding rate	14,88 Mp/s	26,78 Mp/s	38,68 Mp/s
VLAN	4 K, Port-based, IEEE 802.1Q		
Standards & Protocols	IEEE802.3i, IEEE802.3u, IEEE802.3ab, IEEE802.3z, IEEE802.3x, IEEE802.3ad, IEEE802.1Q		
DHCP	IPv4/IPv6 DHCP Client		
Multicast	IGMP snooping		
Traffic control	Port bandwidth control		
Security	DHCP snooping, Storm suppression		
<b>Management</b>			
Web GUI	✓	✓	✓
imCloud (cloud management)	✓	✓	✓
IP address for management:	1		
Default	192.168.2.1		
Static (manually set)	✓	✓	✓
Obtained from DHCP server	✓	✓	✓
Port Management	Monitoring of port status and statistics		
<b>Physical</b>			
Cooling	Passive	Active	Active
Dimensions (Width x Height x Depth) [mm]	266 x 160,8 x 44	330 x 220 x 44	440 x 260 x 44
Operating temperature	0 °C ~ 50 °C		
Working humidity	0°C~50°C, 10%~90%, non-condensing		
Rack mountable	✓		
Rack mounting kit	-	✓	✓
<b>Electrical</b>			
Power supply	P ower adapter (included). AC input: 230V, 50Hz DC output: 54V/2.4A	AC input: 230V, 50Hz	AC input: 230V, 50Hz
Power Consumption	≤130W	≤270W	≤400W
PoE standards	802.3af/at		
PoE power budget	120 W	250 W	370 W
PoE real time monitor	✓	✓	✓



Zapraszamy do kontaktu!  
 Więcej informacji: [www.kreski.pl](http://www.kreski.pl)