

HAVIS DOCKING STATIONS FOR GETAC F120 TABLETS

DS-GTC-1700 SERIES



ULTRA-RUGGED. ULTRA-RELIABLE.

- Supports Getac's F120 Tablets
- Optional port replication with Advanced or Standard content
- Optional Quad pass-through antenna connection
- Spring-loaded, floating connector head
- One-handed docking & undocking
- LPS-140-BW Power Supply Included
- Compact & lightweight while being ultra rugged
- Compatible with Getac's accessories including the stylus, digitizer pen, hand strap, slim hand strap, and high capacity battery
- Lock and key supplied for peace of mind theft deterrence

HAVIS DOCKING STATIONS FOR GETAC F120 TABLETS

DS-GTC-1700 SERIES

Kreski

GETAC F120 TABLET SOLUTION

- Intelligent cable management system
- Integrated VESA 75 mounting pattern
- Polycarbonate construction ensures strength, ruggedness and extreme temperature resistance
- Rounded edges and corners for comfort and safety



PART NUMBER	ETHERNET (RJ45)	USB 2.0	USB 3.2	USB-C 2.0	USB-C 3.2	HDMI	POWERED SERIAL (DB9)	PASS-THRU ANT	EXT POWER
DS-GTC-1701	1	1	2	1	1		1		
DS-GTC-1701-4	1	1	2	1	1		1	QUAD	
DS-GTC-1702-BW	1	1	2	1	1		1		LPS-140-BW
DS-GTC-1702-4-BW	1	1	2	1	1		1	QUAD	LPS-140-BW
DS-GTC-1703									
DS-GTC-1703-4								QUAD	
DS-GTC-1704	1	1	2	1	1	1	1		
DS-GTC-1704-4	1	1	2	1	1	1	1	QUAD	
DS-GTC-1705-BW	1	1	2	1	1	1	1		LPS-140-BW
DS-GTC-1705-4-BW	1	1	2	1	1	1	1	QUAD	

SPECIFICATIONS:

Height: 10.5" (26.7 cm)
Width: 10.0" (25.4 cm)
Depth: 3.2" (8.1 cm)
Weight: 2.7 lbs (1.22 kg)
Mounting: VESA 75

CERTIFICATIONS & TESTING:

Vibration Testing: MIL-STD 810H 514.8
Crash Testing: SAE J1455 30mph
Cycle Testing: Dock/undock 30K cycles
Environmental Testing: Hot/Cold operational -21° C to 50° C
(-6° F to 122° F); Hot/Cold storage -40° C to 85° C (-40° F to 185° F)
Thermal Shock: MIL-STD 810H, Method 503.7
FCC, CE, CAN ICES (B), RoHS
EMC Testing: EN 55032, EN 50498
ESD: IEC 10605

Kreski

Zapraszamy do kontaktu!
Więcej informacji: www.kreski.pl

