

ZCAT-6/8/10
REWINDERS



Zero Tension Loop Controlled Label
Rewinder



- All models are bi-directional.
- Control Input.
- Speed up to 125cm/s.
- 5- Years Parts and Labour Limited Warranty.

The new ZCAT-6, ZCAT-8 and ZCAT-10 Rewinders are the ideal solution for printers that back feed, as well as for extremely sensitive printers that cannot tolerate any rewind force without causing undesirable registration or artifact problems. A free-hanging “loop” of label stock is created between the printer and the Tensioning Roller of the unit thereby eliminating all tension whatsoever on the printer. A special chassis-mounted sensor starts and stops the Rewinder based on the optimum depth of the loop. Fully adjustable tension exists between the Tensioning Roller and the Rewinder thus yielding a consistent and tightly wound finish to

Technical specifications	ZCAT-6	ZCAT-8	ZCAT-10
Max Roll Diameter	300 mm		
Core diameter	76 mm		
Max Label Width	170 mm	220 mm	255 mm
Max roll Weight	9 kg		
Dimensions WDH	483 x 381 x 400mm		
Weight	16.8kg		
Max speed	125 cm/s		
Max Torque	228 in-oz		
Number of Flanges	1		
Power spec. ²	120- 220VAC in, 24VDC 120W Out-5A		
Available Options	Optional Counter Module Optional Outer Guide Flange Optional Paper Loop Guide		

¹ Rewind Direction of the ZCAT (“left-to-right” or “right-to-left”) is specified at the time of order.

² Universal 120-220VAC Power Adaptor supplied with rewinder



Specifications are subject to change without notice. Data ZCAT 06/2018



Labelmate
Chaussée de Ruisbroek 290
1620 Drogenbos (Belgium)

+32 2 375 69 60
brussels@labelmate.com
BTW BE 0674 877 993



Zapraszamy do kontaktu!
Więcej informacji: www.kreski.pl

labelmate.com