

MC93^{ex}-NI Accessories

Datasheet

Kreski

Zapraszamy do kontaktu!
Więcej informacji: www.kreski.pl



It is absolutely necessary to use original accessories from BARTEC!

Accessories for use in potentially explosive atmospheres

Accessories are approved for:

- ATEX: Zone 2/22 (EPS 19 ATEX 1 239 X)
- IECEx: Zone 2/22 (IECEx EPS 19.0108X)
- NEC: Class I, II, III Div 2 (UL E321557)



Battery

Description	<ul style="list-style-type: none"> - Lithium polymer battery 3.6V/7000 mAh (25.4Wh) - Hot-swappable <p>May only be changed and charged outside the potentially explosive atmosphere!</p>
-------------	--

Order no.	B7-A2Z0-0059
-----------	--------------



Spare keypad

Description	<ul style="list-style-type: none"> - Certified in combination with MC 93^{ex}-NI - With green overlay <p>May only be assemble/disassemble outside the potentially explosive atmosphere!</p>
-------------	---

Order no.	with 28 keys, numeric	B7-A2Z0-0063
	with 43 keys, numeric	B7-A2Z0-0065
	with 53 keys, alphanumeric	B7-A2Z0-0066
	with 53 keys, alphanumeric, VT-Emulation	B7-A2Z0-0067



MicroSD card (MLC)

Description	<ul style="list-style-type: none"> - Suitable for MC 93^{ex}-NI - Storage capacity: 32 GB <p>May only be changed outside the potentially explosive atmosphere!</p>
-------------	--

Order no.	17-A1Z0-0010
-----------	--------------



Zapraszamy do kontaktu!
Więcej informacji: www.kreski.pl



Stylus

Description	<ul style="list-style-type: none"> - Suitable for capacitive touchscreen - 3 pieces - Color: black - With spiral cord
Order no.	B7-A2Z0-0062



Leather carry case

Description	<ul style="list-style-type: none"> - Certified in combination with MC93ex-NI - With shoulder strap - Robust industry quality leather
Order no.	B7-A2Z0-0060



Hand strap

Description	<ul style="list-style-type: none"> - 1 piece - Color: black
Order no.	B7-A2Z0-0071



Screen protector

Description	<ul style="list-style-type: none"> - Certified in combination with MC93ex-NI - 5 pieces <p>May only be changed outside the potentially explosive atmosphere!</p>
Order no.	B7-A2Z0-0061

Accessories for use outside potentially explosive atmospheres



4-slot battery charging station

Description	<ul style="list-style-type: none"> - Charging four batteries - Supports fast charging of the battery (charges from 0-90 % in about 3.5 hours)
Scope of delivery	4-slot battery charging station
Also required	(not included with delivery) <ul style="list-style-type: none"> - Power supply with DC connecting cable - AC power cable
Order no.	G7-A0Z0-0042



Base station

Description	<ul style="list-style-type: none"> - Charging the mobile computer - Charging an additional battery - Communication via USB - Supports fast charging of the Mobile computer and battery (charges battery from 0-90 % in about 3.5 hours) - LED notification of battery charging status
Scope of delivery	Base station
Also required	(not included with delivery) <ul style="list-style-type: none"> - Power supply with DC connecting cable - AC power cable
Order no.	G7-A0Z0-0041



Charging adapter for older Docking stations

Description	<ul style="list-style-type: none"> - Charge adapter for backward compatibility with MC9x Docking Station - Allows MC93 to be used with MC90/MC91/MC92 Docking Stations and 4-Slot Docking Stations - Adapter does not provide communications support! - Adapter does not support fast charging of MC93
Scope of delivery	Charging adapter
Order no.	G7-A0Z0-0043



4-slot Ethernet base station

Description	<ul style="list-style-type: none"> - Will charge up to four MC93ex-NI - Allows network speeds up to 1 GB - Provides Ethernet daisy chaining support for connecting multiple base stations together. - Supports fast charging of the Mobile computer (charges battery from 0-90 % in about 3.5 hours)
Scope of delivery	4-slot Ethernet base station
Also required	(not included with delivery) <ul style="list-style-type: none"> - Power supply with DC connecting cable - AC power cable
Order no.	G7-A0Z0-0044



Power supply with DC connecting cable

Description	<ul style="list-style-type: none"> - for 4-slot battery charging station and base station - Input voltage: AC 100 bis 240 V - Output voltage: DC 12 V/4.16 A/50 W
Order no.	G7-A0Z0-0023

Power supply with DC connecting cable

Description	<ul style="list-style-type: none"> - for 4-slot Ethernet base station - Input voltage: AC 100 bis 240 V - Output voltage: DC 12 V/9 A/180 W
Order no.	G7-A0Z0-0045



AC power cable

Description	3-wire, country-specific	
Order no.	Version: US + Canada	G7-A0Z0-0024
	Version: EU + APAC	G7-A0Z0-0026
Please purchase the required country-specific cables in the respective country!		



Zapraszamy do kontaktu!
Więcej informacji: www.kreski.pl