


# Premier Proximity Cards

## CREATE CUSTOM, PRE-PRINTED AND PROGRAMMED CARDS

Zebra Premier Proximity Cards enable customers to create custom, pre-printed and programmed cards with any Zebra card printer\*. The cards have a read range of up to 5 inches so users can scan their cards without removing them from badge holders, wallets and purses. The cards offer universal compatibility with proximity card readers.



When used in an access control application, Zebra Premier Proximity Cards are an effective way to protect company personnel and assets by restricting access to buildings, rooms or other secure locations.

Meeting ISO standards for thickness, these durable cards are made of high-quality PVC to be strong, yet flexible, and resistant to cracking and breaking. Additionally, they feature a printable PVC surface with a glossy finish. Zebra Premier Proximity Cards provide consistent high-quality printed cards every time.

Sold in boxes of 500, the cards can be formatted and pre-programmed with an external number for easy identification and control. And, the cards support 26-37 bit encoding and accept either a horizontal or vertical slot punch for integration into customers' current access control systems.

## Premier Proximity Cards Specifications

### GENERAL SPECIFICATIONS

- Size: CR80 (3.375" x 2.125")
- Thickness: 30mil +/- 10%
- Construction: High-quality PVC, Graphics Quality
- Color: White aGloss
- Packaging: 500 Cards/Sleeve
- Technology: Contactless LF (Low Frequency) Proximity Card
- Frequency: 125 KHz
- Read Range: 2" - 5"
- Compliance: ISO/IEC 7810, ISO/IEC 14443

### FORMATS

- 26-Bit Standard
- 34-Bit
- 35-Bit Corporate 1000
- 36-Bit
- 37-Bit

### OPTIONS

- Custom Pre-printing
- Security Features
- Magnetic Stripe
- Slot Punching
- Pre-programming

### FEATURES

- Offers universal compatibility with proximity card readers.
- Can be formatted and programmed with an external number for easy identification and control.
- Custom pre-printing and programming available.
- Meets ISO standards for thickness.
- Qualified for use with all Zebra Card printers.
- Accepts either a horizontal or vertical slot punch.
- Strong, flexible and resistant to cracking and breaking.

### Ideal for These Applications

- Access control
- Identity management
- Asset management



Specifications subject to change without notice.

\* Zebra printers do not encode proximity cards. Cards must be pre-encoded or encoded using a third-party external encoder.

For more information about the Premier Proximity Cards, visit [www.zebra.com](http://www.zebra.com) or access our global contact directory at [www.zebra.com/contact](http://www.zebra.com/contact)

NA and Corporate Headquarters  
+1 800 423 0442  
inquiry4@zebra.com

Asia-Pacific Headquarters  
+65 6858 0722  
contact.apac@zebra.com

EMEA Headquarters  
zebra.com/locations  
mseurope@zebra.com

Latin America Headquarters  
+1 847 955 2283  
la.contactme@zebra.com