

XENON XP ACCESSORIES GUIDE



TABLE OF CONTENTS

- 1 Wall Mounts, Stands, Holders, and Covers
- 1 Charge and Communication Bases, Chargers, and Batteries
- 2 Cables and Power Supplies



Zapraszamy do kontaktu!
Więcej informacji: www.kreski.pl

WALL MOUNTS, STANDS, HOLDERS, AND COVERS

				
1950GSR-2-2-X 1950GHD-2-2-X 1950GSR-2USB-2-X 1950GHD-2USB-2-X	50129064-001	STND-08R00-000-6	STND-15R00-000-6	STND-22F00-001-6
1950G Ratchet Stand Provides a fixed stand for a corded scanner that enables presentation scanning and two-handed scanning.	Wall-Mount Cup Holder Kit: Plastic bracket facilitates mounting of scanner to wall; two mounting screws included in kit.	Rigid Presentation Stand – 3” Stand: gray, 8 cm (3 in) height, rigid rod, large oval weighted base, cradle for Xenon™ 1900 and Xenon XP 1950 corded scanners.	Rigid Presentation Stand – 6” Stand: gray, 15 cm (6 in) height, rigid rod, large oval weighted base, Xenon cradle.	Flexible Presentation Stand – 9” Stand: gray, 22 cm (9 in) height, flexible rod, large oval weighted base, Xenon cup.
				
VISOR-190X-XT	VISOR 190X	UCOVERXENON	VMHOLDERE-21029	
Extended Sun Visor Extended sun visor for use in direct sunlight or extremely bright environments. For use with Xenon XP 1950 corded and 1952 cordless scanners.	Sun Visor Sun visor for use in direct sunlight or extremely bright environments. For use with Xenon XP 1950 corded and 1952 cordless scanners.	Retractable Lanyard Cover Fabric cover for hanging the scanner from a retractable lanyard.	Forklift Holder Forklift/vehicle-mounted holder for holding a Xenon XP 1950 corded scanner between scans.	

CHARGE AND COMMUNICATION BASES, CHARGERS, AND BATTERIES

				
BAT-SCN01A	BAT-SCN05	SUPCAP-SCN05	MB4-BAT-SCN01NADO	MB4-BAT-SCN01NAW0
Battery Pack Battery: Lithium-ion battery for Xenon 1902 and Xenon XP 1952 cordless scanners.	Smart Battery Pack Battery: Lithium-ion battery for Xenon XP 1952 cordless scanners.	SuperCap Pack Super Capacitor: Lithium-ion battery for Xenon XP 1952 cordless scanners.	4-Bay Battery Charger – Desk Mount 4-bay battery charger (NA) for use with Xenon 1902 and Xenon XP 1952 Lithium-ion batteries, NA desktop power supply (PS-050-4000D-NA), two mounting screws (100006897), and instructions (MBC-INST).	4-Bay Battery Charger – Wall Mount 4-bay battery charger (NA) for use with Xenon 1902 and Xenon XP 1952 Lithium-ion batteries, NA wall-mount power supply (PS-050-4000W-NA), two mounting screws (100006897), and instructions (MBC-INST).

CCB10-010BT-07N	CCB11-010BT-07N	CCB12-010BT-HC	CCB13-010BT-07N	CCB15-010BT-HC
1952 Presentation CCB – Black (Battery)	1952 Presentation CCB – Lyric White (Battery)	1952 Presentation CCB – Healthcare (Battery)	1952 Desktop/Wall-Mount CCB – Black (Battery)	1952 Desktop/Wall-Mount CCB – Healthcare (Battery)
Xenon XP 1952 Presentation CCB, black, 10 m (32.8 ft), Bluetooth®.	Xenon XP 1952 Presentation CCB, white, 10 m (32.8 ft), Bluetooth.	Xenon XP 1952 Presentation CCB, healthcare white, healthcare software.	Xenon XP 1952 Horizontal CCB, black, 10 m (32.8 ft), Bluetooth.	Xenon XP 1952 Horizontal CCB, healthcare white, healthcare software.

CABLES AND POWER SUPPLIES

CBL-020-300-C00	CBL-120-300-C00	CBL-220-300-C00	CBL-420-300-C00	CBL-500-150-S00
RS-232 Power Cable	RS-232 Power Cable	RS-232 Power Cable	RS-232 Power Cable	USB Power Cable
Cable: RS-232 (5V signals), black, DB9 Female, 3 m (9.8 ft), coiled, 5V external power with option for host power on pin 9.	Cable: RS-232C (+/-12V signals), black, DB9 Female, 3 m (9.8 ft), coiled, 5V external power with option for host power on pin 9.	Cable: RS-232 (+5V signals), black, DB9 Male, 3 m (9.8 ft), coiled, external power with option for host power on pin 9 for connection to Wincor Beetle.	Cable: RS-232 (5V signals), Honeywell Bioptic Stratos™ Aux, black, 10 pin modular, 3 m (9.8 ft), coiled, host power possible (dependent upon scanner and Stratos models).	USB Type A HSM 5V1.5 m (5 ft) straight cable.
CBL-500-300-S00	CBL-500-500-C00	CBL-503-300-C00	CBL-600-300-S00	CBL-600-400-C00
USB Power Cable	USB Power Cable	USB Power Cable	IBM Power Cable	IBM Power Cable
Cable: USB, black, Type A, 3 m (9.8 ft), straight, 5V host power.	Cable: USB, black, Type A, 5 m (16.4 ft), coiled, 5V host power.	Cable: USB, black, 12V locking, 3 m (9.8 ft), coiled, 5V host power.	Cable: IBM 46xx Port 9b, black, 3 m (9.8 ft), straight, 12V host power.	Cable: IBM 46xx Port 9b, 12V power, coiled, 4 m (13.1 ft).
CBL-720-300-C00	CBL-MAG-300-S00	46-00525	46-00526	46-00528
Keyboard Wedge Power Cable	RS-232 Power Cable	Power Supply – NA Plug	Power Supply – EU Plug	Power Supply – AU Plug
Cable: KBW, black, PS2, 3 m (9.8 ft), coiled, 5V external power with option for host power.	Cable: RS-232 (5V signals), Magellan Aux Port, black, 10 pin modular, 3 m (9.8 ft), straight, external power with option for host scanner power.	Power Supply: NA plug, 1.0A @ 5.2V DC, 90–255V AC @ 50–60 Hz.	Power Supply: EU plug, 1.0A @ 5.2V DC, 90–255V AC @ 50–60 Hz.	Power Supply: AU plug, 1.0A @ 5.2V DC, 90–255V AC @ 50–60 Hz.
46-00529				
Power Supply – CN Plug				
Power Supply: CN plug, 1.0A @ 5.2V DC, 90–255V AC @ 50–60 Hz.				

Kreski
Zapraszamy do kontaktu!
Więcej informacji: www.kreski.pl

Honeywell Safety and Productivity Solutions

9680 Old Bailes Road
Fort Mill, SC 29707
800-582-4263
www.honeywell.com