



Available on
EaziPrice

Z-Perform™ 1000D Removable

Media Type	Label	✓	Adhesive Type	Permanent	
	Receipt			Removable	✓
	Tag			No Adhesive	
	Wristband				
Material Type	Paper	✓	Environment	Indoor	✓
	Synthetic			Outdoor	
Printing Technology	Direct Thermal (no Ribbon Required)	✓	Properties	Cold Temperature	✓
	Thermal Transfer (Ribbon Required)			Deep Freeze	
Finish	Matte	✓		High Temperature	
	Gloss			Ultra High Temperature	
				High Tack	
				Chemical Resistance	-

Note: Z-Perform 1000D Removable is not recommended for applications involving long term exposure to sunlight, extreme heat or on a PVC surface.

Additional Features

- No ribbon required for direct thermal printing, therefore only one stock item needed
- Produces high contrast black images with recommended Zebra printers
- Good adhesion and clean removability on a wide variety of surfaces
- ISEGA approval for direct contact with dry and non-fatty foodstuffs
- Adhesive complies with European food regulations EC 1935/2004, EU 10/2011 and FDA 175.105 for direct contact with dry and non-fatty foodstuffs

Suggested Applications

- Indoor general purpose labelling and food labelling
- Labelling of most packaging materials
- Removable shelf-edge labelling, product and price labelling in retail
- Product Identification
- Work in progress labelling
- Removable labels for boxes, pallets, shelves or tote bins



Zapraszamy do kontaktu!
Więcej informacji: www.kreski.pl

Technical Specifications

	Description	Caliper
Facestock	Matte white uncoated thermal imaging paper	79 microns
Adhesive	Removable rubber adhesive	12 microns
Liner	60gsm glassine liner	51 microns
	Total	142 microns $\pm 10\%$

Recommended Zebra Printers:

Mobile, desktop, mid-range and high-performance thermal printers

Minimum Application Temperature:

When the label is applied, the environment and surface should be above this temperature

-10°C

Service Temperature Range:

Following correct application and appropriate dwell time (usually 24hrs) the media will withstand this temperature range

-30°C to 70°C

Recommended Storage Conditions:

Storage of product before use

6 months duration when stored at 20°C at 50% RH

Expected Life Span in Application:

Following correct application and appropriate dwell time (usually 24hrs) we expect, but do not warrant, a life span as indicated

Indoor use, for up to 1 year

Product Performance and Suitability

The information contained in this document is to be used for guidance only and is not intended for use in setting specifications. All purchasers of Zebra products shall be solely responsible for independently determining if the product conforms to all requirements of their unique application.

For testing of this material please order sample roll SAMPLE65028.



Zapraszamy do kontaktu!
Więcej informacji: www.kreski.pl