



Zdjęcie jest reprezentatywne



## Eaton 91PS8MBS

Eaton 91PS UPS, 8kVA, 8 kW scalable to 10 kW, No battery, Internal Maintenance Bypass

### General specifications

<b>PRODUCT NAME</b>	Eaton 91PS and 93PS UPS
---------------------	-------------------------

<b>CATALOG NUMBER</b>	91PS8MBS
-----------------------	----------

<b>EAN</b>	6430028229475
------------	---------------

<b>PRODUCT LENGTH/DEPTH</b>	750 mm
-----------------------------	--------

<b>PRODUCT HEIGHT</b>	950 mm
-----------------------	--------

<b>PRODUCT WIDTH</b>	335 mm
----------------------	--------

<b>PRODUCT WEIGHT</b>	76 kg
-----------------------	-------

<b>COMPLIANCES</b>	CE Marked RoHS Compliant CB
--------------------	-----------------------------------

<b>CERTIFICATIONS</b>	IEC/EN 62040-2 IEC/EN 62040-1 EN 62040-3 Manufactured in a plant certified to ISO 9001 and ISO 14001 management system standards
-----------------------	--

## Specyfikacje produktu

AUDIBLE ALARMS	Yes
AUTO SHUTDOWN FUNCTION	Yes
INTERNAL BATTERY INCLUDED	No, kits available
USER REPLACABLE BATTERIES	No
BATTERY CHARGER TYPE	ABM technology
EXTERNAL BATTERY CONNECTION	Hardwired
COLOR	Black
CONSTRUCTION TYPE	Free standing model
EFFICIENCY (ECO-MODE)	98 %
IMPROVED EFFICIENCY MODE	ESS
NUMBER OF COMMUNICATION SLOTS	2
FEED TYPE	AC
FORM FACTOR	Tower
HOT-SWAPPABLE POWER MODULES	No
INPUT CONNECTION	Fixed connection
NUMBER OF OUTPUT CONNECTIONS FIXED CONNECTION	1
OUTPUT FREQUENCY	50 Hz (50/60 Hz programmable)
OUTPUT POWER FACTOR	1
OVERALL EFFICIENCY	96 %
PACKAGE CONTENTS	<ul style="list-style-type: none"><li>• UPS</li><li>• Quickstart guide</li><li>• Safety instructions</li></ul>
PARALLELEABLE	Parallel for capacity and redundancy
NUMBER OF PARALLEL UNITS	4
PHASE (INPUT)	3
PHASE (OUTPUT)	1
POTENTIAL FREE SWITCH CONTACT	Yes
RUNTIME GRAPH	View runtime graph
SNMP	Yes

## Do pobrania

### DEKLARACJE ZGODNOŚCI

[eaton-91ps-93ps-declaration-of-conformity-pl.pdf](#)

[eaton-91ps-and-93ps-8-10kw-declaration-of-conformity-pl.pdf](#)

<b>START-ON-BATTERY</b>	Yes
<b>TOPOLOGY</b>	Online
<b>TYPE OF INTERFACE</b>	Other
<b>INTERNAL MAINTENANCE BYPASS</b>	Yes
<b>USER INTERFACE (HMI)</b>	5 inch touch-screen
<b>KVA RATING</b>	8 kVA
<b>WATTAGE</b>	8 kW
<b>NUMBER OF OUTPUT CONNECTIONS WITH PROTECTIVE CONTACT (SCHUKO)</b>	0
<b>APPLICATION</b>	Data center/ facility/IT
<b>OUTPUT EFFECTIVE POWER</b>	8000 W
<b>TRANSITION TIME FOR FULL LOAD</b>	0 s
<b>EFFICIENCY (IMPROVED EFFICIENCY MODE)</b>	98 %
<b>VOLTAGE DISTORTION OUTPUT (LINEAR LOAD) - MAX</b>	1.5 %
<b>INTEGRATED FUNCTIONALITY</b>	Network Mangement
<b>INPUT FREQUENCY - MIN</b>	50 Hz
<b>INPUT FREQUENCY - MAX</b>	60 Hz
<b>INPUT VOLTAGE - MIN</b>	220 V
<b>INPUT VOLTAGE - MAX</b>	415 V
<b>OUTPUT VOLTAGE - MIN</b>	220 V
<b>OUTPUT VOLTAGE - MAX</b>	240 V
<b>SECONDARY FREQUENCY MIN</b>	50 Hz
<b>SECONDARY FREQUENCY MAX</b>	60 Hz
<b>OUTPUT APPARENT POWER</b>	8000 VA
<b>PRIMARY FREQUENCY - MAX</b>	60 Hz
<b>PRIMARY FREQUENCY - MIN</b>	50 Hz
<b>RUNTIME AT HALF LOAD</b>	0 min
<b>RUNTIME AT FULL LOAD</b>	0 min
<b>MOUNTING METHOD</b>	Tower

PROJECT NAME:
PROJECT NUMBER:
PREPARED BY:
DATA:



Zapraszamy do kontaktu!  
Więcej informacji: [www.kreski.pl](http://www.kreski.pl)



**Eaton Corporation plc**

Eaton House  
30 Pembroke Road  
Dublin 4, Irlandia  
[Eaton.com](http://Eaton.com)

Follow us on social media to get the latest product and support information.



© 2025 Eaton. Wszelkie prawa zastrzeżone.