

Z-Ultimate® 3000T High-Tack

Media Type	Label	✓	Film Type	Polyethylene	
	Receipt			Polyolefin	
	Tag			Polypropylene	
	Wristband			Polyester	✓
Material Type	Paper			Polyimide	
	Synthetic	✓		Properties	Cold Temperature
Printing Technology	Direct Thermal (no Ribbon Required)		Deep Freeze		✓
	Thermal Transfer (Ribbon Required)	✓	High Temperature		✓
Adhesive Type	Permanent	✓	Ultra High Temperature		
	Removable		High Tack		✓
	No Adhesive		Chemical Resistance		Harsh
Finish	Matte		Environment	Indoor	✓
	Gloss	✓		Outdoor	✓

Additional Features

- Outstanding print quality, smear and scratch resistance
- Good resistance to moderate and harsh chemicals and solvents
- Aggressive adhesive offers superior adhesion to low energy plastics and rough, uneven surfaces
- Tear and water resistant
- UL approved for electronic equipment, as a label which will last as long as the product
- Long term durability for asset tracking
- BPA free
- Latex free adhesive

Suggested Applications

- Capital asset labelling
- Labelling of low energy plastics in demanding industrial applications
- Labelling of painted components in the automotive and electronic industry
- Irregular shaped applications
- White goods and serial number labelling
- Healthcare autoclave high pressure sterilisation
- Gloss materials are not suitable for fanfold applications

UL Recognised

Approved for use with the following ribbons:

- 4800
- 5095
- 5100



Technical Specifications

	Description	Caliper
Facestock	Gloss white topcoated polyester	50 microns
Adhesive	Permanent high-tack, high-shear adhesive	50 microns
Liner	65gsm white glassine liner	56 microns
	Total	156 microns ±10%

Recommended Zebra Printers: Mid-range and high-performance thermal printers

Recommended Zebra Ribbons: 4800, 5095, 5100

Minimum Application Temperature: 10°C
When the label is applied, the environment and surface should be above this temperature

Service Temperature Range: -40°C to 150°C
Following correct application and appropriate dwell time (usually 24hrs) the media will withstand this temperature range

Recommended Storage Conditions: 6 months duration when stored at 21°C at 50% RH
Storage of product before use

Expected Life Span in Application: Indoor use, 1 year+
Outdoor use, up to 1 year
Following correct application and appropriate dwell time (usually 24hrs) we expect, but do not warrant, a life span as indicated



Zapraszamy do kontaktu!
Więcej informacji: www.kreski.pl

Suggested Ribbons for Applications requiring Chemical Resistance

	Weak					Moderate				Harsh			Extreme				
	Blood	Body Fluid	Salt Water	Water	Window Cleaner	Alcohol	Ammonia	Bleach	IPA	Gasoline	Grease	Oil	Acetone	IR Reflow	MEK	TCE	Xylene
5095	✓	✓	✓	✓	✓	✓	✓	✓	✓		✓	✓					
5100	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓					

“✓” indicates acceptable chemical resistance

4800 ribbon will also provide chemical resistance, however requires testing in application

180° Angle Peel Adhesion at Room Temperature (N/m):

Stainless Steel	Acrylic	Glass
72 hrs	72 hrs	72 hrs
1342	1254	1243

Facestock Tensile Strength

- Machine direction: 18,000 psi
- Transverse direction: 22,000 psi

Note: For guidance only, not to be used for setting specifications

Product Performance and Suitability

The information contained in this document is to be used for guidance only and is not intended for use in setting specifications. All purchasers of Zebra products shall be solely responsible for independently determining if the product conforms to all requirements of their unique application.

For testing of this material please order sample roll SAMPLE65344.

