

Charger Specifications:

Temperature Limits:

Operating Range: 0°C to +35°C

Storage Range: -40°C to +85°C

Dimensions:

Width: 6.25 inches (159 mm)

Length: 6.5 inches (165 mm)

Height: 2.6 inches (66 mm) - without
batteries or devices inserted.

Weight: 1.2 pounds (0.54 kg)

Warranty:

Each charger is guaranteed
to be free from defects in
materials and workmanship
for 24 months from date of



Compatible Batteries:

HMC3000-IMG-Li Honeywell® Battery

- Highest quality cells used.
- Longer cycle life.
- Extremely rugged.
- Rigorous testing.



Trademarks are the sole property of their respective owners.
The Honeywell® Trademark is used under license from
Honeywell® International Inc.

Global Technology Systems

HCH-3006-CHG

Six-Bay MC3000 Battery Charger



Dual-chemistry charger

Supports Li-Ion and Li-Polymer chemistries.

Hassle-free mounting

Utilizes same mounting bracket as
Symbol® chargers for easy wall mounting.

Made of highly rugged aerospace
grade aluminium housing.

Includes power supplies and
cable.

More efficiency in less space

Charges 50% more batteries in
same space as OEM chargers.

Tri-color charging indications

A charging LED indicates charging

