

HCH-3033-CHG

Charger Specifications:

Temperature Limits:

Operating Range: 0°C to 40°C
32°F to 104°F
Storage Range: -10°C to 50°C
14°F to 122°F

Dimensions:

Length: 420 mm
Width: 160 mm
Height: 108 mm
Weight: 1150 g

Warranty:

Each charger is guaranteed to be free from defects in materials and workmanship for 24 months from date of shipment under normal use.



Compatible Batteries

HMC3X00-Li(S) GTS Battery
HMC3000-LAS-Li GTS Battery

- Highest quality cells used
- Longer cycle life
- Extremely rugged
- Rigorous testing



Trademarks are the sole property of their respective owners.

14.05.16

3 Bay Cradle & 3 Bay Battery Charger

Dual-chemistry charger
Supports Li-Ion and Li-Polymer chemistries.

Includes power supplies and cable.

More efficiency in less space
Charges three spare batteries plus the batteries in three devices simultaneously and fast

Made of highly rugged aerospace grade aluminum housing.



Tri-color charging indications
A charging LED indicates charging status.



Hassle-free mounting
Utilizes same mounting bracket as Symbol® chargers for easy wall mounting.

Can easily be customized to meet your customer needs.

Zapraszamy do kontaktu!
Więcej informacji: www.kreski.pl

For Pricing or Additional Information Contact:

Global Technology Systems, Inc.
550 Cochituate Road Framingham, MA 01701
US: 1.800.267.2711 ■ EU: 00800.5390.5390
www.GTSpower.com @GTSpower1