

Charger Specifications:

Temperature Limits:

Operating Range: 0°C to 40°C
32°F to 104°F

Storage Range: -10°C to 50°C
14°F to 122°F

Dimensions:

Length: 333 mm
Width: 159.69 mm
Height: 113 mm
without device inserted.
Weight: 900 g

Warranty:

Each charger is guaranteed to be free from defects in materials and workmanship for 24 months from date of shipment under normal use.



Compatible Batteries

HMC3X00-Li(S) GTS Battery

HMC3000-LAS-Li GTS Battery

- Highest quality cells used
- Longer cycle life
- Extremely rugged
- Rigorous testing



Trademarks are the sole property of their respective owners.

HCH-3030-CHG

3 Bay Cradle Charger for the Motorola® MC3000/MC3100 Devices

More charging in less space

Charges 50% more batteries in same space as OEM charger.

Includes power supplies and cable.

Dual-chemistry charger

Supports Li-Ion and Li-Polymer chemistries.



Tri-color charging indications

A charging LED indicates charging status.



Hassle-free mounting

Utilizes same mounting bracket as Symbol® chargers for easy wall mounting.

Made of highly rugged aerospace grade aluminum housing.

For Pricing or Additional Information Contact:

Global Technology Systems, Inc.

550 Cochituate Road Framingham, MA 01701

US: 1.800.267.2711 ■ EU: 00800.5390.5390

www.GTSpower.com @GTSpower1

Zapraszamy do kontaktu!
Więcej informacji: www.kreski.pl