

X-Series

AiO Touchscreen Computers



Integrated Touch



Commercial Grade



3-Year Warranty

Product Overview

The Elo X-Series 15-inch, 17-inch and 20-inch All-in-One (AiO) touchcomputers bring style, flexibility and functionality to applications in any retail, self-service or hospitality environment that requires a small footprint POS terminal or kiosk. The X-Series AiO's are available with industry-leading touchscreen technologies including AccuTouch® micro-bezel 5-wire resistive, IntelliTouch® surface acoustic wave, IntelliTouch zero-bezel surface acoustic wave (SAW) and TouchPro™ Projected Capacitive (PCAP).*

With processor options that scale from the value-based Intel Celeron J1900 to the high-performance Intel Core i7, the X-Series is one of the most powerful systems in its class. And with the wide array of field-installable peripherals, spill-resistant sealing and a range of input/output port connection options, versatility is endless.

Full range of standard connectivity ports for retail POS/POI and hospitality applications

Customer-installable peripheral options - MSR, NFC/RFID, Barcode Reader, EMV and customer-facing displays

The unique, modular chassis provides easy access to storage and memory for quick, tool-less service

* 20-inch X-Series AiO touchcomputer comes in PCAP only.



Zapraszamy do kontaktu!
Więcej informacji: www.kreski.pl

X-Series All-in-One Touchscreen Computers

Model	X2 Model (Fanless)	X3 Model (Fanned-Performance)	X5 Model (Fanned-Ultra)	X7 Model (Fanned-Extreme)
Processor	Intel® Celeron® Processor J1900 (2M Cache, up to 2.42 GHz)	Intel® Core i3-4350T Processor (4M Cache, 3.10 GHz) 4 MB Intel® Smart Cache 5 GT/s Direct Media Interface 2 (DMI2)	Intel® Core i5-4590T Processor (6M Cache, up to 3.00 GHz) by Intel® Turbo Boost Technology 2.0) 6MB Intel® Smart Cache 5 GT/s Direct Media	Intel® Core i7-4790T Processor (8M Cache, up to 3.90 GHz) by Intel® Turbo Boost Technology 2.0) 8MB Intel® Smart Cache 5 GT/s Direct Media Interface 2 (DMI2)
Chipset	N/A	Intel H81 Express	Intel Q87 Express	
Video	Intel HD Graphics	Intel HD Graphics 4600		
BIOS	AMI			
Memory (RAM)	4GB 1600MHz DDR3L SO-DIMM on 1 of 2 slots - Expandable to 16GB maximum on 2 slots			
Storage	128GB 2.5" SATA SSD. Additional options include 320GB 5400 rpm HDD, 500GB 7200 rpm HDD, 1TGB 5400 rpm HDD, 256GB 2.5" SATA SSD			
RAID	N/A		RAID 0 / RAID 1	
TPM	N/A		TPM 1.2	
USB Ports	2 x USB 3.0 on I/O, 4 x USB 2.0 (2 on I/O, 2 on USB Front Access) 3 x USB 2.0 on edges for optional Elo peripherals.		4 x USB 3.0 on I/O, 2 x USB 2.0 (USB Front Access). 3 x USB 2.0 on edges for optional Elo peripherals.	
Powered USB	N/A	1 x 24V; 1 x 12V (On Expansion Module)		
Serial Ports	1 x Serial RS-232 (standard), 1 x RJ45 (Native serial); 2 additional on Expansion Module.			
Parallel Ports	N/A			
Ethernet Port	1 x LAN RJ45 (Gigabit), 1 additional on Expansion Module			
Wireless LAN	802.11 b/g/n			
Bluetooth	BT 4.0			
Cash Drawer Port	12V/24V Cash Drawer Port on Expansion Module (24V default; selectable by BIOS setting)			
Additional Video Out	2nd VGA output			
Audio Ports	1 x 3.5 mm Line out, 1 x 3.5 mm MIC in			
Speakers	Two 2W internal speakers			
Operating System Options	No Operating System, Microsoft Windows 7 Professional 32/64-bit, Microsoft Windows POSReady7 32/64-bit, Microsoft Windows 8.1 Industry Embedded Pro 32/64-bit			
Control Buttons	Power, brightness up, brightness down, volume up, volume down, Security Lockouts: Power and Control buttons lock.			
Aspect Ratio	15" models: 4:3 (standard), 17" models: 5:4 (standard), 20" models: 16:9 (standard)			
Active Display Area (W x H)	15" models: 11.97" x 8.98" (304.12mm x 228.1mm) 15" diagonal, active matrix TFT LED LCD, 17" models: 13.30" x 10.64" (337.92mm x 270.36mm) 17" diagonal, active matrix TFT LED LCD, 20" models: 17.1" x 9.39" (434.88mm x 238.68mm) 20" diagonal, active matrix TFT LED LCD			
Native (Optimal) Resolution	15" models: 1024 x 768 @ 60Hz, 17" models: 1280 x 1024 @ 60Hz, 20" models: 1920 x 1080 @ 60Hz			
Brightness (Typical)	LCD panel: 250 nits, AccuTouch: 200 nits, IntelliTouch: 225 nits, IntelliTouch zero-bezel: 225 nits, PCAP: 212.5 nits			
Response Time Total (Typical)	15" models: Total: 16 msec,17" models: Total: 5 msec, 20" models: Total: 20 msec			
Viewing Angle (Typical)	15" models: Horizontal: 80°/85° or 165° total,Vertical: 70°/80° or 150° total, 17" models: Horizontal: ± 85° or 170° total, Vertical: ± 80° or 160° total 20" models: Horizontal: 178° total, Vertical: 178° total			
Contrast Ratio (Typical)	15" models: 700:1, 17" models: 1000:1, 20" models: 3000:1			
Power Supply	External 19VDC universal-type power supply brick, AC input voltage: 100-240 VAC, Input frequency: 50-60 Hz, Maximum output power: 90W (Max Draw: 100W)	External 19VDC universal-type power supply brick AC input voltage: 100-240 VAC Input frequency: 50-60 Hz Maximum output power: 150W (Max Draw: 170W)		
Maximum Touchcomputer Dimensions With Stand (W x H x D)	15" models: 14.38" x 13.73" x 2.65" (365.18mm x 348.84mm x 251.7mm), 17" models: 15.64" x 15.40" x 2.86" (397.29mm x 391.07mm x 251.7mm) 20" models: 19.37" x 14.05" x 9.91" (492.12mm x 356.9mm x 251.7mm)			
Weight (With stand and Expansion Module)	15" models: 16.32 lbs (7.41kg), 17" models: 17.09 lbs (7.76kg), 20" models: 17.73 lbs (8.05kg)			
Temperature	Operating: 0°C to 35°C (32°F to 95°F), Storage: -20°C to 60°C (-4°F to 140°F)			
Humidity (non-condensing)	Operating: 20% to 80%, Storage: 5% to 95%			
Regulatory Approvals / Declarations	15" & 17" models: UL/cUL , FCC, TUV, CE, CB, Mexico COC, C-Tick, VCCI, Argentina S-Mark, CCC, 20" models: UL/cUL , FCC, TUV, CE, CB			
Mounting Options	100mm VESA mount or secure base to tabletop/desktop			
MTBF	50,000 hours demonstrated			
Warranty	Three years (Extend two years with additional charge)			
What's in the Box	X-Series Touchcomputer, North America Power Cord; EU Power Cord; Power Adapter - 150W: X3/X5/X7 Or 90W: X2; Adapter Cable RJ-45 to DB-9; Cable cover locking screw, Quick Installation Guide (QIG)			

To find out more about our extensive range of Elo touch solutions, go to elotouch.com, or call the office nearest you.

North America

Tel +1 408 597 8000
Fax +1 408 597 8050
elosales.na@elotouch.com

Europe

Tel +32 (0)16 70 45 00
Fax +32 (0)16 70 45 49
elosales@elotouch.com

Asia-Pacific

Tel +86 (21) 3329 1385
Fax +86 (21) 3329 1400
www.elotouch.com.cn

Latin America

Tel +1 786-923-0251
Fax +1 305-931-0124
elosales.latam@elotouch.com

Elo reserves the right to change or update, without notice, any information contained herein; to change, without notice, the design, construction, materials, processing or specifications of any products; and to discontinue or limit production or distribution of any products. Elo, the Elo logo, AccuTouch, IntelliTouch and TouchPro are either trademarks or registered trademarks of Elo Touch Solutions, Inc. All other trademarks are the property of their respective owners. © 2017 Elo Touch Solutions, Inc. All rights reserved. 17041AES00020

