



UX10 FULLY RUGGED TABLET

- 10th Generation Intel® Core™ i7/i5 Processor
- 10.1" FHD LumiBond® 2.0 Display with Getac Sunlight Readable Technology (1,000 nits) and Capacitive Touchscreen
- Enhanced Enterprise Security with Optional Intel vPro™, Windows Hello Face-authentication Camera and Multi-factor Authentication Options
- Detachable Keyboard and Multifunctional Hard Handle for On-the-job Flexibility
- Multiple Configurable Options to Fit Diverse Usage Scenarios



Detachable Keyboard



Hard Handle



Specifications

Operating System

Windows 10 Pro

Mobile Computing Platform

Platform Options:

- Intel® Core™ i7 Technology
- Intel® Core™ i7-10510U Processor 1.80 GHz
- 8MB Intel® Smart Cache
- Intel® Core™ i7 vPro™ Technology
- Intel® Core™ i7-10610U Processor 1.80 GHz vPro
- 8MB Intel® Smart Cache
- Intel® Core™ i5 Technology
- Intel® Core™ i5-10210U Processor 1.60 GHz
- 6 MB Smart Cache
- Intel® Core™ i5 vPro™ Technology
- Intel® Core™ i5-10310U Processor 1.70 GHz vPro
- 6MB Intel® Smart Cache

VGA Controller

Intel® UHD Graphics

Display

- 10.1" IPS TFT LCD FHD (1920 x 1200)
- 1000 nits LumiBond® display with Getac sunlight readable technology
- Capacitive multi-touch screen

Storage & Memory

- 8GB DDR4
- Optional: 16GB / 32GB DDR4
- 256GB PCIe NVMe SSD
- Optional: 512GB / 1TB PCIe NVMe SSD

Keyboard

- 6 tablet buttons (Windows, Power, Function Key, Camera Capture/ Barcode Reader Trigger, Volume Up, Volume Down)

Pointing Device

- Touchscreen
- Capacitive multi-touch screen
- Optional: Dual mode touchscreen (multi-touch and digitizer)

Expansion Slot

- Optional (top side): 1D/2D imager barcode readerⁱ, or serial port, or MicroSD slot, or USB 3.0 Type-A port, or USB 3.1 Gen 1 Type-C port, or LAN port (RJ-45), or VGA portⁱⁱ, or HF RFID reader.
- Optional (right side): fingerprint reader, or serial port+LAN port (RJ-45), or HF RFID reader^v.
- Optional (back side): smart card reader, or bridge battery, or bridge battery+smart card reader^v

I/O Interface

- FHD webcam x 1 or Optional Windows Hello face-authentication camera (front-facing) x 1
- 8M pixels auto focus rear camera x 1
- Headphone out / mic-in combo x 1
- DC in Jack x 1
- USB 3.1 Gen 2 Type-A x 1
- HDMI x 1
- Docking connector x 1
- Optional: RF antenna pass-through for GPS, WLAN and WWAN

Communication Interface

- Optional: 10/100/1000 base-T Ethernet
- Intel® Wi-Fi 6 AX200, 802.11ax
- Bluetooth (v5.1)^{vi}
- Optional: Dedicated GPSⁱⁱⁱ
- Optional: 4G LTE mobile broadband with integrated GPSⁱⁱⁱ

Security Feature

- Optional: Intel® vPro™ Technology
- TPM 2.0
- Optional: HF RFID reader^{i,ii}
- Optional: Fingerprint scanner^v
- Optional: smart card reader^v
- Kensington lock

Power

- AC adapter (65W, 100-240VAC, 50 / 60Hz)
- Li-Ion smart battery (11.1V, typical 4200mAh; min.4080mAh) x 1
- Optional: High capacity battery (10.8V, 9240mAh) x 1
- Optional: Bridge battery^v

Dimension (W x D x H) & Weight

- 276.8 x 194.5 x 23.5 mm (10.89" x 7.65" x 0.92"), 1.22 kg (2.68 lbs)^{vii}

Rugged Feature

- MIL-STD-810H certified and IP65 certified
- MIL-STD-461G certified^{viii}
- Optional: ANSI/UL 121201, CSA C22.2 NO. 213
- Optional: Salt fog certified
- 6 feet drop resistant^{ix,x}
- e-Mark certified for vehicle usage

Environmental Specification

- Temperature^x:
 - Operating: -29°C to 63°C / -20°F to 145°F
 - Storage: -51°C to 71°C / -60°F to 160°F
- Humidity:
 - 95% RH , non-condensing

Software

- Getac Utility
- Getac Camera
- Getac Geolocation
- Getac Barcode Manager
- Optional Absolute Persistence

Accessories

- Carry bag
- Multi-bay charger (Dual Bay)
- Multi-Bay charger (Eight-Bay)
- Vehicle adapter (120W, 11-32VDC)
- AC adapter (65W, 100-240VAC)
- Office dock AC adapter (90W, 100-240VAC)
- MIL-STD-461 certified AC adapter (90W, 100-240VAC)
- Digitizer pen
- Capacitive stylus (Hard-tip)
- Protection film
- Tablet folio case
- Hand strap
- Shoulder harness (4-point; handsfree)
- Shoulder strap (2-point)
- Standard battery (11.1V, typical 4200mAh; min. 4080mAh)
- High capacity battery (10.8V, 9240 mAh)
- Detachable keyboard
- Vehicle dock
- Office dock

Bumper-to-Bumper warranty

Accidents can take your equipment out of service when you least expect it, especially in a rugged environment, which can cause costly equipment downtime.

That is why Getac has introduced accidental damage as standard under our Bumper-to-Bumper warranty, to help minimize your enterprise IT costs.

Bumper-to-Bumper is your hassle-free guarantee.

That means you can depend on us to have your unit back in service within days.

Standard

3 years Bumper-to-Bumper

- i 13.56MHz Contactless HF RFID reader (ISO 15693, 14443 A/B, Mifare and FeliCa™ compliant).
- ii 1D/2D imager barcode reader, HF RFID reader, serial port, LAN port (RJ45), USB 3.0 port, USB 3.1 Gen 1 Type-C port, MicroSD slot and VGA port are mutually exclusive options.
- iii Supports GPS and Glonass.
- iv Fingerprint scanner, HF RFID reader and serial port+LAN port (RJ45) are mutually exclusive options.
- v Smart card reader, bridge battery and bridge battery+smart card reader are mutually exclusive options.
- vi Bluetooth performance and connectable distance may be subject to interference with the environments and performance on client devices, users may be able to reduce effects of interference by minimizing the number of active Bluetooth wireless devices that is operating in the area.
- vii Weight and dimensions vary from configurations and optional accessories.
- viii MIL-STD-461G 90W AC adapter sold separately.
- ix Drop test results vary from configurations and optional accessories.
- x Tested by a national independent third party test lab following MIL-STD-810H.

UX10

Fully Rugged Tablet



Docking Solutions

	Vehicle Dock	Office Dock
Serial Port	1	1
VGA	--	1
Microphone	--	1
Audio Output	--	1
DC in Jack	1	1
USB	USB 3.0 x2 USB 2.0 x2	USB 3.0 x2 USB 2.0 x2
LAN	1	1
HDMI	--	1
RF Antenna Connector	3 (WWAN, WLAN, GPS)	--
Kensington Lock	1	1

Getac

GETAC TECHNOLOGY CORPORATION

5F, Building A, No. 209, Section 1, Nangang Rd., Nangang Dist., Taipei City, 11568, Taiwan, R.O.C.
Tel : +886 2 2785 7888
globalmarketing@getac.com | www.getac.com



Copyright © 2020 Getac Technology Corporation and/or any of its affiliates. All Rights Reserved.
Information provided herewith is for reference only,
available specification shall be subjected to quotation by request. V01M08Y20WW