

CN75

Ultra-Rugged Mobile Computer

The Honeywell CN75 and CN75e mobile computers offer the versatility customers demand, providing the choice of a Windows® or Android™ operating system on a single device to meet changing enterprise business demands. The no-compromise design is powered by a 1.5 GHz dual-core, multi-engine processor with 2 GB RAM and 16 GB Flash, offering the highest degree of future-proofing capability.

Specifically designed for mobile field service workers who need power and performance in a compact form factor, the Honeywell CN75 mobile computer offers the perfect balance of ruggedness, duty cycle and ergonomics while providing unparalleled versatility. The CN75e device offers the same power-packed computing but with a larger keypad design, making it ideal for delivery environments where workers may be wearing gloves or have more data input-intensive applications.

The CN75 and CN75e mobile computers deliver unparalleled reliability with smart battery technology that provides enough power to last a full work shift, eliminating dead batteries and downtime. The CN75 and CN75e mobile computers are also equipped with a high-performance imager that provides fast and accurate barcode scanning capabilities even in low-light scanning environments, with unmatched motion tolerance to eliminate costly delays in scan-intensive applications.

The no-compromise design extends to radio connectivity, as well. The wide-area solutions feature a Flexible Network voice and data WWAN radio that operates on networks worldwide, offering switch-on-the-fly network selection capability and eliminating the need for multiple pools of devices dedicated to one network.



The CN75 and CN75e mobile computers' no-compromise design provides the power and performance required by today's mobile field service and transportation workers.

FEATURES & BENEFITS



Supports Windows Embedded Handheld 6.5 and Android 6.0 Marshmallow operating systems for flexible application support and migration.



Flexible radio technology provides optimal network coverage and a superior solution for implementing least-cost routing strategies.



Withstands 2.4 m (8 ft) drops to concrete, 2,000 (1 m) tumbles and has an IP67 seal rating against rain and dust.



Advanced barcode imaging technology with motion tolerance for snappy scanning and white illumination with laser aiming for high read rates.



Full compatibility with printers, application software, communications and a complete set of peripherals and accessories, enabling a comprehensive enterprise business solution.

CN75 Technical Specifications

PHYSICAL CHARACTERISTICS

CN75 Dimensions with Battery:

L x W x D: 16.9 cm x 8.0 cm x 3.4 cm
(6.65 in x 3.15 in x 1.34 in)

Weight: 450 g (15.9 oz) with battery

CN75e Dimensions with Battery:

L x W x D: 19.5 cm x 8.0 cm x 3.4 cm
(7.66 in x 3.15 in x 1.34 in)

Weight: 491 g (17.3 oz) with battery

ENVIRONMENTAL

Operating Temperature: -20°C to +60°C
(-4°F to +140°F)*

Storage Temperature: -30°C to +70°C
(-22°F to +158°F)

Charging Temperature: +5°C to +35°C
(41°F to 95°F)

Relative Humidity: Non-condensing, 95%

Rain and Dust Resistance: IP67

Drop Spec: 2.4 m (8 ft) to concrete per MIL-STD 810G,
1.8 m (6 ft) to concrete across operating temperature
range per MIL-STD 810G, 2,000 (1 m) tumbles per IEC
60068-2-32 specification

Electrostatic Discharge: +/-15 kV air discharge;
+/-8 kV direct discharge

POWER

Battery Pack: 3.7 V, 4000 mAh; IEEE 1725
compliant, Li-Ion, removable, rechargeable

OPERATING SYSTEM

Microsoft® Windows Embedded Handheld 6.5 or
Android 6.0 Marshmallow with GMS

MULTI-ENGINE PROCESSOR ARCHITECTURE

Texas Instruments 1.5 GHz OMAP 4470 dual-core,
multi-engine processor architecture

MEMORY

RAM: 2 GB

ROM: 16 GB Flash

Storage Expansion: Customer-accessible micro-SD
slot for removable memory cards up to 32 GB

DISPLAY

8.9 cm (3.5 in) Transmissive VGA

480 x 640 pixels

65,536 (16-bit RGB) colors

High-durability touch screen

Hardened Corning® Gorilla® Glass display for
superior durability

LED backlight

Ambient light sensor

STANDARD COMMUNICATIONS

USB – Full Speed 2.0 Host, USB – Full Speed 2.0 Client

SOFTWARE APPLICATIONS AND COMPONENTS

Device Management:

SmartSystems™ Foundation provides a single,
integrated environment for hands-free deployment
and management of devices on-site or remote. Also
compatible with leading third-party data and device
management products.

ScanNGo for easy barcode-based enterprise-wide
device provisioning. It can be used to download
device management software from Honeywell ISVs.

CloneNGo, a peer-to-peer device management
software that enables simple device cloning,
eliminating the need to use a management console
for device provisioning.

Application Development: Honeywell Developer Library

Device Health Monitoring: On-board monitoring of
key subsystems including scanning, communications
and battery life

Optional Honeywell Enterprise Client Pack: Terminal
Emulation and HTML 5 Browser

Optional Launcher: Application locking

DATA MANAGEMENT

Skynax® Mobile Communications

INTEGRATED RADIOS

Wireless WAN: Worldwide Voice and Data
(can switch between UMTS and CDMA radio networks)

UMTS/HSPA+

UMTS Frequencies: 800, 850,
900, 1900, 2100 MHz

GSM/GPRS/EDGE Frequencies:
850, 900, 1800, 1900 MHz

Max Speeds (Network Dependent):
Uplink – 5.76 Mbps; Downlink – 14.4 Mbps

CDMA/EV-DO Rev A

Dual Band CDMA2000 Bands: BCO
& BC1 (800/1900 MHz)

Max Speeds (Network Dependent):
Uplink – 1.8 Mbps; Downlink – 3.1 Mbps

Wireless LAN: IEEE 802.11 a/b/g/n

Security: Wi-Fi Certified for WPA and WPA2,
WAPI Certified

Authentication: 802.1x

Cisco Compatibility: CCXv4

Encryption: WEP (64- or 128-bit), AES, TKIP

Wireless PAN: Integrated Bluetooth® Power Class 1.5
Version 4

GLOBAL POSITIONING SYSTEM (with WAN Radio Option)

12-channel integrated GPS; network-independent
autonomous mode; supports assisted operation via
XTRA®, CP E911

GPS dedicated AT commands

Protocol: NMEA-0183 V2.3

Tracking Sensitivity: better than -158 dBm

GLONASS support

CN75 Technical Specifications, continued

SENSOR TECHNOLOGY

Accelerometer: Embedded accelerometer enables automatic or application-specific features such as screen rotation or system suspend

AUDIO SUPPORT

Supports VoIP/speech recognition/push-to-talk applications; front and rear speakers; rear speaker >80 dB at 40 cm (15.7 in); front receiver and front panel microphone for handset audio communication and audio recording; wireless Bluetooth headset support; wired headset support via snap-on adapter

INTEGRATED SCANNER

EA30 High-Performance Motion-Tolerant 2D Imager: (up to 500 in/s) white LED illumination; red laser aimer and framer optimized for all lighting conditions. Capable of scanning all common 1D and 2D barcodes; 1D as small as 4 mils; 2D as small as 6.6 mils. Refer to User's Manual for depth-of-field performance.

INTEGRATED CAMERA

5-megapixel auto-focus color camera with LED flash

KEYPAD OPTIONS

All keypad options feature backlit hard keycaps with laser-etched legends.

CN75:



NUMERIC KEYPAD



QWERTY KEYPAD

CN75e:



LARGE NUMERIC KEYPAD



QWERTY KEYPAD

HONEYWELL GLOBAL SERVICES SUPPORT

Contact for Support: www.hsmcontactsupport.com

Public Knowledgebase Articles:

www.hsmknowledgebase.com

Telephone support available in North America (800-782-4263). Outside of this area, contact your local representative.

ACCESSORIES

FlexDock modular docking system, vehicle dock, vehicle holder, snap-on adaptors, removable scan handle, magnetic stripe reader, 6822 full-page printer and PW50 workboard printer

REGULATORY APPROVALS AND COMPLIANCE

CN75LAN, CN75WAN

Safety: cULus Listed, BSMI

EMC: Class B – FCC/ICES/EN, GOST-R

Radio: FCC, Industry Canada, A-tick (AU), NCC, IDA, ICASA, POSTEL, NTC, ETA, SIRIM, ANATEL

Environmental: EU Directives-WEEE; RoHS; Batteries and Accumulators; Packaging and Waste Packaging

NON-INCENDIVE VERSION

CN75 and CN75e with NI certification comply with the following: Suitable for use in Division 2 locations

Safety: cULus Listing – ISA/ANSI 12.12.01

Gases: Class I – Groups A, B, C, D

Dusts: Class II – Groups F, G

Fibers and Flyings: Class III

***Max. Ambient:** 50°C (122°F) T6

For a complete listing of all compliance approvals and certifications, please visit www.honeywellaidc.com/compliance.

For a complete listing of all supported barcode symbologies, please visit www.honeywellaidc.com/symbologies.

Microsoft and Windows are trademarks or registered trademarks of Microsoft Corporation in the United States and/or other countries.

Bluetooth is a trademark or registered trademark of Bluetooth SG, Inc. in the United States and/or other countries.

Corning and Gorilla Glass are trademarks or registered trademarks of Corning, Inc. in the United States and/or other countries.

SmartSystems and Skynax are trademarks or registered trademarks of Honeywell International Inc. in the United States and/or other countries.

All other trademarks are the property of their respective owners.



For more information

www.honeywellaidc.com

Honeywell Safety and Productivity Solutions

9680 Old Bailes Road

Fort Mill, SC 29707

800-537-6945

www.honeywell.com



Zapraszamy do kontaktu!

Więcej informacji: www.kreski.pl