



NORDIC ID HH85



THE TOUGHEST MEMBER OF THE ANDROID FAMILY

Created in the forests of Finland. The Nordic ID HH85 builds on an IP65 and 1.6-meter drop tested frame which is useful when tracking your assets in difficult environments. The ergonomic pistol grip design is easy to hold even when wearing gloves.

In these challenging conditions the reader must perform, and this is where one of the lightest, rugged designs in the RFID market can help. The battery gives you up to 18 hours of continuous operation while using one of the largest displays in the industry.

Of course you need brains and brawn. The Nordic ID HH85 is equipped with Android 9 software that complies with your IT rules and fits your needs perfectly.

The software also allows options that are designed to help. The camera can capture important information regarding possible damage to your assets or reception of goods.

This rugged, intelligent, and flexible device is the perfect match for industrial applications.

NORDIC ID HH85 RFID ACD



UHF RFID



WLAN



LTE



2D Imager
Barcode



Bluetooth



GNSS



Android
9

PRODUCT HIGHLIGHTS

- Market leading state-of-the-art UHF RFID performance
- Future proof your data collection with this powerful industrial level RAIN RFID performance
- Protect your investment thanks to its superior ruggedness
- Unique combination of large display and ergonomic pistol grip
- Ergonomic design focused on comfortable use
- Operates 18 hours on a single charge
- Android operating system for easy application development
- Fully integrated to Nordic ID solutions

NORDIC ID HH85 RFID ACD



UHF RFID IDENTIFICATION

| | |
|-------------------------|--|
| Supported standard | ISO 18000-63 (EPC Class 1 Gen2v2) |
| Frequency | ETSI 865.6–867.6 MHz or FCC/IC 902–928 MHz |
| RF radiated power | Max. ERP 2 W (33dBm) / EIRP 3.3 W (35.2dBm) Adjustable in 1dB steps (30 steps) |
| Antenna features | <ul style="list-style-type: none">• Software controllable antenna polarizations (vertical, horizontal or vertical/horizontal switching)• Reading range up to 15 m / 50 ft |
| Max receive sensitivity | -80 dBm |
| Typical reading speed | Up to 1000 tags per second |

BARCODE IDENTIFICATION AND IMAGING

| | |
|-----------|---|
| 2D imager | <ul style="list-style-type: none">• All major 1D barcodes and 2D codes• High visibility LED aimer• 2 characters pre and post fixes, padding, replacement• Enhanced aiming mode (automatic switching between scan line / aiming dot)• Configurable scan alert sounds |
| Camera | 5 Mpix rear-facing camera with auto focus and LED flash (torch mode supported) |

PLATFORM

| | |
|------------------|---|
| RFID | Nordic ID NUR2-1W reader module |
| CPU | Octa-Core ARM Cortex-A53 1.8 GHz |
| Operating system | Android 9 |
| Memory | <ul style="list-style-type: none">• 2 GB RAM• 16 GB Flash• MicroSD slot with support for SDXC cards |
| Sensors | Accelerometer, ambient light sensor, Time of Flight sensor (only in barcode variant), proximity sensor, pedometer, gyroscope |

USER INTERFACE

| | |
|------------------------|--|
| Display | <ul style="list-style-type: none">• 4.7 HD capacitive touch screen, 1280 x 720 pixels, 16.7 M colors• Adjustable LED backlight, Daylight readable, Gorilla glass 3, usage with gloves supported |
| Keypad | 3 backlit physical keys below the display, 2 customizable trigger buttons on the sides, 1 trigger button on the pistol grip |
| Audio | Microphone, earpiece and IHF speaker |
| Signals and indicators | RGB LED and vibra for haptic feedback |

DROP AND SHOCK

| | |
|----------------------------|---|
| Drop and impact resistance | 1.6 m / 5.2 ft |
| ESD | Contacts +/- 4 kVdc Air discharge +/- 8 kVdc |

CONNECTIVITY

| | |
|-------------------------|---|
| Wireless WAN (optional) | Europe <ul style="list-style-type: none">• 4G LTE (B1/B3/B5/B7/B8/B20/B28A/B38/B40/B41)• 3G WCDMA (B1/B2/B5/B8)• GPRS / EDGE (850/900/1800/1900) |
| GNSS (optional) | Assisted GPS, BeiDou, GLONASS and Galileo |
| Wireless LAN | IEEE 802.11 a/b/g/n/ac. Dual band WLAN, supports 2.4 GHz and 5 GHz networks |
| Wireless PAN | <ul style="list-style-type: none">• Bluetooth 4.2 Class 2• Classic and Low Energy modes supported |
| PAN | <ul style="list-style-type: none">• USB 2.0 via USB Type-C connector• Desktop charger provides USB connectivity via USB Type-C connector |
| NFC | NFC standards supported: ISO/IEC 14443A, ISO/IEC 14443B, FeliCa, ISO/IEC 15693 (Vicinity) |

POWER

| | |
|-----------------------|--|
| Battery | <ul style="list-style-type: none">• Rechargeable, removable Lithium-Ion battery: 10050 mAh, 3.6 V• Up to 18 hours in intensive use |
| Charging | <ul style="list-style-type: none">• Charging over desktop charger (0 to 80 %) 4 hours• Charging over USB Type-C connector (0 to 80 %) 4 h (with charger supporting Qualcomm Quick Charge 3.0) |
| External power supply | <ul style="list-style-type: none">• AC adapter for desktop charger: input 100-240 VAC, 1A, 50-60 Hz / output 24 VDC, 1.25A, 30 W / Power cable for EU, UK or US• AC adapter for multiunit desktop charger: input 100-240 VAC, 1A, 50-60 Hz / output 24 VDC, 6.25A / 150W / Power cable for EU, UK or US |
| Backup battery | For real-time clock: keeps time for 200 days |
| Battery Hot Swap | Supported |

SIZE AND WEIGHT

| | |
|------------|---|
| Dimensions | (H) 214 x (W) 87/72 x (D) 135/29 mm (H) 8.4 x (W) 3.4/2.8 x (D) 5.3/1.1 inch |
| Weight | 642 gr / 22.65 oz |

ENVIRONMENT

| | | | |
|-----------------------|-----------------------------|----------------|----------------|
| Temperature | Operating | -20° to +55 °C | -4 to +131 °F |
| | Storage | -20° to +60 °C | -4 to +140 °F |
| | Charging | 0° to +45 °C | +32 to +113 °F |
| Relative humidity | 10 % to 95 % non-condensing | | |
| Environmental sealing | IP65 | | |

Zapraszamy do kontaktu!
Więcej informacji: www.kreski.pl



SUPPORT

- Maintenance service and extended maintenance contract
- Software customization and development support
- Technology, product and integration training
- Technology and project consultation
- Project management services

WARRANTY

- 2 year warranty
- Free technical support during and after 2 year warranty

SOFTWARE DEVELOPMENT ENVIRONMENT

- Android Studio, Visual Studio
- Source code available at: <https://github.com/NordicID>



NORDIC ID GROUP
Joensuunkatu 7 | FI-24100 Salo, FINLAND
tel. +358 2 727 7700 | fax +358 2 727 7720
sales@nordicid.com | www.nordicid.com

GERMANY
Nordic ID GmbH | Bielefeld, GERMANY
tel. +49 5206 70 84 70 | fax +49 5206 70 847 10
sales@nordicid.com | www.nordicid.de

V1.0

Nordic ID reserves the right to make changes to the information on this data sheet without prior notification. Availability of solution options may vary regionally. Please contact a Nordic ID representative for clarification on specifications and options. The N-Mark is a trademark or registered trademark of NFC Forum, Inc. in the United States and in other countries.