

### Before



Users need to adjust the distance when scanning barcodes, wasting a lot of time.

# After



With AR-3100 series scanners, barcodes can be read from contact which greatly increases efficiency.

# Application Retail Savings on your total purchase of \$10 or more before taxes. Available at any Bulk Barr. When the same the same to th

# Feature-rich to make daily work simple and easy



**Compact & simple to use** Lightweight form factor reduces working fatigue.

### **Long DoF Coverage**

Covers from contact to standard scan range, one scanner that does the job of two (contact reading & distant reading).



Reads barcodes on LCD screens
Supports all types of electronic LCD screen, such as mobile phone, tablet.



Reads high density 3mil barcodes

barcodes commonly used on small

Users can capture high density

retail items such as jewelry.

# Supports DataMagic function

Scanned data output can be customized to adopt various database structures.



### **Vibration function**

With vibration mode, users can instantly confirm a successful scan even in a noisy environment.



# **General Specifications**

| Models                                      |                | AR-3100  |                  | AR-3200                   |                  | AR-3201   |          |
|---|----------------|--|------------------|---------------------------|------------------|---|----------|
| Symbologies                                 | Linear         | Code11, Code39, Code93, Code32 (Pharmaceutical), Code128, Code bar, Interleaved 2 of 5, Industrial 2 of 5, IATA 2 of 5, Matrix 2 of 5, EAN/JAN-13, EAN/JAN-8, UPC-A, UPC-E, UPC-A/EAN-13 with EXtend Coupon code, Telepen, Plessey Code, GS1 Databar RSS14, GS1 Databar Limited, GS1 Databar, Omni directional, GS1 Databar Expanded, China Post |                  |                           |                  |   |          |
|   | Stacked Linear | GS1 Databar Expanded Stacked, GS1 Databar RSS14  |                  |                           |                  | Stacked, C16K, CodaBlockF   |          |
| Depth of Field<br>Ambient Light: 270~330Lux |                | Near (cm)  | Far (cm)         | Near (cm)                 | Far (cm)         | Near (cm)   | Far (cm) |
| Code39                                      | 3mil           | 0  | 7.5              | 1.6                       | 8.4              | 1.6   | 8.4      |
|   | 4mil           | 0  | 10.8             | 1.4                       | 12.4             | 1.4   | 12.4     |
|   | 5mil           | 0  | 14.6             | 1.0                       | 16.1             | 1.0   | 16.1     |
|   | 20mil          | 0  | 58               | 1.7                       | 78.0             | 1.7   | 78.0     |
| EAN13                                       | 13mil          | 0  | 43               | 1.3                       | 53.5             | 1.3   | 53.5     |
| Characteristics                             |                |  | A.               |                           |                  |   |          |
| Dimensions                                  |                | H140mm x W67mm x D169mm  |                  |                           |                  | Scanner: H140mm x W67mm x D169mm<br>Cradle: H106mm x W90mm x D141mm         |          |
| Weight                                      |                | 115g   |                  |                           |                  | Scanner: 178g (Battery included)<br>Cradle: 219g                            |          |
| Power                                       |                | 5V+-5%   |                  |                           |                  |   |          |
| Trigger switch                              |                | >1,000,000 cycles  |                  |                           |                  |   |          |
| Light source                                |                | RED LED 620nm~630nm  |                  |                           |                  |   |          |
| Interface                                   |                | USB (HID/Virtual Com), RS-232  |                  |                           |                  |   |          |
| Indication                                  |                | LED and adju   | ustable beep sou | nd, vibrator              |                  |   |          |
| Battery                                     |                | _  |                  |                           |                  | Rechargeable Li-Ion battery pack (3.6V, 2600mAh, 9.36Wh)                    |          |
| Battery charge time                         |                | -  |                  |                           |                  | Full charged 5 hours (For adapter) Full charged 7 hours (For USB cable only |          |
| Standby idle                                |                | -  |                  |                           |                  | >102 hours  |          |
| Number of scan                              |                | _  |                  |                           |                  | >96,000 reads   |          |
| Expected hours of operation                 |                | <u> </u>   |                  |                           |                  | >81 hours   |          |
| Supported connection                        |                |  |                  |                           |                  | BT 2.1+EDR, 100meter<br>Support SPP/HID                                     |          |
| Performance                                 |                |  |                  |                           |                  | Supportor   |          |
| Resolution                                  |                | 3mil PCS>=3  | 30%              |                           |                  |   |          |
| Scan Rate                                   |                | 500 scan/sec   |                  |                           |                  |   |          |
| Scan Width                                  |                | 25.7cm (code 39 , 20mil,pcs 90%)   |                  |                           |                  |   |          |
| Scan Angle                                  |                | Yaw: ±60° Pitch: ±70° Roll: ±45° , EAN13, 13mil  |                  |                           |                  |   |          |
| Environment                                 |                | 1411. 200 11   | tem 170 Rom 1    | 15 / 15 11 11 15 15 11 11 |                  |   |          |
| Light strength                              |                | 80.000 Lux (   | PCS 90% / Code   | 39. 20mil "1234") (       | Continue reading |   |          |
| Temperature                                 | Operating      | 80,000 Lux (PCS 90% / Code 39, 20mil "1234") Continue reading<br>-20°C to 60°C (-4°F to 140°F)   |                  |                           |                  |   |          |
|   | Storage        | -30°C to 70°C (-22°F to 158°F)   |                  |                           |                  | -20°C to 60°C (-4°F to 140°F)   |          |
|   | Battery Charge | =  |                  |                           |                  | 0°C to 40°C (32°F to 104°F)   |          |
| Humidity                                    |                | 5% to 95% relative humidity, non-condensing  |                  |                           |                  |   |          |
| ESD   |                | ±12KV Contact discharge, ±20KV Air discharge, ±12KV Vcp Hcp discharge  |                  |                           |                  |   |          |
| Drop  |                | 1.8M   |                  |                           |                  |   |          |
| Regulatory                                  |                |  |                  |                           |                  |   |          |
| Regulatory Approvals                        |                | CE, FCC, BSMI, RoHS, WEEE, BIS   |                  |                           |                  |   |          |
| Environmental                               |                | ROHS compliant   |                  |                           |                  |   |          |

<sup>\*</sup>Argox reserves the right to enhance and modify the specification without prior notice. Please check Argox sales representative for most updated specifications.

## Optional Items



Stand: Auto-sensing (presentation) applications



Zapraszamy do kontaktu! Więcej informacji: www.kreski.pl

### Argox Information Co., Ltd.

7F., No.126, Ln.235, Baoqiao Rd., Xindian Dist., New Taipei City 231, Taiwan (R.O.C.)
Tel: +886-2-8912-1121 Fax: +886-2-8912-1124 https://www.argox.com https://www.youtube.com/user/argoxmkt email:service@argox.com
Copyright © 2020. Argox Information Co., Ltd. All Rights Reserved.





