











**UHF RFID** reader



**Gun Grip** 





# <u>Kr</u>eski

Zapraszamy do kontaktu! Więcej informacji: www.kreski.pl



Charging cradle for gun grip

The unitech EA500P (Plus) Android 8.1 comes with the Google GMS license. It is a rugged 5"mobile enterprise computer within a compact stylish design. The EA500P (Plus) combines strong features with powerful data collection. It provides convenient connectivity (with fast roaming), reading capabilities and enhances the service level for a variety of vertical applications within the retail, hospitality, healthcare and field service sectors.

computer with the **SLEEK DESIGN** of the EA500P(Plus)

**RETHINK** your idea of a rugged enterprise mobile







#### Dual-Sim

The Unitech EA500P (Plus) supports Dual-Sim. A great way to manages business and personal numbers within the same device or you can add a local data plan while traveling outside of your home country or region.



### Allrouder

Thanks to POGO pins and USB-C connerctor on the bottom side, the EA500P (Plus) has limitless scalability options for future accessories such as gun grip and docking stations.



### Compact design enterprise format

EA500P (Plus) is one of the most flexible and sleek enterprise mobile computer with a weight of only 210q.



### Choose your engine

The EA500P (Plus) gives your workforce the technology it needs to take your business to the next level. The EA500P (Plus) is available with a Basic 2D imager or Premium 2D imager.

## Operation System

CPU 1.4GHz, Qualcomm 8940 octa core 64 bits processor

RAM 2GB/4GB optional Memory ROM 16GB/64GB optional

Android 8.1 with GMS

Google Enterprise Device certified

**Dual Sim** SIM

Languages Multi-language

Input Chinese/ English, supports handwriting Others

and soft keyboard.

### Display

OS

5.0 inch TFT-LCD HD (720 x 1280) color screen, 300nits, Gorilla Glass 3. Ultra sensitive capacitive touch screen, compatible with gloves and supports wet resistance.

## Camera/Photos/Video

2MP front camera

13MP rear camera with LED flash and auto-focus function

## Indicator

LED's and vibration

### Communication

USB USB Type C OTG

Yes, over USB Type C

**POGO PIN** Charging via cradle and USB client IEEE 802.11a/b/g/n/ac/d/e/f/h/i/k/v/w/r WLAN

IPV4, IPv6.

**FAST ROAMING** PMKID caching, 802.11r, OKC Bluetooth® Bluetooth® 4.2 + BR/EDR + BLE

WWAN Global brands with dual SIM Slot

> 4G FDD-LTE (B1/B2/B3/B4/B5/B7/B8/B20/ B28A/B28B)

3G: WCDMA(B1/B2/B5/B8)

(2100, 1900,850, 900 MHz)

GSM/EDGE/GPRS 2G :

(850, 900, 1800, 1900 MHz) GPS, AGPS, BeiDou, GLONASS

Acceleration, motion, proximity sensor, light sensor, Sensors

> G-sensor, digital compass (E-compass), pressure sensor, gyroscope and height meter

5Hz to 2KHz,60 minute duration per axis, 3 axis Vibration

# WiFi Security

**WLAN Security:** 

802.1x(EAP): EAP-TLS, EAP-TTLS, PEAP-MSCHAPv2,

PEAP-TLS, PEAP-GTC, PWD, SIM, AKA

Encryption: WEP, WPA/WPA2-PSK

### Buttons

**GPS** 

5 keys- Programmable function button; dual dedicated scan buttons; volume up/down buttons; on/off button

# EA500P(PLUS)

v1.2 Specifications

# **Software Support**













SOTI TeamViewer armets Zello

Data capture

**2D IMAGER** 

BASIC 2D: Zebra SE2100

Suppor t all major 1D and 2D barcodes

PREMIUM 2D: Honeywell N6603 engine.

White illumination

High Visibility Laser Aimer Fast scan speed

Ultra-fast motion tolerance up to 5 meters p/s

Supports color barcodes

Supports poorly printed barcodes Supports 1D, 2D and OCR

Symbology/X-Dim Typical Range\*

100% U.P.C 46 mm - 419 mm 5 mil Code 39 64 mm - 163 mm 10 mil Code 39 28 mm - 338 mm 6.7 mm PDF417 46 mm - 185 mm 10 mil Data Matrix 53 mm - 203 mm

Resolution linear barcodes: 0.127 mm Resolution 2D matrix codes: 0.169 mm

HF/NFC Frequency 13.56Mhz

Support: ISO14443A/B, ISO15693 standard,

Supports NFC

**Power Source** 

Main battery Rechargeable and Changeable (Non-swappable)

3.8V 4000mAh (typical)

3.8V 3800mAh (minimum)

Operation time 10-12 hours

(depending on the specific environment)

Real time clock battery RTC battery

# Audio

Microphone, speaker and 3.5mm audio jack. Support noise cancellation, PPT headset support, cellular circuit switch voice.

### Enclosure

Dimension 155.8 mm x 76.2 mm x 13.5 mm

Weight 210g with battery

### Environmental

Operating temperature -10°C to +50°C Storage temperature -20°C to +70°C Charging Temperature 0°C to 40°C

Relative Humidity 5% ~ 95% (non-condensing) **Drop Specification** 1.5m drop to concrete at room temperature per MIL-STD810G

**IP65** Sealing

Tumble 1.0m tumble for 200 cycles and 400 times

**ESD** 8K / 15KV

# Device supported MDM

SOTI, AirWatch, 42Gears and MoboLink

Regulatory Approvals

# CE, RED, NCC, BSMI, CCC, VCCI, FCC

### Accessories USB type C cable / adaptor

Power adaptor Sylus

Glass Screen protector Vehicle cradle

Screw mount for vehicle cradle Suction mount for vehicle cradle 1-slot charging cradle 6-slot charging cradle Gun gripHandstrap Charging cradle for gun grip RP100 UHF/RFID Reader

Kreski

Zapraszamy do kontaktu!

Więcej informacji: www.kreski.pl





