


Havis Docking Station for Dell Latitude Rugged Extreme

DS-DELL-400 Series

The Havis Docking Station for the Dell Latitude 14 Rugged and Latitude 12 & 14 Rugged Extreme Notebooks brings you the best computing solution for all your business needs. The DS-DELL-400 Series Docking Station offers computer charging, security, and connection to peripherals in medical, enterprise, and in-vehicle workplaces. Maximize your productivity with this rugged yet lightweight dock, which has been built with theft deterrence, longevity and stability in mind.



- Constant connectivity is maintained with a guided, floating docking connector.
- Docking station was engineered with fully functional front- and rear-facing connectors.
- Mounting bracket and integrated cable strain relief allows for ease of installation and faster rollouts.
- Theft deterrence is accomplished through Havis' rugged locking system and front hooks, which keep your Latitude Rugged Extreme Notebook safe and secure.
- Strain relief for connectors prevents loose connections and accidental disconnects.
- Scalable connectivity provides a flexible solution.
- Havis offers a full line of accessories to complete any solution.











Havis Docking Station for Dell Latitude Rugged Extreme



Front- and rear-facing port replication protects cable connections while integrated strain relief protects from accidental disconnects



Full Port Replication

- Best-in-class circuit and power system supports fully powered USB 3.0
- USB: Fully-Powered USB 3.0 (3)
- USB: Fully-Powered USB 2.0, front accessible (1)
- Ethernet: RJ45 (1)
- Serial DB9 (2)
- · Video: VGA (1)
- · Video: HDMI (1)
- Speaker & Mic: Stereo (1 each, front-facing)
- Power Input: 19.5 V DC (Part # DS-DELL-401/401-3/402/402-3/405/405-3/406/406-3)
- Power Input: 10-17 V DC (Part# DS-DELL-404/404-3/407/407-3)
- Antenna Connection: Triple Hi-Gain (Optional)

Specifications

Height: 10.8" (27.6 cm)
Width: 12.4" (31.5 cm)
Depth: 2.7" (6.9 cm)
Weight: 5.25 lbs (2.38 kg)

Certifications & Testing

- Vibration Testing: MIL-STD 810G 514.5
- Impact Test: Crash Simulation per SAE J1455 (Forward/Rearward/Side Impact Directions)
- Cycle Test: Latch tested to 30,000 cycles
- Environmental Testing: Hot/Cold Operation and Storage
- CE, FCC
- RoHS

Part Number	USB 2.0	USB 3.0	Ethernet	Serial	VGA	HDMI	Speaker /Mic		Internal Power Supply	Dock Input Power	Antenna Connection (Triple Hi-Gain)
DS-DELL-401	1	3	1	2	1	1	Yes	No	No	19.5 V DC*	None DS-DELL-401-3
DS-DELL-402	1	3	1	2	1	1	Yes	Yes	No	19.5 V DC	None DS-DELL-402-3
DS-DELL-403**	0	0	0	0	0	0	0	No	No	n/a	None
DS-DELL-404	1	3	1	2	1	1	Yes	No	Yes	10-17 V DC	None DS-DELL-404-3
DS-DELL-405	1	3	1	0	0	0	Yes	No	No	19.5 V DC*	None DS-DELL-405-3
DS-DELL-406	1	3	1	0	0	0	Yes	Yes	No	19.5 V DC	None DS-DELL-406-3
DS-DELL-407	1	3	1	0	0	0	Yes	No	Yes	10-17 V DC	None DS-DELL-407-3

^{*} Requires an external Dell authorized DC power supply

© 2017 Havis, Inc.



^{**} Cradle only option (no electronics)