



0702L 7-inch LCD

Touchscreen Monitor



Edge-to-edge design with integrated 10-touch



3-Year Warranty



Commercial-grade

Product Overview

The Elo 0702L 7-inch touchscreen monitor delivers a professional-grade interactive solution with Elo's industry-leading TouchPro® PCAP technology featuring edge-to-edge glass and enabling up to 10 simultaneous touches. Backed by a three-year warranty, the feature rich touchscreen monitor is equipped with DisplayLink technology - enabling connectivity for power, video and touch over a single cable. With a compact form factor measuring just over half an inch thin and a clean design made for simple integration, the 0702L is ideal for customer facing point of interaction installations in point-of-sale, brand loyalty, point of information, signage and hospitality applications. With a minimal footprint, the 0702L is also well-suited for industrial kitchen equipment controllers.

DisplayLink technology provides touch, video and power connectivity over a single cable

Touchscreen is compatible with use of finger, glove and stylus

Integrate with ease - From stands and pole mounts to shelf mounts, wall mounts and 3rd party VESA mounts

0702L 7-inch LCD Touchscreen Monitor

Black					
7" / 177.8 mm					
6.07" x 3.38" / 154.08 mm x 85.92 mm					
Active matrix TFT LCD					
TouchPro PCAP					
10 Touches					
5:3					
800 x 480					
800 x 480 60 Hz					
16.2M					
Panel: 500 nits; with TouchPro PCAP: 430 nits					
25 msec					
Horizontal: 75° or 150° total; Vertical: 55°/65° or 120° total					
500:1					
1 x Micro USB (DisplayLink input for touch, video and power)					
Input Video Horizontal Sync frequency range: 31.5KHz / Input Video Vertical Sync (frame rate) frequency range: 60Hz					
Input connector: Micro USB Input signal specifications: 5 V ±5% Power Consumption (Typical) - ON: 3.7 W; SLEEP: 0.9 W; OFF: 1.9 W					
4.61" x 7.11" x 0.7" / 117.22 mm x 180.58 mm x 17.7 mm					
6.69" x 9.13" x 3.74" / 170 mm x 232 mm x 95 mm					
Unpackaged - 0.77 lbs / 0.35 kg; Packaged - 1.43 lbs / 0.65 kg					
VESA 75mm x 75mm					
Operating: 0°C to 40°C / 32°F to 104°F; Storage: -20°C to 60°C / -4°F to 140°					
Operating: 20% - 80% / Storage: 10% - 95%					
Canada CUL, IC; China CCC; Europe CE; United States FCC, UL; Japan VCCI; Internationa CB; Australia RCM; Mexico NOM, Korea KCC, Tawian BSMI					
IP65					
IK06					
3 years					
4 year warranty coverage - Elo P/N: E898247					
5 year warranty coverage - Elo P/N: E898449					
3 year warranty coverage + AUR - Elo P/N: E898648 4 year warranty coverage + AUR - Elo P/N: E894921					
4 year warranty coverage + AUR - Elo P/N: E894921 5 year warranty coverage + AUR - Elo P/N: E895125					
5 year warranty coverage + AUR - Elo F/N: E875125 Touchmonitor, Micro USB Y-cable, Quick Install Guide					

Ordering Information

Part Number	Part Description	Technology	Surface Treatment	Touch Interface	Color	Mount
E796382	ET0702L-2UWA-1-BL-G	TouchPro PCAP	Anti-glare	USB	Black	No Stand



Zapraszamy do kontaktu! Więcej informacji: www.kreski.pl

Learn more about Elo at **EloTouch.com**.

Americas

Tel +1 408 597 8000 elosales.na@elotouch.com

Europe (EMEA) Tel +32 (0)16 70 45 00

EMEA.Sales@elotouch.com

Asia Pacific Tel +86 (21) 3329 1385 www.elotouch.com.cn

Elo reserves the right to change or update, without notice, any information contained herein; to change, without notice, the design, construction, materials, processing or specifications of any products; and to discontinue or limit production or distribution of any products. Elo, the Elo logo and TouchPro are either trademarks or registered trademarks of Elo Touch Solutions, Inc. All other trademarks are the property of their respective owners. © 2020 Elo Touch Solutions, Inc. All rights reserved. 20031AES00123

