

1715L 17-inch LCD

Touchscreen Monitor



Integrated Touch



Commercial Grade



3-Year Warranty

Product Overview

The Elo 1715L 17-inch standard format touchscreen monitor is designed, developed and built to provide a space-saving and cost-effective touch solution.

The 1715L can function as a desktop or wall-mounted unit and includes a VESA mounting option. The touchscreen is factory-sealed against dirt, dust, and liquids and with controls on the side rather than the front, the touchscreen can be locked-out for public use. The optional 3-track magnetic stripe reader (MSR), programmable to either HID or Keyboard Emulation (USB only), is easily installed by the user, providing an elegant, integrated solution and eliminating the need for external brackets or attachments.

Available with AccuTouch® five-wire resistive and IntelliTouch® surface acoustic wave (SAW) with an anti-glare display and Dual/Serial USB

Touchscreen sealed from dirt, dust and liquid

Removable base and VESA mounting option

Customize with integrated 3-track magnetic stripe reader (MSR)

1715L 17-inch LCD Desktop Touchmonitor

| Specifications | |
|---------------------------------------|---|
| Model | 1715L |
| Color | Dark gray |
| Active Display Area | 13.3" x 10.6" (338mm x 270mm) |
| Monitor Dimensions | 15.4" x 14.4" x 8.0" (391mm x 366mm x 203mm) |
| LCD Technology | Active Matrix TFT LCD with LED backlighting |
| Diagonal Size | 17" |
| Native Resolution | 1280 x 1024 |
| Other Supported Resolutions | 1280 x 1024 @ 60 or 75 Hz; 1280 x 960 @ 60 Hz; 1152 x 864 @ 75 Hz; 1024 x 768 @ 60, 65 Hz, 70 or 75 Hz; 832 x 624 @ 75 Hz; 800 x 600 @ 56, 60, 72 or 75 Hz; 720 x 400 @ 70 Hz; 720 x 350 @ 70 Hz; 640 x 480 @ 60, 66 Hz, 72 or 75 Hz |
| Number of Colors | 16.7 million |
| Number of Touches | Single-touch |
| Brightness (typical) | LCD panel: 250 nits; IntelliTouch: 225 nits; AccuTouch: 200 nits |
| Response Time - Total (typical) | 5 msec |
| Viewing Angle (from center) | Horizontal: $\pm 85^\circ$ or 170° total; Vertical: $\pm 80^\circ$ or 160° total |
| Contrast Ratio (typical) | 1000:1 |
| Video | Input Connector: 15-pin female D-sub Sync Format: Separate H&V syncs, Composite sync, and Sync-On-Green Displayable horizontal scan frequency range: 31.5 - 80 KHz Displayable vertical scan (frame rate) frequency range: 56.3 - 75 Hz |
| Power | AC Input - Input Connector: IEC 60320 C6; Input voltage range: 100-240VAC 50/60Hz DC Input - Input Connector: Coaxial power jack (Barrel inner diameter: 6.4 +/- 0.3mm. Pin outer diameter: 2.0 +/- 0.1mm. Barrel depth: 8.8 +/- 0.3mm); Input Voltage range: 12V +/- 5% |
| Power Consumption (Typical): | Monitor only: ON: 10.52 W; SLEEP: 1.34 W; OFF: 0.46 W |
| Shipping Dimensions | 17.99" x 11.42" x 17.32" (457mm x 290mm x 440mm) |
| Temperature | Operating: 32°F to 104°F (0°C to 40°C); Storage: -4°F to 122°F (-20°C to 60°C) |
| Humidity | Operating 20%-80%; Storage 10%-90% noncondensing |
| Weight (approx.) | Actual: 15.2lb (6.9kg); Shipping: 21.2lb (9.6kg) |
| Regulatory Approvals and Declarations | North America/ Worldwide: UL, cUL, S, MPR II, FCC, CE, VCCI, IC, C-TICK. Asia Models: UL, cUL, S, MPR II, FCC, CE, VCCI, IC, C-TICK, KC, CCC, BSMI, China RoHS |
| User's Controls | Digital OSD. OSD buttons: menu, up, down, select, power; OSD: contrast, brightness, H/V position, RGB (color temp), clock, phase, recall, Language (English, German, Spanish, Japanese, French); OSD disable/enable: power, OSD menu |
| Mounting Options | Removable base, 100 mm VESA mount; threaded-through mounting holes under base |
| Warranty | 3 years |
| Extended Warranty | 4 year warranty coverage - Elo P/N: E898247 5 year warranty coverage - Elo P/N: E898449 3 year warranty coverage + AUR - Elo P/N: E898648 4 year warranty coverage + AUR - Elo P/N: E894921 5 year warranty coverage + AUR - Elo P/N: E895125 |
| MTBF | 50,000 hours demonstrated |
| What's in the Box | QIG, User Manual CD, VGA cable, serial cable (attached if support combo), power cord, USB cable |

Ordering Information

| Model | Part Number | Technology | Interface | Surface Treatment | Color | Availability |
|-------|-------------|--------------|------------|-------------------|-----------|----------------|
| 1715L | E603162 | AccuTouch | Serial/USB | Antiglare | Dark Gray | Americas, EMEA |
| | E719160 | IntelliTouch | Serial/USB | Antiglare | Dark Gray | Americas, EMEA |



Zapraszamy do kontaktu!
Więcej informacji: www.kreski.pl

Learn more about Elo at EloTouch.com.

Americas

Tel +1 408 597 8000
elosales.na@elotouch.com

Europe (EMEA)

Tel +32 (0)16 70 45 00
EMEA.Sales@elotouch.com

Asia Pacific

Tel +86 (21) 3329 1385
www.elotouch.com.cn

Elo reserves the right to change or update, without notice, any information contained herein; to change, without notice, the design, construction, materials, processing or specifications of any products; and to discontinue or limit production or distribution of any products. Elo, the Elo logo, AccuTouch and IntelliTouch are either trademarks or registered trademarks of Elo Touch Solutions, Inc. All other trademarks are the property of their respective owners.
© 2020 Elo Touch Solutions, Inc. All rights reserved. 20111AES00068

