



# 3300 High-Performance Wax/Resin

Ribbon	Ribbon Type		Compatible Material	Print Speed				Temperature Resistance			Smear/Scratch Resistance			Chemical Resistance					
2300	Wax	Standard	Uncoated/Coated Paper																
2100	Wax	High-Performance	Uncoated/Coated Paper																
3400	Wax/Resin	High-Performance	Uncoated/Coated Paper Matte Synthetics																
3300	Wax/Resin	High-Performance	Uncoated/Coated Paper Matte/Gloss Synthetics																
3200	Wax/Resin	Premium	Uncoated/Coated Paper Matte Synthetics																
4800	Resin	Performance	Matte/Gloss Synthetics																
5095	Resin	High-Performance	Matte/Gloss Synthetics																
5100	Resin	Premium	Matte/Gloss Synthetics																
Image Lock™	Resin	Specialist	Z-Xtreme™ 5000T																

#### **Additional Features**

- A versatile multi-use ribbon. Can be used on both paper and standard synthetics, reducing the need to stock multiple ribbons.
- With medium scratch resistance on Zebra paper, matte and gloss synthetic labels
- Provides a higher level of mechanical resistance compared to wax ribbons
- Resistant to many everyday chemicals and when used with speciality synthetics and can withstand mild to medium chemical exposure

# **Suggested Applications**

- Signage and logos, printing symbols
- Identifying and tracing substances and preparations
- Customised labels for the retail sector
- Outdoor product tag and labelling for wire, cable and fabricated parts
- Indoor and outdoor product and shelf-edge labelling
- Labels subject to moderate abrasion or friction
- Pharmacy and pharmaceutical labelling







# **Technical Specifications**

	Description
Colour	Black
Base Film	Polyester
Base Film Caliper	4.5 microns
Total Caliper	9 microns
Scanning Capabilities	IR and Visible Light

# **Ribbon Compliance**

	,
REACH/ Substances of Very High Concern (SVHC)	✓
RoHS	✓
Dodd-Frank Act (Conflict Minerals)	✓
Carcinogenic, Mutagenic and Reprotoxic, or Substances Toxic Substances 1976/769/ EC	✓
California Proposition 65	✓
FDA 21 CFR Part 175.300 – Indirect Food Contact – Resinous and Polymeric Coatings	✓
European Food Directive 1935/2004/EC	✓
Halogen free	✓
Latex free	✓
Animal derivatives free	✓
BP Free	✓

Stocked Sizes Available for the following Zebra Printers:

4' wide Desktop models

**Recommended Storage Conditions:** 

1 year duration when stored at 5°C to 35°C at 20% to 80% RH



Zapraszamy do kontaktu! Więcej informacji: www.kreski.pl





### **Product Performance and Suitability**

The information contained in this document is to be used for guidance only and is not intended for use in setting specifications. All purchasers of Zebra products shall be solely responsible for independently determining if the product conforms to all requirements of their unique application.

All products should be pre-tested to ensure they meet all intended requirements of specific end-use applications.

For testing of this ribbon on Zebra Desktop printers please contact your Supplies Specialist representative.

Please note this is a desktop ribbon only.



Zapraszamy do kontaktu! Więcej informacji: www.kreski.pl