

## Z-Perform™ 1000T High-Tack

<b>Media Type</b>	Label	✓	<b>Adhesive Type</b>	Permanent	✓
	Receipt			Removable	
	Tag			No Adhesive	
	Wristband		<b>Environment</b>	Indoor	✓
<b>Material Type</b>	Paper	✓		Outdoor	
	Synthetic		<b>Properties</b>	Cold Temperature	✓
<b>Printing Technology</b>	Direct Thermal (no Ribbon Required)			Deep Freeze	✓
	Thermal Transfer (Ribbon Required)	✓		High Temperature	
<b>Finish</b>	Matte	✓		Ultra High Temperature	
	Gloss			High Tack	✓
				Chemical Resistance	-

### Additional Features

- Excellent adhesion on a wide variety of surfaces
- Adhesive carries excellent low temperature resistance
- Produces acceptable barcodes and images when printed with Zebra 2300 and 2100 wax ribbons and recommended Zebra printers
- Adhesive complies with European food regulation EC 1935/2004, EU 10/2011 and BfR Recommendation XXI for direct contact with dry, moist and non-fatty foodstuffs
- Adhesive complies with FDA 175.105 for direct contact for dry foodstuffs
- BPA free
- Latex free adhesive

### Suggested Applications

- High volume box labelling
- Logistics labelling e.g. boxes and pallets
- Product identification
- Work-in-progress labels
- Shipping, picking and receiving labels in warehousing applications
- Labelling of most packaging materials and plastic substrates
- Print and apply applications



Zapraszamy do kontaktu!  
Więcej informacji: [www.kreski.pl](http://www.kreski.pl)

## Technical Specifications

	Description	Caliper
Facestock	Matte white uncoated paper	66 microns
Adhesive	Permanent rubber adhesive	13 microns
Liner	60gsm glassine liner	51 microns
Total		130 microns $\pm 10\%$

**Recommended Zebra Printers:** Desktop, mid-range and high-performance thermal printers

**Recommended Zebra Ribbons:** 2300, 2100

**Minimum Application Temperature:** 0°C  
When the label is applied, the environment and surface should be above this temperature

**Service Temperature Range:** -40°C to 70°C  
Following correct application and appropriate dwell time (usually 24hrs) the media will withstand this temperature range

**Recommended Storage Conditions:** 1 year duration when stored at 20°C to 25°C at 40% to 50% RH  
Storage of product before use

**Expected Life Span in Application:** Indoor use, for 1 year+  
Following correct application and appropriate dwell time (usually 24hrs) we expect, but do not warrant, a life span as indicated

## Product Performance and Suitability

The information contained in this document is to be used for guidance only and is not intended for use in setting specifications. All purchasers of Zebra products shall be solely responsible for independently determining if the product conforms to all requirements of their unique application.

For testing of this material please order sample roll SAMPLE65354.

