

## Z-Perform™ 1000T Removable

<b>Media Type</b>	Label	✓	<b>Adhesive Type</b>	Permanent	
	Receipt			Removable	✓
	Tag			No Adhesive	
	Wristband		<b>Environment</b>	Indoor	✓
<b>Material Type</b>	Paper	✓		Outdoor	
	Synthetic		<b>Properties</b>	Cold Temperature	✓
<b>Printing Technology</b>	Direct Thermal (no Ribbon Required)			Deep Freeze	
	Thermal Transfer (Ribbon Required)	✓		High Temperature	
<b>Finish</b>	Matte	✓		Ultra High Temperature	
	Gloss			High Tack	
				Chemical Resistance	-

### Additional Features

- Good tack and adhesion to a wide range of surfaces
- Good long term removability
- Produces acceptable barcodes and images when printed with Zebra 2300 and 2100 wax ribbons and recommended Zebra printers
- Adhesive carries good cold temperature resistance
- Adhesive complies with European food regulation EC 1935/2004, EU 10/2011 and BfR Recommendation XXI for direct contact with dry, moist and such kind of fatty foodstuffs which have a reduction factor of at least 3
- Adhesive complies with FDA 175.105 for direct contact with dry foodstuffs
- BPA free
- Latex free adhesive

### Suggested Applications

- Labelling of packaging materials e.g. boxes, pallets in logistics applications
- Product identification
- Removable labels for boxes, pallets or tote bins
- Removable work-in-progress labels



Zapraszamy do kontaktu!  
Więcej informacji: [www.kreski.pl](http://www.kreski.pl)

## Technical Specifications

	Description	Caliper
Facestock	Matte white uncoated paper	66 microns
Adhesive	Removable acrylic adhesive	12 microns
Liner	57gsm glassine liner	51 microns
Total		129 microns $\pm 10\%$

**Recommended Zebra Printers:** Desktop, mid-range and high-performance thermal printers

**Recommended Zebra Ribbons:** 2300, 2100

**Minimum Application Temperature:** -15°C  
When the label is applied, the environment and surface should be above this temperature

**Service Temperature Range:** -30°C to 80°C  
Following correct application and appropriate dwell time (usually 24hrs) the media will withstand this temperature range

**Recommended Storage Conditions:** 1 year duration when stored at 20°C to 25°C at 40% to 50% RH  
Storage of product before use

**Expected Life Span in Application:** Indoor use, for up to 1 year  
Following correct application and appropriate dwell time (usually 24hrs) we expect, but do not warrant, a life span as indicated

## Product Performance and Suitability

The information contained in this document is to be used for guidance only and is not intended for use in setting specifications. All purchasers of Zebra products shall be solely responsible for independently determining if the product conforms to all requirements of their unique application.

For testing of this material please order sample roll SAMPLE5207.



Zapraszamy do kontaktu!  
Więcej informacji: [www.kreski.pl](http://www.kreski.pl)