

Z-Select™ 2000T



Available
from stock
on ZipShip

| | | | | | |
|---------------------|--|---|---------------|------------------------|---|
| Media Type | Label | ✓ | Adhesive Type | Permanent | ✓ |
| | Receipt | | | Removable | |
| | Tag | | | No Adhesive | |
| | Wristband | | Environment | Indoor | ✓ |
| Material Type | Paper | ✓ | | Outdoor | |
| | Synthetic | | Properties | Cold Temperature | ✓ |
| Printing Technology | Direct Thermal (no Ribbon Required) | | | Deep Freeze | |
| | Thermal Transfer (Ribbon Required) | ✓ | | High Temperature | |
| Finish | Matte | ✓ | | Ultra High Temperature | |
| | Gloss | | | High Tack | |
| | | | | Chemical Resistance | - |

Z-Select materials feature a protective topcoat, which provides the following benefits over an equivalent uncoated material (e.g. Z-Perform)

- Excellent print quality and definition
- Faster print speeds
- Improved printhead life
- Resistance to moisture, oils and other environmental factors

Additional Features

- Excellent print quality when printed with Zebra 2300, 2100, 3400 and 3200 ribbons and a recommended Zebra printer
- Adhesive complies with European food regulation EC 1935/2004, EU 10/2011 and BfR Recommendation XIV for direct contact with dry and moist, non-fatty foodstuffs
- Adhesive complies with FDA 175.105 for direct contact with dry foodstuffs, or alternatively separated by a functional barrier
- BPA free
- Latex free adhesive

Suggested Applications

- Shelf edge labelling, product and price labelling in retail applications
- Work in progress labelling
- Product identification
- Sterile services labelling in healthcare applications
- Shipping, picking and receiving labels in warehousing applications
- Labelling of packaging materials e.g. boxes and pallets in logistic applications

Technical Specifications

| | Description | Caliper |
|-----------|-----------------------------|------------------------|
| Facestock | Matte white topcoated paper | 74 microns |
| Adhesive | Permanent acrylic adhesive | 14 microns |
| Liner | 57gsm glassine liner | 51 microns |
| Total | | 139 microns $\pm 10\%$ |

Recommended Zebra Printers:

P4T™, desktop, mid-range and high-performance thermal printers

Recommended Zebra Ribbons:

2300, 2100, 3400, 3200, 5555

Minimum Application Temperature:

When the label is applied, the environment and surface should be above this temperature

0°C

Service Temperature Range:

Following correct application and appropriate dwell time (usually 24hrs) the media will withstand this temperature range

-20°C to 80°C

Recommended Storage Conditions:

Storage of product before use

1 year duration when stored at 20°C to 25°C at 40 to 50% RH

Expected Life Span in Application:

Following correct application and appropriate dwell time (usually 24hrs) we expect, but do not warrant, a life span as indicated

Indoor use, for 1 year+

Product Performance and Suitability

The information contained in this document is to be used for guidance only and is not intended for use in setting specifications. All purchasers of Zebra products shall be solely responsible for independently determining if the product conforms to all requirements of their unique application.

For testing of this material, order from the ZipShip price list or order sample roll SAMPLE5257.



Zapraszamy do kontaktu!
Więcej informacji: www.kreski.pl