

## 8000T Semi-Gloss Piggyback

Media Type	Label	✓	Adhesive Type	Permanent	✓
	Receipt			Removable	
	Tag			No Adhesive	
	Wristband		Environment	Indoor	✓
Material Type	Paper	✓		Outdoor	
	Synthetic		Properties	Cold Temperature	✓
Printing Technology	Direct Thermal (no Ribbon Required)			Deep Freeze	
	Thermal Transfer (Ribbon Required)	✓		High Temperature	
Finish	Matte			Ultra High Temperature	
	Gloss	✓		High Tack	
				Chemical Resistance	-

### Additional Features

- A multi-layer construction with two layers of adhesive and liner. Labels can be applied to a surface, then at a later date, removed from the 'piggyback' liner and re-applied to a second surface
- Produces good quality small detailed barcodes with Zebra 2300 and 2100 ribbons
- Good adhesion to a wide variety of surfaces including irregular surfaces
- Adhesive complies with European food regulations EC 1935/2004, EU 10/2011 and BfR Recommendation XIV for direct contact with dry, moist and non-fatty foodstuffs
- Adhesive complies with FDA 175.105 for direct contact with dry foodstuffs, or alternatively separated by a functional barrier
- BPA free
- Latex free adhesive

### Suggested Applications

- Labelling of packaging materials including corrugated, plastic, glass and metal
- Work in progress labelling
- Order picking labelling
- Return mailing labels
- Shipping labels with a removable section for signature



Zapraszamy do kontaktu!  
Więcej informacji: [www.kreski.pl](http://www.kreski.pl)

## Technical Specifications

	Description	Caliper
Facestock	Semi-gloss white paper	69 microns
Adhesive	Permanent acrylic adhesive	16 microns
Liner	61gsm glassine liner	54 microns
Adhesive	Permanent acrylic adhesive	16 microns
Liner	57gsm glassine liner	51 microns
Total		206 microns $\pm 10\%$

**Recommended Zebra Printers:** Mid-range and high-performance printers

**Recommended Zebra Ribbons:** 2300, 2100, 3400, 3200

**Minimum Application Temperature:** 0°C  
When the label is applied, the environment and surface should be above this temperature

**Service Temperature Range:** -20°C to 80°C  
Following correct application and appropriate dwell time (usually 24hrs) the media will withstand this temperature range

**Recommended Storage Conditions:** 1 year duration when stored at 20°C to 25°C at 40% to 50% RH  
Storage of product before use

**Expected Life Span in Application:** Indoor use, for 1 year+  
Following correct application and appropriate dwell time (usually 24hrs) we expect, but do not warrant, a life span as indicated

## Product Performance and Suitability

The information contained in this document is to be used for guidance only and is not intended for use in setting specifications. All purchasers of Zebra products shall be solely responsible for independently determining if the product conforms to all requirements of their unique application.

For testing of this material, please order sample roll SAMPLE65137.



Zapraszamy do kontaktu!  
Więcej informacji: [www.kreski.pl](http://www.kreski.pl)