

Z-Slip

Media Type	Label	✓	Film Type	Polyethylene	
	Receipt			Polyolefin	
	Tag			Polypropylene	✓
	Wristband			Polyester	
Material Type	Paper	✓	Properties	Polyimide	
	Synthetic	✓		Cold Temperature	✓
Printing Technology	Direct Thermal (no Ribbon Required)	✓		Deep Freeze	
	Thermal Transfer (Ribbon Required)			High Temperature	
Adhesive Type	Permanent	✓		Ultra High Temperature	
	Removable			High Tack	
	No Adhesive			Chemical Resistance	Extreme
Finish	Matte	✓	Environment	Indoor	✓
	Gloss			Outdoor	

Additional Features

- Direct thermal, paper and polypropylene label combination
- Excellent print quality
- Unique construction protects printable side from chemical and keeps information secure.

Suggested Applications

- Packing slip applications
- Invoice documents
- Personalised messaging for internet or catalogue gift deliveries
- Certificate of conformance
- Commercial invoice for customs declarations
- Material Safety Data Sheets



Zapraszamy do kontaktu!
Więcej informacji: www.kreski.pl

Technical Specifications

	Description	Caliper
Facestock	White smooth direct thermal topcoated paper	59 microns
Adhesive	Permanent acrylic adhesive	9 microns
Facestock	Clear polypropylene	21 microns
Total		89 microns $\pm 10\%$

Recommended Zebra Printers:

Desktop, mid-range and high-performance thermal printers

Minimum Application Temperature:

When the label is applied, the environment and surface should be above this temperature

-5°C

Service Temperature Range:

Following correct application and appropriate dwell time (usually 24hrs) the media will withstand this temperature range

-29°C to 55°C

Recommended Storage Conditions:

Storage of product before use

1 year duration when stored at 21°C at 50% RH

Expected Life Span in Application:

Following correct application and appropriate dwell time (usually 24hrs) we expect, but do not warrant, a life span as indicated

Indoor use, 1 year

Expected Chemical Resistance

	Weak					Moderate				Harsh			Extreme				
	Blood	Body Fluid	Salt Water	Water	Window Cleaner	Alcohol	Ammonia	Bleach	IPA	Gasoline	Grease	Oil	Acetone	IR Reflow	MEK	TCE	Xylene
DT	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓

“✓” indicates acceptable chemical resistance

Product Performance and Suitability

The information contained in this document is to be used for guidance only and is not intended for use in setting specifications. All purchasers of Zebra products shall be solely responsible for independently determining if the product conforms to all requirements of their unique application.

For testing of this material please contact your Supplies Specialist Representative.