

Media Type

Material Type

Printing

Technology

Finish



High Tack

Chemical Resistance

Z-Perform™ 1000T 190 Tag

Label			Permanent
Receipt		Adhesive Type	Removable
Tag	✓		No Adhesive
Wristband		Environment	Indoor
Paper	✓		Outdoor
Synthetic			Cold Temperature
Direct Thermal		Properties	Deep Freeze
o Ribbon Required)			High Temperature
Thermal Transfer (Ribbon Required)	✓		Ultra High Temperature

from stock on ZipShip

Additional Features

- Good print quality when printed with Zebra 2300, 2100, 3400 and 3200 ribbons with a recommended Zebra printer
- BfR Recommendation XXXIV for direct contact with dry, moist and non-fatty foodstuffs
- Complies with DIN EN 71 part 3 and part 9 as the product does not release any heavy metals and does not contain prohibited amines or colourants
- **BPA** free

Suggested Applications

Indoor cold temperature labelling

(no Ribbon

Matte

Gloss

- Visitor identification tags
- Admission tickets
- Warehouse and inventory control tags
- Shop floor / work in progress tracking tickets
- Shelf-edge tags
- Packaging inserts
- Pallet tagging







Technical Specifications

	Description		Caliper
Facestock	190gsm matte white uncoated paper		170 microns
		Total	170 microns ±10%

Recommended Zebra Printers: Desktop, mid-range and high-performance

thermal printers

Recommended Zebra Ribbons: 2300, 2100, 3400, 3200

Minimum Application Temperature: 0°C

When the label is applied, the environment and surface should be above this temperature

> **Service Temperature Range:** -43°C to 93°C

Following correct application and appropriate dwell time (usually 24hrs) the media will withstand this temperature range

Recommended Storage Conditions: 1 year duration when stored at 0°C to 21°C

Storage of product before use at 35% to 50% RH

Expected Life Span in Application:

Following correct application and appropriate dwell time (usually 24hrs) we expect, but do not warrant, a life span as indicated

Indoor use, for 1 year+

Product Performance and Suitability

The information contained in this document is to be used for guidance only and is not intended for use in setting specifications. All purchasers of Zebra products shall be solely responsible for independently determining if the product conforms to all requirements of their unique application.

For testing of this material, please order from the ZipShip price list or order sample roll SAMPLE5284.



Zapraszamy do kontaktu! Więcej informacji: www.kreski.pl