



MS852B+ ESD

Bluetooth® ESD-safe 2D Imager Scanner

The MS852B+ ESD (Electrostatic discharger) Bluetooth® 2D imager scanner is a high-performance device but additional designed to satisfy the stringent requirements of cleanrooms and static-safe manufacturing environments.

ESD Protection

The MS852B+ ESD (Electrostatic discharger) Bluetooth® 2D imager scanner is a high-performance device but additional designed to satisfy the stringent requirements of cleanrooms and static-safe manufacturing environments. unitech's MS852B+ ESD-safe scanner is made by internal mixed way with antistatic agent to protect MS852 series to be ESD safe to be used at ESD protected area including its cable. With the Internal mixed way, the body of the product and its cable can withstand ESD up to $10^5 \sim 10^9$ ohms per square and no containing Chlorine material. The Internal mixed way can provide a longer time of ESD protection than external addition way due to external additional anti-static in the latter part of the packaging or processing process was wiped away. An internal mixed antistatic agent can continue to add antistatic agent to the plastic surface, to make up the surface due to wipe and the amount of antistatic agent consumed. It is a reliable tool to streamline your workflow in manufacturing environments.

Move without Restrictions

Featuring 2D scanning technology, the MS852B+ESD has the ability to capture most 1D / 2D barcodes on mobile screens, even damaged or poorly printed barcodes and special barcode symbologies such as OCR on passport, Dot codes on tires or cigarette package, and Digimarc barcode on special retail packages. Moreover, the MS852B+ESD supports Bluetooth® dual-mode technology (Bluetooth LE® V4.2 & Bluetooth® 2.1+EDR, Class 1) to give you the freedom and bring your business the flexibility. It is compatible with any smartphone, tablet, or computer—the MS852B+ESD pairs easily to any mobile device or PC. Besides, it allows users to transmit data to the host from up to 100 meters from the base. MS852B+ ESD also can automatically populate electronic forms in a single scan from US driver's licenses or ID card. With its advanced barcode technology and durable design, the MS852B+ ESD handheld scanner is a highly reliable tool to increase productivity and efficiency.

Intuitive and User-Friendly

With excellent motion tolerance design, the MS852B+ ESD increased scan speed and operational effectiveness even while moving. Equipped with a louder beeper and brighter LED indicators, the MS852B+ ESD allows users to recognize the feedbacks easily even in dark environment.

Ultra-Durability

While sustaining a 2.1 meters drop to concrete, MS852B+ ESD incorporated with IP42 rugged design for protection against dust and moisture. Moreover, the built-in long lifecycle trigger of 10 million times guarantees a continuous productivity for best reliability. This scanner can be used in the most practical way depending on the scanning task in various solutions in retail, logistics, manufacturing, hospitality, and government.

Features

- Withstands ESD up to $10^5 \sim 10^9$ ohms per square
- Megapixel barcode sensor that enhances the maximum compatibility
- Support most 1D / 2D barcode on mobile screens, even damaged or poorly printed barcodes
- Support OCR, Dot codes, and Digimarc barcodes
- Support Bluetooth® dual-mode technology (Bluetooth LE® V4.2 & Bluetooth® 2.1+EDR, Class 1)
- Wireless transmission range up to 100m in the line of open sight.
- Long battery life up to 25 hours per a fully charged battery
- Durable design: IP42 and 2.1m drop spec
- Auto Bluetooth pairing / auto switch between trigger & presentation mode with cradle



MS852B+ ESD

Specifications

Symbologies

1D

Codabar, Code 11, Code 128, Code 2 of 5, Code 39, Code 93 and 93i, EAN/JAN-13, EAN/JAN 8, IATA Code 2 of 5, Interleaved 2 of 5, Matrix 2 of 5, MSI, GS1 Databar, UPC-A, UPC E, UPC-A/EAN-13 with Extended Coupon Code, Coupon GS1 Code 32(PARAF), EAN-UCC Emulation, GS1 Data Bar, TLC39 2D Stacked: Codablock A, Codablock F, PDF417, MicroPDF417

2D

2D Matrix: Aztec Code, Data Matrix, MaxiCode, QR Code, Chinese Sensible (Han Xin), Grid Matrix, Dot Code
Postal: Australian Post, British Post, Canadian Post, China Post, Japanese Post, Korea Post, Netherlands Post, Planet Code, Postnet
Support OCR barcodes
Support DPM barcodes
Prefix, Suffix, Code ID, Reformatting Date

OCR Barcodes
DPM Barcodes
Data Formatting

Electrical

Indicator
Battery Type
Battery Capacity
Battery Charging time
Operating Time

LED & Beeper & Vibrator
Rechargeable and replaceable battery pack.
2850mAh
<6.5 hours
>25 hours
Up to 50,000 scans at 1 scan/5 second"

Environmental

ESD Protection
Mechanical Shock
Operating Temperature
Storage Temperature
Relative Humidity
IP Rating

Functional after 8K Contact and 15K Air
2.1 M onto concrete (scanner only)
-10°C to 50°C (14°F to 122°F)
-40°C to +70°C (-40°F to +158°F)
95% non-condensing
IP42

Accessories

USB cable
1-slot charging cradle
Battery pack

Package Contents

MS852B+ ESD Scanner with battery
Cradle
Interface cable

System

Memory 7MB for batch mode/ 20KB for auto mode
Key Trigger Key

Optical & Performance

Sensor 1280 X 800 global shutter
Illumination Red laser or 528 nm visible green LED
Ambient Light White or Red LED
100,000 Lux (Sunlight)
Skew Angle ±60°
Pitch Angle Sensor ±60°
Roll Angle 0 - 360°
Optical Resolution 1D 3mil/ 0.075mm
Printing Contrast Scale Minimum 20%
Depth of Field Symbology | Density | Near | Far
(DOF PCS=80%) 13 mil UPC 3.8 cm 40.5 cm
3 mil C39 6.6 cm 18.3 cm
5 mil C39 5.3 cm 26.5 cm
6,7 mil DM 7.2 cm 18.0 cm
10 mil DM 5.9 cm 24.8 cm
5 mil PDF 7.4 cm 18.6 cm
6,7 mil PDF 5.9 cm 23.8 cm
6,7 mil QR 7.2 cm 16.3 cm
15 mil QR 2.7 cm 30.8 cm

Communication

Radio Bluetooth LE® V4.2
Bluetooth® 2.1+EDR, Class 2 Dual mode
Wireless Coverage 100m (line of sight)
Interface/ Profile Serial Port and HID profiles
Host Interface supported USB

Functionality

Operation Mode Trigger Mode, Presentation Mode, Buffer Mode

Regulatory Approvals

CE, FCC, BSMI, VCCI, NCC, TELEC, BQB



Headquarters

Taipei, Taiwan
<http://www.ute.com> e-mail: info@hq.ute.com

unitech America

Los Angeles
<http://us.ute.com> e-mail: info@us.ute.com
<http://can.ute.com> info@can.ute.com
Mexico
<http://latin.ute.com> e-mail: info@latin.ute.com

unitech Asia Pacific & Middle East

Taipei
<http://apac.ute.com> info@apac.ute.com / info@india.ute.com
<http://mideast.ute.com> info@mideast.ute.com

unitech Europe

Tilburg / Netherlands
<http://eu.ute.com> e-mail: info@eu.ute.com

unitech Japan

Tokyo
<http://jp.ute.com> e-mail: info@jp.ute.com

unitech Greater China

Beijing, Shanghai, Guang Zhou, Xiamen
<http://cn.ute.com> info@cn.ute.com
Taipei <http://tw.ute.com> info@tw.ute.com



Zapraszamy do kontaktu!
Więcej informacji: www.kreski.pl



www.ute.com
02/21 Rev.C