



1500 Series Scanners from CipherLab

Accelerate your business

Handheld scanners are much faster than human fingers. Pull the trigger and the work is done instantly: complete series, update inventories, check patient records, and record production line parts and activities. Handheld scanners accelerate work with error-free capture of critical information, keeping your company data up to date and up to the minute.

Cut costs

CipherLab scanners are versatile, agile, and priced right for long-lasting value. Your company benefits from years of use, backed by a manufacturer honored in the industry for its innovative, reliable products and customer service. The 1500 series scanners capture data from regular to long barcodes with a choice of linear imager, 2D imager, or laser. Together with *Bluetooth*® cordless and corded applications, the 1500 series scanners help you run business more efficiently with improved operations.



Go where the work takes you

The 1500 series includes wireless scanners to unleash workers, so they can go where the work is and get more done, in more places. Our 1500 series *Bluetooth*® scanners connect with the communication stand up to 90 meters (295 feet) away. Beyond that, they keep working by storing information until the scanner is back in range.

Smart solutions with immediate payoffs

Accelerate receiving with fast, reliable, low-cost CipherLab 1500 handheld scanners

European retail giant Valora deployed 1,100 CipherLab 1500 scanners to improve product receiving in its Swiss sales outlets.



"After performing extensive tests, it was clear that the CipherLab scanner performed much better than any of the other solutions. We had no previous experience with CipherLab and were positively surprised with its error-free scans, reliability, and the convincing value for money it offers."

Christian Wurger, Head of the Corporate IT Operation/ Support, Valora, Switzerland

Streamline tracking and delivery with wireless CipherLab *Bluetooth*® scanners

To ensure better tracking and delivery of mail and goods, Brazil's ECT, the largest post office in Latin America, relies on the flexibility and productivity of CipherLab

Bluetooth scanners.



"With the new scanners, employees can easily reach the items to scan. They can walk around outdoors and scan packages in the unloading/departing zones, allowing them to work faster and get more work done. And the database is always updated when they are back in wireless range."

Marcel Gomes, Complex Solutions Provider for ECT, Brazil.

Update stock and reply distribution requirements in real time with wireless CipherLab Bluetooth® scanners

To ensure accurate CD/DVD replenishment, ASDA/Wal-Mart combines the wireless connectivity of CipherLab *Bluetooth*® scanners and Smartphones/PDAs to instantly send stocking requirements to the distribution center.



"After searching worldwide for scanners with good communication capabilities, we found CipherLab *Bluetooth*® scanners with high-quality and reliable performance. CipherLab scanners not only provide real-time stocking updates, but also record deliveries made to the actual supermarkets, which improves the efficiency of our business operation."





Snappy scanning, speedy decoding

The 1500 series with linear imaging reader scan and decode barcodes up to 520 times per second to speed work, eliminate rescans and keep up with your fastest operation. This high speed delivered with low power consumption makes auto-sense scanning very effective.

Wireless freedom

Range of Operation

The 1500 series *Bluetooth*® wireless scanners have a 90-meter line-of-sight range from the communication stand. If it's not in range, with the optional linear imager and laser scanners, the scanner's buffer memory holds up to 256 scans in reserve, ready to transmit automatically when you're back in range again. Or, use batch mode to record over 32,000 scans – that's freedom to roam widely. The 1500 *Bluetooth*® scanner with 2D reader has a buffer memory of 10 K or 4 MB in batch mode.

House of Wireless Power

CipherLab offers you the multi-shift service with the 1500 series *Bluetooth*® scanner. Without interruption of workflow, users get to finish work more productively and efficiently.

A Great Variety at Your Fingertips

Every business is different and has different scanning needs, which is why CipherLab have a broad range of scanners to suit any businesses whatever their needs. The 1500 series comes in a range of varieties. The linear imager scanner offers the option of reading long barcodes, for example the ones on bills, making it suitable for utility companies, banks, and collecting agencies. The option of 2D imager is good for scanning barcodes on medicine packaging or hospital equipments making them suited for pharmaceutical or hospitals.

PC Software to Custom-Configure Scanners to Any Environment

CipherLab **ScanMaster** software provides comprehensive tools to configure any scanner, such as enabling and disabling hands-free scanning, choosing edit format and symbology types, plus more. With ScanMaster, scanners can be easily customized to fit every working environment. ScanMaster for PC is included with all CipherLab scanners. In addition, 1500 series is also supported by **CipherConnect** which is a COM-to-key utility designed for CipherLab *Bluetooth*® scanners to work as an input device for smart devices, such as Smartphone or PDA. The software enables intensive data collection and transmission via CipherLab *Bluetooth*® scanner to the smart device.



















		1 1 1 6	
(₁ eneral	Hand	lheld Scani	ner .
			19

### Content is a content of the cont												
Control Cont				1500P	1560P	1502	1562	1504P	1504A	1564A		
Content Cont			Linear Imager		La	ser		2D Imager				
Seminated profiles	Category		Corded		Corded	, ,	Corded		Bluetooth® Class 2 (2.4 GHz) Version 4.0+EDR			
Optional serious	RF Communication of Bluetooth® scanner	Communication of			-					90 m ¹ / 295 ft. line of sigh		
Electrical Eught source	Standard promo			CCD Linear Ser		La	,	CMOS Image Sensor CMOS Image Sensor		· ·		
Code 39 - 3 ml										•		
Code 39 - 3 ml		Resolu	tion	3 mil		4	4 mil		3 mil - 1D barcode / 5 mil - 2D barcode			
Depth UPCA 13 mil				· ·								
Programmatice Figure Fig		Depth				1.5 to 51.5 cm / 0.6 to 20.3 in.						
Fedit Group Code 10m2												
Section Sect		field		ıil								
Scanning angle			Long barcode	1500P : 10 to 20 cm / 3.9 to 7.9 in			-					
Minimum PCS		Scanni				Pitch +60° Skew+60°	tch +60° Skew+60°					
Sean rate \$20 scars/ second 100 scars/ second 60 scars/ second 30 scars/ second Antibert llumination 100,0000 lux												
Amberit Illumination Hands-free scanning Auto-sense and continuous modes Continuous mode Codebar, Code 39, Code 39, Code 128, GS1 DataBar (RSS), Industrial 2 of 5, Interfeave 2 of 5, ISBT-128, Italian and French Pharmacodes, Matrix 2 of 5, Imperit Memory 200, Interfeave 2 of 5, ISBT-128, Italian and French Pharmacodes, Matrix 2 of 5, Imperit Memory 200, Interfeave 2 of 5, ISBT-128, Italian and French Pharmacodes, Matrix 2 of 5, Imperit Memory 200, Interfeave 2 of 5, ISBT-128, Italian and French Pharmacodes, Matrix 2 of 5, Imperit Memory 200, Interfeave 2 of 5, ISBT-128, Italian and French Pharmacodes, Matrix 2 of 5, Imperit Memory 200, Imperit Memory 200	Performance			-		-						
Hands-fice scanning Auto-sense and continuous modes Codabar, Code 39, Code 93, Code 128, CS1 DataBar (RSS), Industrial 2 of 5, 150 peries 10 sorres 150 peries 10 sorres 150 peries 10 parameter 150 peries 150 peries 10 parameter 150 peries 150 peries 150 peries 10 parameter 150 peries 150 pe		Scan ra	ate	520 scan	s/ second	100 scan	s/ second	60 scans / second 30 scans / second				
Codabar, Code 39, Code 93, Code 128,GS1 DataBar (RSS), Industrial 2 of 5, Interleave 2		Ambien	t illumination			100,0	00 lux					
Description		Hands-	free scanning	Auto-sense and o	continuous modes	Continuo	ous mode	Auto-se	ense and presentation	modes		
Language support		Barcodes support		Codabar, Code 39, Code 93, Code 128,GS1 DataBar (RSS), Industrial 2 of 5, Interleave 2 of 5, ISBT-128, Italian and French Pharmacodes, Matrix 2 of 5, MSI, Plessey, Telepen, UPC / EAN / GS1-128, and more 1500 series 1D scanners 2D: PDF417, MicroPDF417, Data Mat 2D: PDF417, Micr					ipport 417, Data Matrix, R Code, Aztec, MaxiCode, stal Codes: US PostNet, tal, Australian Postal,			
Dimension x w x H		Progran	nmable features	Data editing, interface selection, symbology configuration								
Dimension x w x H		Langua	age support									
Weight Weight Window Color Weight Window Color Weight Window Color Weight Weig		Dimens	sion L x W x H			15.3 x 6	6.1 x 9.3 cm / 6.0 x 2.4	x 3.7 in.	· ·			
Color Switch Switch Switch Tactile Switch	Physical	Weight		1500P: 149 g / 5.2 oz.	173 g / 6.1 oz.				144 g / 5.1 oz.	172 g / 6.1 oz.		
Memory Buestoon Scanner	•	Color					Black					
Figure Second S		Switch		Tactile Switch								
Voltage	Electrical	for Blueto	oth scanner		4 K / 512 K		4 K / 512 K	10 K / 4 MB				
Power consumption Standby / Operating 1500P: 20 mA / 286 mA 20 mA / 250 mA 35 mA / 210 mA 25 mA / 210 mA 60 mA / 420 mA 25mA / 270 mA 25mA / 300 mA Temperature Operating: 0°C to 50°C / 32°F to 122°F Storage: -20°C to 60°C / -4°F to 140°F Humidity Operating: 10% to 90% Storage: 5% to 95% Impact resistance Ingress protection IP30 Electrostatic discharge Is kV contact ±15 kV air Electrostatic discharge BSMI, CE, RCM, FCC, IC, NCC, SRMC, JRL FCC, IC, NCC, SRMC, JRL FCC, IC, NCC, SRMC, JRL ROHS, REACH, WEEE, ErP Configuration Setup options include Windows®-based ScanMaster software, by direct connection or printing out barcode settings USB, RS232 and keyboard wedge cables, hands-free adjustable stand, Three-way desk/wall/auto-sense stand with optional weighted base, communication stand for Bluetooth® scanner provides Bluetooth® communication for up to 7 scanners, single battery charger for Bluetooth® scanner										26 hours based on 1 scan / 5 second		
Standby / Operating 1500P: 20 mA / 286 mA 20 mA / 250 mA 35 mA / 210 mA 25 mA / 210 mA 60 mA / 420 mA 25 mA / 210 mA 25 mA / 300 mA Temperature		Voltage	•	+5 V ±10% / 3.7 V 800 mAh Li-ion battery								
Humidity Operating: 10% to 90% Storage: 5% to 95% Impact resistance Ingress protection Electrostatic discharge BSMI, CE, RCM, FCC, IC IC, NCC, SRMC, JRL Regulatory Compliance Configuration Setup options include Windows®-based ScanMaster software, by direct connection or printing out barcode settings USB, RS232 and keyboard wedge cables, hands-free adjustable stand, Three-way desk/wall/auto-sense stand with optional weighted base, communication stand for Bluetooth® scanner provides Bluetooth® communication for up to 7 scanners, single battery charger for Bluetooth® scanner				1500P: 20 mA / 286 mA	20 mA / 250 mA	35 mA / 210 mA	25 mA / 210 mA	60 mA/ 420 mA	25mA / 270 mA	25mA / 300 mA		
User Environment Impact resistance		Tempe	rature	Operating: 0°C to 50°C / 32°F to 122°F Storage: -20°C to 60°C / -4°F to 140°F								
User Environment Impact resistance												
User Environment Electrostatic discharge BSMI, CE, RCM, FCC, IC, Regulatory Compliance BSMI, CE, RCM, FCC, IC, IC, NCC, SRMC, JRL Regulatory Compliance BSMI, CE, RCM, FCC, IC, RC, IC, NCC, SRMC, JRL RoHS, REACH, WEEE, ErP Configuration Setup options include Windows*-based ScanMaster software, by direct connection or printing out barcode settings USB, RS232 and keyboard wedge cables, hands-free adjustable stand, Three-way desk/wall/auto-sense stand with optional weighted base, communication stand for Bluetooth* scanner provides Bluetooth* communication for up to 7 scanners, single battery charger for Bluetooth* scanner				1.5 m (4.9 ft)								
Electrostatic discharge BSMI, CE, RCM, BSMI, CE, RCM, FCC, IC, IC, NCC, SRMC, JRL BSMI, CE, RCM, BSMI, CE, RCM, FCC, IC, KC RC, NCC, SRMC, JRL ROHS, REACH, WEEE, ErP Configuration Setup options include Windows®-based ScanMaster software, by direct connection or printing out barcode settings USB, RS232 and keyboard wedge cables, hands-free adjustable stand, Three-way desk/wall/auto-sense stand with optional weighted base, communication stand for Bluetooth® scanner provides Bluetooth® communication for up to 7 scanners, single battery charger for Bluetooth® scanner		Ingress	protection	IP30								
Regulatory Compliance BSMI, CE, RCM, FCC, IC RC, NCC, SRMC, JRL ROHS, REACH, WEEE, ErP Configuration Setup options include Windows*-based ScanMaster software, by direct connection or printing out barcode settings USB, RS232 and keyboard wedge cables, hands-free adjustable stand, Three-way desk/wall/auto-sense stand with optional weighted base, communication stand for Bluetooth* scanner provides Bluetooth* communication for up to 7 scanners, single battery charger for Bluetooth* scanner	User Environment	Electros	tatic discharge	±8 kV contact ±15 kV a				ir				
Configuration Setup options include Windows®-based ScanMaster software, by direct connection or printing out barcode settings USB, RS232 and keyboard wedge cables, hands-free adjustable stand, Three-way desk/wall/auto-sense stand with optional weighted base, communication stand for Bluetooth® scanner provides Bluetooth® communication for up to 7 scanners, single battery charger for Bluetooth® scanner										BSMI, CE, RCM, FCC, IC, KC, NCC, SRMC, JRL		
USB, RS232 and keyboard wedge cables, hands-free adjustable stand, Accessories Three-way desk/wall/auto-sense stand with optional weighted base, communication stand for <i>Bluetooth</i> ® scanner provides <i>Bluetooth</i> ® communication for up to 7 scanners, single battery charger for <i>Bluetooth</i> ® scanner				RoHS, REACH, WEEE, ErP								
Accessories Three-way desk/wall/auto-sense stand with optional weighted base, communication stand for Bluetooth scanner provides Bluetooth communication for up to 7 scanners, single battery charger for Bluetooth scanner	Configuration			Setup options include Windows®-based ScanMaster software, by direct connection or printing out barcode settings								
	Accessories		Three-way desk/wall/auto-sense stand with optional weighted base, communication stand for Bluetooth® scanner									
	Warranty		5 years 3 years 3 years (engine 1 year) 3 years 3 years (engine 1 year)									

1.It is based on communication stand without weighted base. 2.The data is tested with USB interface.



HEADQUARTERS CipherLab Co., Ltd. 12F, 333 Dunhua S. Rd., Sec.2 Taipei, Taiwan 10669 Tel +886 2 8647 1166 Fax +886 2 8732 3300 www.cipherlab.com

CipherLab Electronics Trading (Shanghai) Co., Ltd. E Room, 9F, No.726 West Yan'an Road. Changning District, Shanghai, China 200050 Tel +86 21 3368 0288 Toll Free 400 920 0285 Fax +86 21 3368 0286 CipherLab USA Inc. 2552 Summit Avenue STE 400 Plano, Texas, USA 75074 Tel +1 469 241 9779 Toll Free 888 300 9779 Fax +1 469 241 0697 CipherLab Europe Cahorslaan 24, 5627 BX Eindhoven, The Netherlands Tel +31 (0) 40 2990202