

The new generation TSC mobile printer, the Alpha-30R, is user-friendly and drop-resistant. It enhances customer service, boosts productivity and improves shopper experience in retail stores. The Alpha-30R is stylish and comfortable in use and prints receipts or labels on-demand. Mobile printing operations can be carried out much faster and with more accuracy.

The Alpha-30R is compact and very efficient, it also has a large capacity smart battery that enables it to carry out a full shift of work without interruption. The Apple-certified MFi Bluetooth® 5.0 connection and 802.11ac Wi-Fi fast roaming features allow the Alpha-30R to provide reliable and seamless communication with user devices to achieve optimal mobile field-work.

The Alpha-30R's smart battery paired with SOTI Connect and TSC Console remote printer management gives real-time visibility that helps enterprises scale their business activities seamlessly and efficiently.

The Alpha-30R design emphasizes durability, it has the most robust specifications in its class. The ruggedness of the Alpha-30R meets MIL-STD-810 military-grade standards for drop and vehicle vibrations. It has an IP54 rating and will withstand a 2.1 m drop and a 1.0 m tumble. While the protective case allows it to withstand a 2.5 m drop in a harsh environment.

The Alpha-30R has a full line of accessories to meet a range of different environments on the go. It is especially suited for retail applications. It is also environmentally friendly and can support linerless media printing to reduce waste. Go green!

### **Key Features**



# Sophisticated TSC Sense Care

- Auto scans and detects printhead bad dots during printing
- Monitors the smart battery to ensure full-shift productivity, reduces total cost of ownership and avoids downtime



### Dynamic Remote Printer Management

 SOTI Connect and TSC Console support multiple management tasks. This reduces costs and avoids downtime of businesscritical devices



# Seamless Mobility Communication

- MFi Bluetooth® 5.0 with NFC tap-topair setup enables easy connectivity
- Dual-band Wi-Fi with fast roaming as well as enterprise-grade security ensures reliable and safe operation



# Full Line of Accessories

- Assist in performing diverse labeling tasks including hands-free mobility
- Fulfills linerless printing needs



# Industry-specific Durability Standards

- IP54 rating for dust and water resistance
- Rugged design for drops from 2.1 m and tumbles from 1.0 m



### Integrated Software Pack

- Supports label printing applications for different platforms
- TSC mobile printing app is available for both iOS and Android™ users

### **Applications**



#### Retail

- Chain stores shelf labeling
- Super market relabeling
- Food delivery



#### **Healthcare**

- Mobile specimen collection
- Drug management
- Asset label



#### **Transportation and Logistics**

- · Shipping and receiving
- Direct store delivery



#### **Manufacturing**

- Raw materials, finished goods
- Asset management



Zapraszamy do kontaktu! Więcej informacji: www.kreski.pl



## **Mobile Printing For Your Business**



## **Key Benefits**



#### Faster and Rugged Design for On the Go Printing

The innovatively designed Alpha-30R features two models with different print speeds. The basic model offers up to 5 ips, while the premium model goes up to 6 ips to enhance field worker productivity. They are built for durability, and the Alpha-30R is IP54 rated for dust and water resistance. It has been rigorously tested to withstand a 2.1 m drop and an 800 drops tumble. When used with a protective case, the ruggedness level is improved and the printer will withstand a 2.5 m drop. The Alpha-30R meets MIL-STD-810 military standards for drop and vehicle vibration as proof of the rugged design for all your field mobility solutions.



#### Easy Remote Printer Management with SOTI Connect and TSC Console

Quickly and remotely monitor a fleet of Alpha-30R mobile printers, configure settings, deploy programs, and troubleshoot problems using SOTI Connect and TSC Console's powerful printer management tools to avoid downtime and lower the total cost of ownership. The Alpha-30R's smart battery, paired with printer management tools, can intelligently monitor battery health status and remaining capacity to ensure continuous productivity over a full shift.



### **Seamless Mobility Communication**

Seamless and reliable wireless connectivity is crucial for mobile devices. TSC has introduced our latest 802.11 a/b/g/n/ac Wi-Fi certified module which enables fast roaming and enterprise-grade security to ensure reliable and safe operation. The Alpha-30R is equipped with Apple-certified MFi Bluetooth® 5.0 with NFC tap-to-pair for easy connectivity, and users get a secure connection to print labels on-demand. The TSC Mobile Utility APP is available for both iOS and Android™ users. This APP makes it easy for authorized IT staff to troubleshoot and solve mobile printer problems quickly and efficiently.



#### **Full Line of Accessories**

The Alpha-30R offers a full line of accessories including a protective case, multiple battery charging options and more to meet your receipt and label printing requirements. Available with a complete forklift and vehicle accessory option, the Alpha-30R's vehicle mount adaptor gives users the flexibility to easily integrate the printer with a forklift with intuitive RAM® mount components.



#### **Integrated Software Pack**

The Alpha-30R supports OPOS drivers and provides mainstream platform SDK including Windows™, Windows™ Mobile (WinCE), Android™, and iOS. The OPOS and SDK software packs integrated into the Alpha-30R mobile printer allow users to interpret ESC/POS commands and to develop applications compatible with the unified POS specification. After integration, the customized software can be leveraged and tailored to switch between POS terminals and printers for quick port communications, connections, and print command transfers.

# Alpha-30R Accessories



Alpha-30R	Description	Factory Option	User Option
	Protective Case with Shoulder Strap The protective case enhances the extra level of protection for harsh environment especially for the outdoor usage.		~
	Shoulder Strap Designed for carrying the printer directly without a protective case.		~
	<b>Belt Clip</b> Use the belt clip for a complete hands-free solution.		~
	<b>Li-ion Smart Battery</b> The Li-on smart battery works with TSC Console and SOTI Connect to monitor battery information, charge cycles, and remaining capacity.		~
	<b>1-Slot Docking Cradle</b> Easily charge the printer without removing the battery.		~
Total Total Total	<b>4-Slot Docking Cradle</b> Easily charge multiple printers without removing the battery.		~
TEC .	<b>1-Slot Battery Charger</b> Use the 1-slot charger to quickly charge the battery without any downtime.		~
The state of the s	<b>4-Slot Battery Charger</b> The 4-slot charger is well-suited for heavy-duty missions.		~
	<b>12-24VDC Vehicle Power Adaptor</b> For automobile vehicle plug to charge on the car.		~
	<b>12-60VDC Vehicle Power Adaptor</b> For automobile vehicle plug to charge on the car.		~
	Battery Eliminator Connect printer and vehicle power source directly by open-ended wire without using battery. It can be used with vehicle mount adaptor.		~
	<b>Vehicle Mount Adaptor</b> Easily mount the printer on a forklift.		~
	<b>Linerless Kit</b> The linerless kit suits linerless printing needs.	~	

## ZOD I Doto Choot

Aipna-30i	R   Data Sheet		
Printer model	Alph	a-30R	
Version	Basic	Premium	
Resolution	8 dots/mm (203dpi)		
Printing method	Direct Thermal		
Max. print speed	Up to 127 mm (5")/second	Up to 152 mm (6")/second	
Max. print width	72 mm (2.83")		
Max. print length	2,794 mm (110")		
Enclosure	Plastic with rubber over molded		
Physical dimension	118 mm (W) x 158 mm (H) x 68 mm (D) 4.64" (W) x 6.22" (H) x 2.68" (D)		
Weight (including battery)	0.65 kg (1.43 lbs)		
Drop specification	2.1 m (6.9 ft), with protective case can be 2.5 m (8.2 ft)		
MIL-STD 810	Drop and vibration		
Tumble test	800 free falls from 1 m (3.3 ft), with protective case can be 1000 free falls from 1 m (3.3 ft)		
IP rating	IP54 (w/o case, paper path is excluded)		
Max. roll capacity	57 mm (2.24") 0D		
Processor	32-bit RISC CPU		
Memory	128 MB SDRAM, 128 MB Flash		
Interface	Either one selected Type C USB 2.0 + MFi Bluetooth 5.0 + Passive NFC tag Type C USB 2.0 + 802.11 a/b/g/n/ac with Bluetooth 4.2 + Passive NFC tag Type C is for communication only		
Power	7.4V DC, 3080 mAh Li-ion rechargeable battery	7.4V DC, 3030 mAh Li-ion rechargeable smart battery	
Operation switch, button	<ul> <li>3 buttons (On/off, feed, and cover-open)</li> <li>2 color LEDs for printer status and battery charging status</li> <li>1 LCD for printer status</li> </ul>		
Sensors	Reflective sensor     Head open sensor	Reflective sensor     Gap sensor     Head open sensor	
Real time clock	Standard		
Internal fonts	8 alpha-numeric bitmap fonts     One Monotype Imaging® CG Triumvirate Bold Condensed scalable font		
Bar code	1D bar code     Code 39, Code 93, Code 128UCC, Code 128 subsets A.B.C, Codabar, Interleave 2 of 5, EAN-8, EAN-13, EAN-128, UPC-4     UPC-E, EAN and UPC 2(5) digits add-on, MSI, PLESSEY, POSTNET, China POST, GS1 Data bar     2D bar code     PDF-417, Maxicode, DataMatrix, QR code, Aztec		
Printer language	TSPL-EZC (EPL2, ZPL2, CPCL), or ESC-POS		
Media type	Receipt paper, receipt paper with black mark in printing side, selected label, linerless (outside wound)	Receipt paper, receipt paper with black mark in printing side or backside, label, linerless (outside wound)	
Media width	25.4 ~ 80 mm (1	l" ~ 3.15" w/ liner)	
Media thickness	0.06 ~ 0.16 mm (2.36 ~ 6.3 mil)		
Media height	Label: Min.	25.4 mm (1")	
Media core diameter	Standard: 12.7 mm (0.5") Optional: 19.05 mm (0.75")		
Environment condition	Operation: $-20 \sim 55^{\circ}\text{C}$ ( $-4 \sim 131^{\circ}\text{F}$ ), $10 \sim 90\%$ non-condensing Storage: $-30 \sim 70^{\circ}\text{C}$ ( $-22 \sim 158^{\circ}\text{F}$ ), $10 \sim 90\%$ non-condensing		
Environmental concern	Comply with RoHS, WEEE		
Accessories	• Quick start guide • Belt Clip • Li-ion battery • Power adapter		
Limited warranty	Printer: 2 years Print head: 25 km (1 million inches) or 12 months which comes first Platen: 50 km (2 million inches) or 12 months which comes first Pattery: 1 year		

Product models and specifications are subject to change without notice





**Factory options** 

**User options** 







• Battery: 1 year

• Protective case with shoulder strap

• Type C USB 2.0 cable

• 1-slot docking cradle

· 4-slot docking cradle

• 1-slot battery charger

• Shoulder strap

• 0.75" media core adaptor



Linerless kit



• 4-slot battery charger

with RAM® MOUNTS

• 12-24VDC vehicle power adaptor

• 12-60VDC vehicle power adaptor

battery eliminator

• Vehicle mount adapter can be used

• 12-48VDC power source with











**Treski** 

#### **CORPORATE HEADQUARTERS**

TSC Auto ID Technology Co., Ltd. Tel: +886 2 2218 6789 E-mail: apac\_sales@tscprinters.com

#### LI ZE PLANT

TSC Auto ID Technology Co., Ltd. Tel: +886 3 990 6677 E-mail: apac\_sales@tscprinters.com

#### **AMERICAS**

TSC Auto ID Technology America Inc. Tel: +1 657 258 0808 E-mail: americas\_sales@tscprinters.com

TSC Mexico Representative Office Tel: +1 52 (33) 3673 1406  $E\text{-}mail: americas\_sales@tscprinters.com$ 

TSC Brazil Representative Office Tel: +55 (11) 3554 7225 E-mail: americas\_sales@tscprinters.com

#### **EMEA**

TSC Auto ID Technology EMEA GmbH Tel: +49 (0) 8106 37979 000 E-mail: emea\_sales@tscprinters.com

#### **RUSSIA**

TSC Auto ID Technology EMEA GmbH Tel: +7 495 249 9017 E-mail: emea\_sales@tscprinters.com

#### **Middle East**

TSC Auto ID Technology ME Ltd, FZE Tel: +971 4 2533 069 E-mail: emea\_sales@tscprinters.com

#### **ASIA PACIFIC**

TSC Auto ID Technology Co., Ltd. Tel: +886 2 2218 6789 E-mail: apac\_sales@tscprinters.com

TSC India Distributor's Office Tel: +91 2267 082 465 E-mail: apac\_sales@tscprinters.com

#### CHINA

Tianjin TSC Auto ID Technology Co., Ltd. Tel: +86 22 5981 6661 E-mail: apac\_sales@tscprinters.com

#### **KOREA**

TSC Korea Representative Office Tel: +82 2 852 3322 E-mail: apac\_sales@tscprinters.com