

PRINTER





The Versatile Front-Desk Card System

The **Elypso** printer was designed for all your individual plastic card printing and personalization needs: monochrome or color, with multiple encoding options.

Specially developed for use at customer-facing counters, **Elypso** fits seamlessly with your existing systems and is your best choice for instant card personalization.





Configuration on demand

- According to your needs, Elypso can print either single or dual sided cards.
- The printer can also be equipped with encoders for magnetic stripe and contact and contactless smart cards.





Perfect integration

- The software architecture of Evolis Premium SDK was designed to make Elypso fit seamlessly with your existing computer systems.
- Very compact (barely bigger than a standard letter size sheet of paper) and quiet, Elypso is discreet and has a small footprint.



Ease of use

- Thanks to Elypso's unique frontloading design, insertion and retrieval of cards make it easy to access even in tight spaces.
- With the Evolis Premium Suite® software you can receive notifications and easily control the printer from your computer.



ELYPSO

- Automatic ribbon recognition and set-up
- Easy handling
- USB connectivity
- Ethernet TCP/IP connectivity
- Optional reject tray

- Manual feeder: card to card printing
- LED control panel
- On-site configuration by adding specific modules
- All encoding options

Manual card feeder model with a color touch screen to interact with the printer



Main Features

General features

- · Direct-to-card dye-sublimation/ Resin thermal transfer
- · Edge-to-edge printing, singlesided, upgrade kit for dual-sided printing as an option
- · Standard 300 x 300 dpi resolution
- · Customizable 300 x 600 dpi resolution (color and monochrome printing) or 300 x 1200 dpi resolution (monochrome printing only)
- · 32 MB memory (RAM) standard optional 64 MB1

Printing performances²

- · Single side:
- Color (YMCKO): 20.2 s per card
- Monochrome: 6.5 s per card
- · Dual side (YMCKO-K): 27.3 s per card

Interfaces

- · USB (1.0, 1.1, 2.0, 3.0), cable supplied
- · Ethernet TCP-IP 10BaseT, 100BaseT (Traffic Led)
- · 802.11b/g wireless connection as an option

Card management and specifications

- · Manual feeder: card to card printing
- · Reject tray: 30 cards (0.76 mm -30 mil) as an option
- · Card thickness: 0.50 to 1.25 mm (20 to 50 mil), no gauge adjustment, case by case for the 0.25 mm/10 mil plastic cards
- · Card types: PVC cards, composite PVC cards, PET cards, ABS cards¹, special varnished cards¹
- · Card format: ISO CR80 ISO 7810 (53.98 mm x 85.60 mm)

Additional encoding modules

- · Available modules:
- Magnetic stripe encoder ISO 7811 HiCo/LoCo, JIS2
- Smart contact station ISO 7816-2
- Contact smart card encoder PC/ SC, EMV 2000-1
- Contactless smart card encoder -ISO 14443A, B, ISO15693, MIFARE, DESFire, HID iCLASS, UHF (standard compliance: EPC C1 Gen2 / ISO18000-6C ETSI EN 302 208 or FCC part 15.247)
- Other specific encoders upon request
- · Internal USB or IP ports
- · Options can be combined
- · Factory-installed or installed on site

Safety

- · Support for Kensington® security
- · Data encryption for magnetic encoding¹

Oisplay

- · Printer LEDs
- · Color touch screen as an option
- · Graphical notifications from the printer2: cleaning alerts, empty/low level ribbon alert, etc.

Evolis High Trust® ribbons

To maximise the quality and durability of printed cards, the lifespan of the print head and the overall printer reliability, use Evolis High Trust® ribbons.

- · Automatic identification and settina
- · Delivered in a drop-in cassette for easy handling
- · Ribbon saver for monochrome printing

List of ribbons available on www.evolis.com

© Software





- · Delivered with Evolis Premium Suite® for Windows®:
- Printer driver
- Evolis Print Center for printer administration and settings
- Evolis Printer Manager for graphical notification³
- 24/7 online support
- Compatible with Windows® (32/64 bits): XP SP3, Vista, W7, W8,
- · Delivered with a driver for Mac OS X (from 10.6)
- · Linux upon request
- · Evolis Premium SDK for remote supervision of the printer, while facilitating and speeding up integration into IT systems

© Eco-friendly design, certifications and statement of compliance

- · Standby, sleep modes & reduced energy consumption
- · CE, FCC, ICES, VCCI, CCC, KC, BIS
- · EAC4
- · RoHS


Size and weight

- · Size (H x W x D): 195 x 205 x 314 mm (7.68" x 8.07" x 12.36")
- · Weight: 2.95 kg (6.5 lbs)

Warranty

- · 1-year warranty (printer and print head)5
- · Warranty extension available as an option





A GLOBAL PROVIDER OF IDENTIFICATION SOLUTIONS

- Worldwide leader in card personalization systems for decentralized issuance
- International expertise and local support through a network of 400 distributors in 140 countries
- A unique ability to meet specific customer requirements with a Project department dedicated to design and construction of tailor-made solutions
- Evolis is ISO 9001 certified, which reflects our comprehensive approach, both in terms of quality and continuous improvement

www.evolis.com



Zapraszamy do kontaktu! Więcej informacji: www.kreski.pl

HQ / EUROPE - MIDDLE-EAST - AFRICA

Evolis - 14 avenue de la Fontaine - ZI Angers-Beaucouzé 49070 - Beaucouzé - FRANCE

T +33 (0) 241 367 606 - F +33 (0) 241 367 612 - info@evolis.com

LISA - CANADA

Evolis Inc. - Providence - RI - USA - evolisinc@evolis.com

LATIN AMERICA

Evolis Inc. - Fort Lauderdale - FL - USA - evolisinc@evolis.com

ASIA - PACIFIC

Evolis Asia Pte Ltd - Singapore - evolisasia@evolis.com

CHINA

Evolis China - Shanghai - evolischina@evolis.com

INDIA

Evolis India - Mumbai - evolisindia@evolis.com