

**ZONE 1  
CL I DIV 1****Remote Speaker  
Microphone****Push-To-Talk****ISM interface****IS-RSMG2.1**

The wired remote loudspeaker microphone is specially designed for PTT applications. With its robust but lightweight housing and the secure ISM interface, this device is an ideal addition to our mobile devices IS330.1 and IS530.1. The dynamic loudspeaker is specially designed for noisy environmental conditions.



# i.safe MOBILE

IS-RSMG2.1



ATEX approval: EX-Zone 1  
Ⓔ II 2G Ex ib IIC T4 Gb



IECEx approval: EX-Zone 1  
Ex ib IIC T4 Gb



NEC500 approval:  
Class I Division 1, Groups A B C D T4  
Intrinsically Safe

## TECHNICAL FEATURES

<b>Loudspeaker</b>	Dynamic   3-stage volume control Sensitivity: 93 dB (1 mW) Bandwidth: 50 Hz to 8 kHz
<b>Microphone</b>	Electret   Omni-Directional Sensitivity: -38 dB $\pm$ 3 dB (1 kHz) Bandwidth: 50 Hz to 16 kHz
<b>Measurement</b>	Size: 98,11 x 65,93 x 26,96 mm   Weight: 212 g
<b>Power supply</b>	Over the connected device
<b>Cable length</b>	flexible spiral cable from 48 to 130 cm
<b>Connection</b>	ISM interface
<b>Type of protection</b>	IP54   Operation range from -20 °C up to +60 °C

Zapraszamy do kontaktu!  
Więcej informacji: [www.kreski.pl](http://www.kreski.pl)

## SET CONTENT

Remote Speaker Microphone, Quick Start Manual and Safety Instructions

Please visit our website and you will find more detailed information, as well as an overview of compatible accessories.

[WWW.ISAFE-MOBILE.COM](http://WWW.ISAFE-MOBILE.COM)

EN