

The mobile multifunctional set consisting of a Trigger Handle (hand-held barcode scanner) and an industrial smartphone IS530.x is a flexible combination for reliable data acquisition in Ex areas. The HID-active, ready-to-use high-performance scanner captures any 1D or 2D barcodes at close range of up to 6 meters or distances of up to 18 meters via the reliable Zebra OEM imager scan engines. The data is further processed directly via the IS530.x smartphone connected via the ISM interface.

<sup>)</sup> All trademarks and copyrights are the properties of their respective owners. ) © 2022 by i.safe MOBILE GmbH | All rights reserved. | Misprints, errors and modifications excepted. | 1055MD01REV03\_EN\_12.2022





(IS-TH1xx.M1



ATEX approval: Mining
I M1 Ex ia op is I Ma
II 2G Ex ib op is IICT4 Gb
II 2D Ex ib op is IIICT135°C Db



IECEx approval: Mining Ex ia op is I Ma Ex ib op is IIC T4 Gb Ex ib op is IIIC T135°C Db

## **TECHNICAL FEATURES**

Weight  $MR = 380 \text{ g} \mid ER = 400 \text{ g} \text{ (without IS530)}$ 

**Size** 202 x 90,4 x 125 mm

Indication function Loudspeaker | Vibration | LED-Display

**Power supply** Over IS530 | this can be loaded in the handle

**Communication** Over the multi functional ISM interface of the IS530

**Type of protection** MIL-STD 810H | IP68 dust-/waterproof | usable from -20 °C to +60 °C

## **SCAN TYPES**

IS-TH1MR.M1 (mid range) with Zebra SE4750 MR | up to 6 m

IS-TH1ER.M1 (extended range) with Zebra SE4850 ER | up to 18 m



Zapraszamy do kontaktu! Więcej informacji: www.kreski.pl



**(** IS530.M1 **)** 



Android<sup>™</sup> 10



4,5" Gorilla Glass®
3. generation,
resolution 854 x 480 pixels



3600 mAh battery, replaceable, 3.8 V. 13.68 Wh



Bluetooth® 5



GSM 850/900/1800/ 1900 MHz WCDMA: UMTS B1/2/4/5/8 LTE-FDD: B1/2/3/4/5/7/8/12 with MFBI B13/14/17/20/25/ 26/28A/28B/29/30/66 LTE-TDD: B38/B39/B40/B41 TD-5CDMA: B34/B39



Qualcomm Snapdragon SDM660 Octa-Core Kryo Gold-Quad cores 2,2 GHz Kryo Silver-Quad cores 1,8 GHz 4 GB RAM 64 GB internal memory



2,4 GHz + 5 GHz: IEEE 802.11 a/b/g/n/ac/e/k/r/h with hotspot for max. 8 connections

The complete description you will find on our homepage: www.isafe-mobile.com